



Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer Name: Momentive performance material

260 Hudson River Rd Waterford NY 12188

Revised: 07/12/2012

Prepared by Product Regulatory Compliance

CHEMTREC 1-800-424-9300 **MSDS Contact** 1-888-443-9466

Information 4information@momentive.com

Chemical Family/Use: Silicone Rubber

Formula: Mixture

HMIS

Health: 1 Flammability: 1 Reactivity: 0

NFPA

Health: 1 Flammability: 1 Reactivity: 0

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION! Attention: Not for injection into humans.

Form: Liquid Form: White Odor: Faint

POTENTIAL HEALTH EFFECTS

INGESTION

May be harmful if swallowed.

SKIN

Skin irritation is possible after contact with the uncured product.

INHALATION

None known.

EYES

May cause eye irritation.

MEDICAL CONDITIONS AGGRAVATED

None known.



Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

SUBCHRONIC (TARGET ORGAN)

Respiratory System

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Dermal

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	CAS-No.	WGT. %
A. HAZARDOUS		
Silicic acid, ethyl ester	11099-06-2	1 - 5 %
B. NON-HAZARDOUS		
Siloxanes and Silicones, di-Me hydroxy terminated	70131-67-8	60 - 100 %
Calcium Carbonate	471-34-1	10 - 30 %

4. FIRST AID MEASURES

INGESTION

None known.

SKIN

Wash area with soap and water.

INHALATION

None known.

EYES

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

FLASH POINT: ca. 298 °C; 568 °F

METHOD Open Cup

IGNITION TEMPERATURE: 450 °C; 842 °F; Not applicable

FLAMMABLE LIMITS LEL:Not applicable
FLAMMABLE LIMITS UEL:
Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed. Avoid inhalation of vapors and spray mists. Avoid contact with skin and eyes. Use only in well-ventilated areas. Keep out of reach of children. May generate formaldehyde at temperatures greater than 150 C(300 F). See Section 8 of the MSDS for Personal Protective Equipment.

STORAGE

Keep container tightly closed. Keep out of the reach of children.



Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Eye wash facilities and emergency shower must be available when handling this product.; Use only in well-ventilated areas.

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

EYE AND FACE PROTECTION

Safety glasses with side shields

OTHER PROTECTIVE EQUIPMENT

None known.

Exposure Guidelines

Component	CAS-No.	Source	Value

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°C):

VAPOR PRESSURE (20 C) (MM HG):

VAPOR DENSITY (AIR=1):

FREEZING POINT:

No data available.

No data available.

No data available.

PHYSICAL STATE:

ODOR:

Color:

EVAPORATION RATE (BUTYL ACETATE=1):

SPECIFIC GRAVITY:

DENSITY:

Liquid

Faint

White

> 1

ca. 1.2

1.18 g/cm3

ACID / ALKALINITY (MEQ/G): No data available.



Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

pH: Not applicable SOLUBILITY IN WATER (20 C): Insoluble

SOLUBILITY IN ORGANIC SOLVENT (STATE Soluble in toluene xylene

SOLVENT):

VOLATILE ORGANIC CONTENT: 2 %(m) VOC EXCL. H2O & EXEMPTS (G/L): 6 g/l

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION.

Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Silicon dioxide.; Formaldehyde.; This product contains methylpolysiloxanes which will likely generate formaldehyde at approximately 300 degrees Fahrenheit (150'C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and has been classified by the National Toxicology Program as as a known human carcinogen. A MSDS for formaldehyde is available from Momentive. See Section 11 for additional information on formaldehyde.

INCOMPATIBLE MATERIALS

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: No data available.

CARCINOGENICITY

The National Toxicology Program (NTP) classifies formaldehyde as "known to be a human carcinogen" with respect to nasopharyngeal cancer, sinonasal cancer and myeloid leukemia. The International Agency for Research on Cancer (IARC) classifies formaldehyde as "carcinogenic to humans". U.S. OSHA regulates formaldehyde as a potential human carcinogen. See the OSHA Formaldehyde Workplace Standard at 29 CFR 1920.1048 (the "OSHA Standard"). Safe handling and use instructions are provided in this MSDS and in the OSHA Standard. OSHA has identified 0.5 ppm, calculated as an eight-hour time-weighted average ("TWA") concentration, as the "Action Level". Please review and understand the guidance contained in this MSDS, and refer to the OSHA Standard for regulatory requirements that might be applicable to your operation and use. Many studies and other evaluations

MOMENTIVE

MATERIAL SAFETY DATA SHEET

Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

have been performed concerning formaldehyde's potential to cause cancer. To review some of these studies and for further information go to www.osha.gov; http://monographs.iarc.fr; http://ntp-server.niehs.nih.gov; http://epa.gov; http://www.nap.edu and other authoritative websites then search on formaldehyde.

ACUTE DERMAL

Remarks: No data available.

ACUTE INHALATION

Remarks: No data available.

OTHER

None.

SENSITIZATION

No data available.

SKIN IRRITATION.

No data available.

EYE IRRITATION

No data available.

MUTAGENICITY

No data available.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

No data available.

DISTRIBUTION

No data available.

CHEMICAL FATE

No data available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Disposal should be made in accordance with federal, state and local regulations.



Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

14. TRANSPORT INFORMATION

Further Information: This product is not regarded as dangerous goods according to the national

and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Australia Inventory of Chemical y (positive listing)

Substances (AICS)

EU list of existing chemical y (positive listing)

substances

Japan Inventory of Existing & New y (positive listing)

Chemical Substances (ENCS)

China Inventory of Existing y (positive listing)

Chemical Substances

Korea Existing Chemicals y (positive listing)

Inventory (KECI)

Canada DSL Inventory y (positive listing)
Canada NDSL Inventory n (Negative listing)
Philippines Inventory of Chemicals y (positive listing)

and Chemical Substances

(PICCS)

TSCA list y (positive listing) On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

CERCLAReportable quantity 111857 lbs **PRODUCT COMPOSITION**Ethanol

64-17-5

CERCLA Reportable Quantity
Reportable quantity: 100 LBS

SARA (311,312) HAZARD CLASS

Acute Health Hazard

CALIFORNIA PROPOSITION 65

Warning! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Canadian Regulatory Information

WHMIS CLASSIFICATION



Version: 1.6 07/12/2012

RTV11 001 SILICONE RUBBER COMPOUND

D2B - Toxic Material Causing Other Toxic Effects

Other

SCHDLE B/HTSUS: 3910.00.0000 Silicones in primary forms

ECCN: EAR99

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit NEGL = negligible
EST = estimated NF = none found
NA = not applicable UNKN = unknown
NE = none established REC = recommended

ND = none determined V = recommended by vendor

SKN = skin TS = trade secret R = recommended MST = mist

NT = not tested STEL = short term exposure limit

ppm = parts per million ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).