



SDS Number: Page 1 of 7

UL54190 Part A RESIN

Revision No.: 2 Revision Date:03/20/2020

Section 1 IDENTIFICATION

Product Name: UL54190 Part A RESIN

Manufacturer: Chemical Concepts

410 Pike Road Huntingdon Valley, PA. 19006 Phone: 800.220.1966 Email: sales@chemical-concepts.com Website: www.chemical-concepts.com Information department: Environment protection department.

Materials Uses: Epoxy RESIN used with an Epoxy Hardener (Part B) to Bond Various Substrates. In Case of Emergency Contact: INFOTRAC: 800-535-1035

Section 2 HAZARD IDENTIFICATION

GHS Classification:

CATEGORY	SIGNAL WORD	HAZARD STATEMENT(S)
Health Skin Corrosion/Irritation, Category 2 Eye Irritation, Category 2A Skin Sensitization, Category 1 STOT SE, Category 3	WARNING WARNING WARNING WARNING	H315 – Causes skin irritation H319 – Causes serious eye irritation H317 – May cause an allergic skin reaction H335 – May cause respiratory irritation
		<u>.</u>

GHS Precaution Statements:

Prevention:

- P261 Avoid breathing dust/fume/mist/vapors/spray.
- P264 Wash hands (or other affected skin surfaces) thoroughly after handling.
- P270 Do not eat, drink, or smoke when using this product.
- P273 Avoid release to the environment
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301/P312 – IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

P302/P352 – IF ON SKIN: Wash with plenty of soap and water.

P333/P313 – If skin irritation or rash occurs get medical advice/attention.





SDS Number: Page 2 of 7

UL54190 Part A RESIN

Revision No.: 2 Revision Date:03/20/2020

Storage:

P403 - Store in a well-ventilated place.

P410 – Protect from sunlight.

P411 – Store at temperatures not exceeding 25°C (75°F).

Disposal:

P501 – Dispose of contents/containers in accordance with local/regional/national/international regulations.

Route of Entry: Eye contact, skin contact, inhalation, and ingestion.


Target Organs: Skin, eyes, respiratory tract, digestive tract, liver, kidney, olfactory and Central Nervous System (CNS).

Skin Contact: May cause irritation of the skin. Prolonged exposure may cause sensitization. Preexisting skin conditions may be aggravated by exposure to this material.

Eye Contact: May cause irritation and/or sensitization.

Respiratory Contact: Respiratory tract irritant. Prolonged exposure may result in dizziness, nausea, headache, and anesthetic effects. May cause sensitization. Preexisting respiratory conditions may be aggravated by exposure to this product. May cause CNS depression.

Ingestion: Call a physician or poison control center immediately. If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. If vomiting occurs, the head should be kept low so that the stomach vomit doesn't enter the lungs.



Section 3 COMPOSITION / INFORMATION ON INGREDIENTS

Name: Mixtures, Adhesives Bisphenol A Epoxy Resin Non-hazardous Ingredients
 CAS #
 % by Weight

 25068-38-6
 80 - 100%

 Not Applicable < 10%</td>

Section 4 FIRST-AID MEASURES

Skin: Remove contaminated clothing. Flush skin with water, then wash affected areas with soap and water. If irritation develops, seek medical attention. Wash or dispose of clothing before reuse.

Eye: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush if possible. Seek immediate medical attention.

Respiratory: Loosen clothing as necessary and position individual in a comfortable position. Move exposed to fresh air. Give artificial respiration if necessary. If breathing is difficult give oxygen. Immediately get medical assistance.





SDS Number: Page 3 of 7

UL54190 Part A RESIN

Revision No.: 2 Revision Date:03/20/2020

Ingestion: Give patient water to dilute material in stomach. DO NOT induce vomiting. Seek immediate medical attention. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration. DO NOT give anything by mouth to an unconscious person.

Section 5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: In case of fire, water spray, fog, dry chemical or CO₂, or alcohol resistant foam.
 Specific Hazards Arising from the Chemical: Fire may produce irritating, corrosive and/or toxic gases.
 Hazardous Thermal: Decomposition products may include the following materials: Carbon dioxide, carbon monoxide, halogenated compounds.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, and rubber boots. In enclosed spaces, use self-contained breathing apparatus (SCBA) and protective clothing.

Flammability Classification: Combustible, Class IIIB estimated.

Risk of Explosion due to Mechanical Impact: Not Applicable.

Risk of Explosion due to Static Discharge: Not Applicable.

Autoignition Temp.: Not Available

LEL: Not Available

UEL: Not Available

Section 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Keep unnecessary personnel away. Avoid contact with skin or inhalation of spillage, dust or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Eliminate all sources of ignition. For large spill or leak wear self-contained breathing apparatus (SCBA) and appropriate PPE.

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid releases to the environment. Retain and dispose of contaminated was water. Keep out of sewers and drains. Contact local authorities if case of spillage to drain/aquatic environment.

Clean-Up Methods and Materials: Absorb with an inert material and place in an appropriate container for disposal.

Section 7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing vapors. Use in a well-ventilated area. Wear rubber gloves (nitrile or butyl) and chemical resistant apron. Wear chemical splash goggles. Do not reuse empty containers.

Storage Precautions: Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well ventilated area.

Section 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters and Exposures:

Material Name: Bisphenol A Epoxy Resin (CAS: 25068-38-6) Exposure Limits: None

Engineering Controls: Provide adequate ventilation (general or local exhaust). Ensure that a working eyewash and safety shower are in the work area. **Individual Protection Measures and PPE:**





SDS Number: Page 4 of 7

UL54190 Part A RESIN

Revision No.: 2 Revision Date:03/20/2020

Eye / Face Protection: Wear safety glasses with side shields or splash goggles.

Skin Protection: Chemical resistant gloves (nitrile or butyl) and chemical resistant apron are recommended. **Respiratory Protection** In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Thermal Hazards: None.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

	Part A RESIN
Appearance:	Viscous Liquid
Color:	Clear
Odor:	Not Available
Odor Threshold:	Not Available
pH:	Not Available
Melting Point / Freezing Point:	Not Available
Initial Boiling Point:	260°C (500°F)
Flash Point and Method:	Pensky-Martens Closed Cup: 251°C (>484°F) (ASTM D 93)
Flammability:	Not Available
Lower Explosion Limit:	Not Available
Upper Explosion Limit:	Not Available
Vapor Pressure:	.03 mm Hg @ 77ºC (171ºF)
Vapor Density:	Not Available
Relative Density:	1.17 (9.7 lbs./gallon)
Solubility in Water:	Negligible
Partition Coefficient (n-Octanol in Water):	Not Available
Auto-Ignition Temperature:	Not Available
Decomposition Temperature:	Not Available
Viscosity (Dynamic CPS/mPa-s):	8,000 to 10,000 CPS
Percent Volatile:	Not Available
Specific Gravity:	1.17

Section 10 STABILITY AND REACTIVITY

Reactivity: Product is stable under normal conditions.

Chemical Stability: The product is stable.

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid: Avoid exposure – obtain special instructions before use. Avoid all possible sources of ignition (spark or flame).

Materials to Avoid (Incompatibility): strong oxidizing materials, strong acids, strong alkalis.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other hazards: Reacts with considerable heat release with some curing agents.

Section 11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:





SDS Number: Page 5 of 7

UL54190 Part A RESIN

Revision No.: 2 Revision Date:03/20/2020

Bisphenol A Epoxy Resin (CAS: 25068-38-6)

LD50 = 11,400 mg/kg (oral, rat) LD50 = 2,000 mg/kg (dermal, rat) Not Available

Acute Toxicity to Humans: This product has not been tested for human effects. No additional information. Chronic Toxicity to Animals: This product has not been tested for animal effects. No additional information. Chronic Toxicity to Humans: This product has not been tested for human effects. No additional information.

Irritation/Corrosion:

Conclusion/Summary:

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bisphenol A Epoxy Resin (CAS: 25068-38-6)	Skin – Erythema/Eschar 404 Acute Dermal Irritation/Corrosion	Rabbit	1.5 – 2		
	Skin – Edema 404 Acute Dermal Irritation/Corrosion	Rabbit	1.0 – 1.5		
	Eyes – 405 Acute Eye Irritation/Corrosion	Rabbit	0		
	Eyes – Redness of the Conjunctivae	Rabbit	0.7		
	Skin – Moderate Irritation	Rabbit		24 hours	
	Skin – Severe Irritant	Rabbit		24 hours	
	Eyes – Mild Irritant	Rabbit			

Eye Damage / Irritation: Not Available.

Respiratory Sensitization: Not Available.

Skin Sensitization: Not Available.

Ingestion: Not Available.

Mutagenicity: Not Available.

Carcinogenicity: Not Available.

Reproductive Toxicity: Not Available.

Teratogenic Effects: Not Available.

STOST- Single Exposure:

Product/ingredient name	Category	Route of Exposure	Target Organ
Bisphenol A Epoxy Resin (CAS 26068-38-6)	Category 3		

STOST – Repeated Exposure: Not Available.

Aspiration Hazard: Not Available

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity: This product contains components that may be toxic to aquatic organisms and may cause long term adverse effects in an aquatic environment.

Product/ingredient name	Result	Species	Exposure
Bisphenol A Epoxy Resin (CAS 25068-38-6)	Acute LC50 1.3 mg/l - 203 Fish, Acute Toxicity Test	Fish - Fish	96 hour
	Acute EC50 2.1 mg/l - 202 Daphnia sp. Acute Immobilization Test and Reproductive Test	Aquatic invertebrates. Water Flea	48 hour
	Acute No-observable-effect-concentration 0.3 mg/l – 211 Daphnia Magna Reproduction Test	Aquatic invertebrates. Water Flea	21 day
	Acute LC50 > 11 mg/l	Aquatic plants - Algae	72 hour

Persistence and Degradability: Not Available.





UL54190 Part A RESIN

Revision No.: 2 Revision Date:03/20/2020

Bioaccumulative Potential:

SDS Number:

Page 6 of 7

Product/ingredient name	LogPow	BCF	Potential
Bisphenol A Epoxy Resin (CAS 26068-38-6)	2.64 - 3.78	3 – 31 31.00	Low

Mobility in Soil: Not Available.

Other Adverse Effects: No known significant effects or critical hazards.

	Section 13	DISPOSAL CONSIDERATIONS	
--	------------	-------------------------	--

Disposal Methods:

Part A RESIN: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recycle-able products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14 TRANSPORT INFORMATION

CFR: Not Regulated TDG: Not Regulated DOT Classification: Not Regulated IATA: IMO: Marine Pollutant: YES

Section 15 REGULATORY INFORMATION

U.S. Federal Regulations United States – TSCA 12(b) – Chemical export notification: None required. United States – TSCA 5(a)2 – Final significant new use rules: Not listed. United States – TSCA 5(a)2 – Proposed significant new use rules: Not listed. United States – TSCA 5(e) – Substances consent order: Not listed. SARA 311/312 Chemical: Yes Classification Hazard Categories: Immediate (acute) health hazard

SARA 313 (TRI reporting)Not regulated.Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPS) List:Not regulated.Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):Not regulated.Safe Drinking Water Act (SDWA):Not regulated.

State Regulations

California Proposition 65:

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. **WARNING:** This product contains less than







SDS Number: Page 7 of 7

UL54190 Part A RESIN

Revision No.: 2 Revision Date:03/20/2020

1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Oxirane, 2-(phenoxymethyl)-	Yes	No	5 µg/day	No
Phenol, 4,4'-(1-methylethylidene)bis-	No	Yes	No	No

TSCA (Toxic Substances Control Act): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory Requirements.

International Regulations:

DSL (Canada Domestic Substance List): All components of this product are on the DSL (Canada Domestic Substance List) or are exempt from DSL.

EINECS: Not Available.

WHMIS: B2, C, D2B.

Section 16 OTHER INFORMATION

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF SDS DOCUMENT







SDS Number: Page 1 of 6

UL54190 Part B Hardener

Revision No.: 2 Revision Date:03/02/2020

Section 1 IDENTIFICATION

Product Name: UL54190 Part B Hardener

Manufacturer: Chemical Concepts

410 Pike Road Huntingdon Valley, PA. 19006 Phone: 800.220.1966 Email: sales@chemical-concepts.com Website: www.chemical-concepts.com Information department: Environment protection department.

Materials Uses: Epoxy RESIN used with an Epoxy Hardener (Part B) to Bond Various Substrates. In Case of Emergency Contact: INFOTRAC: 800-535-1035

Section 2 HAZARD IDENTIFICATION

GHS Classification:

CATEGORY	SIGNAL WORD	HAZARD STATEMENT(S)
Health Skin Irritation, Category 2 Eye Irritation, Category 2A Skin Sensitization, Category 1A	DANGER WARNING WARNING	H315 – Causes skin irritation H319 – Causes serious eye irritation H317 – May cause an allergic skin reaction

GHS Precaution Statements:

Prevention:

P261 – Avoid breathing dust/fume/mist/vapors/spray.

- P264 Wash hands (or other affected skin surfaces) thoroughly after handling.
- P270 Do not eat, drink, or smoke when using this product.
- P273 Avoid release to the environment
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301/P312 – IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

P302/P352 - IF ON SKIN: Wash with plenty of soap and water.

P333/P313 – If skin irritation or rash occurs get medical advice/attention.

Storage:



SAFETY DATA SHEET SD.S



SDS Number: Page 2 of 6

UL54190 Part B Hardener

Revision No.: 2 Revision Date:03/02/2020

P403 - Store in a well-ventilated place.

P410 – Protect from sunlight.

P411 – Store at temperatures not exceeding 25°C (75°F).

Disposal:

P501 – Dispose of contents/containers in accordance with local/regional/national/international regulations. **Route of Entry:** Eye contact, skin contact, inhalation, and ingestion.


Target Organs: Skin, eyes, respiratory tract, digestive tract, liver, kidney, olfactory and Central Nervous System (CNS).

Skin Contact: May cause irritation of the skin. Prolonged exposure may cause sensitization. Preexisting skin conditions may be aggravated by exposure to this material.

Eye Contact: May cause irritation and/or sensitization.

Respiratory Contact: Respiratory tract irritant. Prolonged exposure may result in dizziness, nausea, headache, and anesthetic effects. May cause sensitization. Preexisting respiratory conditions may be aggravated by exposure to this product. May cause CNS depression.

Ingestion: Not an expected route of entry. If ingested it may cause irritation to the gastrointestinal tract.



Section 3 COMPOSITION / INFORMATION ON INGREDIENTS

Name: Mixtures, Adhesives	CAS #	% by Weight
Polyamide	Proprietary	20% to 60%
Hydrogenated Terphenyl	61788-32-7	1% to 10%
Amino Esters	Proprietary	1% to 10%
Amino Esters	Fiophetary	1 /0 10 10 /0

Section 4 FIRST-AID MEASURES

Skin: Remove contaminated clothing. Flush skin with water, then wash affected areas with soap and water. If irritation develops, seek medical attention. Wash or dispose of clothing before reuse.

- **Eye:** Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush if possible. Seek immediate medical attention.
- **Respiratory:** Remove patient to fresh air. If patient is having difficulty breathing, seek immediate medical attention. If not breathing, clear airway and start mouth-to-mouth artificial respiration (or use bag-mask respirator). Seek immediate medical attention.
- **Ingestion:** Give patient water to dilute material in stomach. DO NOT induce vomiting. Seek immediate medical attention. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration. DO NOT give anything by mouth to an unconscious person.

Section 5 FIRE-FIGHTING MEASURES







SDS Number: Page 3 of 6

UL54190 Part B Hardener

Revision No.: 2 Revision Date:03/02/2020

Suitable Extinguishing Media: In case of fire, use dry chemical or CO₂. Water spray may cause frothing.
 Specific Hazards Arising from the Chemical: Sealed containers of adhesive may rupture violently at elevated temperatures due to polymerization.

Special Protective Equipment and Precautions for Firefighters: Use self-contained breathing apparatus (SCBA) and protective clothing.

Flash Point and Method: 193°F (93°C). Tag Closed Cup.

Flammability Classification: Not Determined.

Risk of Explosion due to Mechanical Impact: Not Applicable.

Risk of Explosion due to Static Discharge: Not Applicable.

Hazardous Products of Combustion: Carbon Oxides (CO and CO₂), and various Hydrocarbons.

Autoignition Temp.: 703°F (373°C).

LEL: Not Determined.

UEL: Not Determined.

Section 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: For large spill or leak wear selfcontained breathing apparatus (SCBA) and appropriate PPE.

Environmental Precautions: Keep out of sewers and drains.

Clean-Up Methods and Materials: Absorb with an inert material and place in an appropriate container for disposal.

Section 7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing vapors. Use in a well-ventilated area. Wear rubber gloves (nitrile or butyl) and chemical resistant apron. Wear chemical splash goggles. Do not reuse empty containers.

Storage Precautions: Store in a cool, dry, well-ventilated area at temperatures less than 75°F (25°C). Storage above 212°F (100°C) may cause explosive decomposition. Avoid storage in direct sunlight. Keep containers closed when not in use. Keep away from heat sources, sparks, and open flames.

Section 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters and Exposures:

Material Name:Exposure Limits:Hydrogenated Terphenyl (CAS 61788-32-7):OSHA PEL:TWA 0.5 PPMSTEL 0.5 PPM

Engineering Controls: Provide adequate explosion proof ventilation (general or local exhaust). Ensure that a working eyewash and safety shower are in the work area.

Individual Protection Measures and PPE:

Eye / Face Protection: Wear safety glasses with side shields or splash goggles.

Skin Protection: Chemical resistant gloves (nitrile or butyl) and chemical resistant apron are recommended. **Respiratory Protection** In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Thermal Hazards: None.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES





SDS Number: Page 4 of 6

UL54190 Part B Hardener

Revision No.: 2 Revision Date:03/02/2020

	Part B Hardener
Appearance:	Black Paste
Odor:	Characteristic
Odor Threshold:	Not Available
pH:	Not Determined.
Melting Point / Freezing Point:	Not Determined.
Initial Boiling Point:	430°F (221°C)
Flash Point and Method:	199°F (93°C) Tag Closed Cup
Evaporation Rate:	Not Available.
Flammability:	Not Available.
Lower Explosion Limit:	Not Determined.
Upper Explosion Limit:	Not Determined.
Vapor Pressure:	Not Determined.
Vapor Density:	Not Determined.
Relative Density:	10.4 – 11.2 lbs./gallon
Solubility(ies):	Not Available
Partition Coefficient (n-Octanol in Water):	Not Applicable
Auto-Ignition Temperature:	703°F (373°C)
Decomposition Temperature:	Not Available
Viscosity (Dynamic CPS/mPa-s):	50K – 100K
Percent Volatile:	Not Available
Specific Gravity:	1.25 – 1.35 g/cm ³
VOC:	Not Determined.

Section 10 STABILITY AND REACTIVITY

Reactivity: Product is stable as supplied and when used as intended.

Chemical Stability: Not Available.

Possibility of Hazardous Reactions: No dangerous reactions known.

Conditions to Avoid: Avoid extreme temperatures. Avoid freezing.

Materials to Avoid (Incompatibility): Oxidizing agents.

Hazardous Decomposition Products: Carbon Oxides (CO, CO₂), and various Hydrocarbons.

Section 11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals: Not Available.

Acute Toxicity to Humans: This product has not been tested for human effects. No additional information. Chronic Toxicity to Animals: This product has not been tested for animal effects. No additional information. Chronic Toxicity to Humans: This product has not been tested for human effects. No additional information. Skin Corrosion / Irritation: Not Available.

Eye Damage / Irritation: Not Available.

Respiratory Sensitization: Not Available.

Skin Sensitization: Not Available.

Mutagenicity: Classifiable as "none" for human.

Carcinogenicity: Not classifiable for human or animal.

Reproductive Toxicity: Not Available.

Teratogenic Effects: Classifiable as "none" for human.







SDS Number: Page 5 of 6

UL54190 Part B Hardener

Revision No.: 2 Revision Date:03/02/2020

STOST- Single Exposure: Not Available. STOST – Repeated Exposure: Not Available.

Aspiration Hazard: Not Available.

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity: Not Available. Persistence and Degradability: Not Available. Bioaccumulative Potential: Not Available. Mobility in Soil: Not Available. Other Adverse Effects: Not Available.

Section 13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Part B Hardener: Dispose of in accordance with Federal, State, and local regulations.

Section 14 TRANSPORT INFORMATION

UN Number: Not Regulated.

UN Proper Shipping Name: Not Regulated. Transport Hazard Class: Not Regulated. Packing Group: Not Regulated. DOT Classification: Not Regulated. Special Provision for Transport: Not Regulated. ADR / RID Classification: Not Regulated. ICAO/IATA Classification: Not Regulated. IMO/IMDG Classification: Not Regulated. Marine Pollutant: No additional information.

Section 15 REGULATORY INFORMATION

U.S. Federal Regulations

Chemical (& CAS Number)	SARA 302 (EHS)TPQ	SARA 313 de minimis	CAA 112(r) TQ	RCRA Code
None of the ingredients are listed.				

All quantities in pounds.

State Regulations

Chemical (& CAS Number)	CA	MA	MN	NJ	PA	RI
	Prop 65	RTK	RTK	RTK	RTK	RTK
None of the Ingredients are listed.						

TSCA (Toxic Substances Control Act): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory Requirements.

International Regulations:







SDS Number: Page 6 of 6

UL54190 Part B Hardener

Revision No.: 2 Revision Date:03/02/2020

DSL (Canada Domestic Substance List): All components of this product are on the DSL (Canada Domestic Substance List) or are exempt from DSL.

EINECS: Not Available. **WHMIS:** B2, C, D2B.

Section 16 OTHER INFORMATION

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF SDS DOCUMENT

