

Safety Data Sheet
acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

1 Identification

- **Product identifier**
- **Trade name: Quick Tac 2-Acetone Based-CAA Aerosol**
- **Relevant identified uses of the substance or mixture.**
Adhesive
Activator
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Adhesive Systems, Inc.
A Division of Royal Adhesives & Sealants, LLC
9411 Corsair Road
Frankfort, Illinois 60423
Phone Number: 800-552-0299
- **Information department: Environment protection department.**

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS06



GHS07



GHS08

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 1)

- **Signal word** *Danger*

- **Hazard statements**

Extremely flammable aerosol. Pressurized container: May burst if heated.

Toxic in contact with skin.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not spray on an open flame or other ignition source.

Wear protective gloves / protective clothing.

Wear eye protection / face protection.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 1

- **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 4

Physical Hazard = 1

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture

- **Hazardous components:**

67-64-1 acetone	50-100%
-----------------	---------

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 2)

74-98-6	propane	10-25%
106-97-8	butane (containing $\geq 0,1$ % butadiene (203-450-8))	2.5-10%
99-97-8	N,N-dimethyl-p-toluidine	$\leq 1.0\%$

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Call a doctor immediately.
Overexposure, remove to fresh air and seek medical attention.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
Extremely flammable aerosol.
Contents under pressure. Pressurized container may explode when exposed to heat or flame. During a fire hazardous gases may be formed.
- **Advice for firefighters**
Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Use only in well ventilated areas.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Empty containers may contain hazardous residuals. Keep away from heat, sparks and open flame. DO NOT cut, drill, puncture, weld or grind on or near full, partially full or empty product containers.
Store in a cool location away from direct heat.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**
Store as flammable liquid.
Keep away from open flames and high temperatures.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
DO NOT expose to heat or temperatures above 50C (122F)
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm
	Long-term value: 594 mg/m ³ , 250 ppm
BEI	

74-98-6 propane

PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F in TLVs & BEIs book; NIC-EX

106-97-8 butane (containing ≥0,1 % butadiene (203-450-8))

REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV	Short-term value: (2370) mg/m ³ , (1000) ppm
	NIC-EX

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 4)

99-97-8 N,N-dimethyl-p-toluidine

WEEL Long-term value: 0.5 ppm

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

Safety glasses with side shields or tightly sealed goggles. Selection of eye protection is based on how the product will be used.

· **Body protection:**

Protective work clothing

Emergency showers and eye wash stations should be available.

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Compressed gas

Color: Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 5)

· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point:	Undetermined.
Boiling point:	Not applicable, as aerosol.
· Flash point:	<-18 °C (<-0 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	365 °C (689 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Flammable limits:	
Lower:	1.7 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	8300 hPa (6226 mm Hg)
· Specific gravity at 20 °C (68 °F):	0.692 g/cm ³ (5.775 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.0 %
Solids content:	Not available
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No further information is available.
- **Conditions to avoid** Heat, flames, sparks, hot surfaces, ignition sources.
- **Incompatible materials:** Reacts with oxidizing agents.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

USA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** May irritate the skin.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:** May cause organ damage through prolonged or repeated exposure.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:** At present there are no ecotoxicological assessments.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 7)

14 Transport information

· UN-Number	UN1950
· DOT, IMDG, IATA	
· UN proper shipping name	
· DOT	Aerosols, flammable
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· Transport hazard class(es)	
· DOT	
	
· Class	2.1
· Label	2.1
· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· Packing group	
· DOT, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Gases
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Product may be shipped as a Limited Quantity. Until 12/31/2020, the Consumer Commodity, ORM-D, may be used in place of the limited quantity diamond label for packages of UN 1950 Aerosols.
· DOT	Limited Quantity
· IMDG	Limited Quantity

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 8)

· IATA	Limited Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· **Proposition 65**

· **Chemicals known to cause cancer:**

99-97-8 | N,N-dimethyl-p-toluidine

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· **New Jersey Right-to-Know List:**

67-64-1	acetone
74-98-6	propane
106-97-8	butane (containing $\geq 0,1$ % butadiene (203-450-8))

· **New Jersey Special Hazardous Substance List:**

67-64-1	acetone	F3
74-98-6	propane	F4
106-97-8	butane (containing $\geq 0,1$ % butadiene (203-450-8))	F4

· **Pennsylvania Right-to-Know List:**

67-64-1	acetone
74-98-6	propane
106-97-8	butane (containing $\geq 0,1$ % butadiene (203-450-8))

· **Pennsylvania Special Hazardous Substance List:**

67-64-1	acetone	E
---------	---------	---

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
---------	---------	---

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 11/17/2016

Revision Number 1

Revision Date 11/17/2016

Trade name: Quick Tac 2-Acetone Based-CAA Aerosol

(Contd. of page 9)

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **Department issuing SDS:** Environment protection department.

· **Creation Date:** 11/17/2016

· **Date of preparation / last revision** 11/17/2016 / -

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Acute Tox. 3: Acute toxicity – Category 3

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2