Permatex.

SAFETY DATA SHEET



Revision Date 21-Apr-2016

1. IDENTIFICATION

Product identifier

Product Name ULTRA BLACK GASKET MAKER 8.75OZ AE

Other means of identification

Product Code 82080 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

ITW Permatex Canada
6875 Parkland Blvd. 35 Brownridge Road, Unit 1
Solon, OH 44139 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Serious eye damage/eye irritation | Category 2A |
|-----------------------------------|----------------|
| Skin sensitization | Category 1 |
| Carcinogenicity | Category 2 |
| Gases under pressure | Compressed gas |

Label elements

Emergency Overview

Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer

Contains gas under pressure; may explode if heated



Appearance Black Physical state Paste Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

27.18 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

| Chemical Name | CAS No | Weight-% | Trade Secret |
|------------------------------------|------------|----------|--------------|
| SYNTHETIC ISOPARAFFINIC HYDROCARON | 64742-47-8 | 3 - 7 | * |
| NITROGEN | 7727-37-9 | 1 - 5 | * |
| STEARIC ACID | 57-11-4 | 1 - 5 | * |
| 2-BUTANONE OXIME | 96-29-7 | 1 - 5 | * |
| ALUMINIUM POWDER | 7429-90-5 | 0.1 - 1 | * |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

ΑE

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aiderUse personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required. Contents under pressure. Do not puncture

or incinerate cans.

Environmental precautions

Environmental precautionsDo not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

Revision Date 21-Apr-2016

AL CONTRACTOR OF THE CONTRACTO

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if

walked on.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Use personal protective equipment as required. Contents under pressure. Do

not puncture or incinerate cans.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from

moisture.

Incompatible materials Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|------------------|----------------------------------|--|-----------------------------|
| ALUMINIUM POWDER | TWA: 1 mg/m³ respirable fraction | TWA: 15 mg/m³ total dust | TWA: 5 mg/m ³ Al |
| 7429-90-5 | | TWA: 5 mg/m ³ respirable fraction | - |
| | | (vacated) TWA: 5 mg/m ³ Al | |
| | | Aluminum | |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

ΑE

Remarks • Method

Polymerization

Polymerization

Air = 1

Physical state Paste **Appearance** Black Odor Mild

Odor threshold No information available

Property Values

No information available pН No information available Melting point / freezing point

Boiling point / boiling range Not Applicable Flash point > 93 °C / > 200 °F **Evaporation rate** No information available

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available

Vapor pressure <5 mmHa Vapor density >1

Relative density 1.44

Water solubility Not applicable

Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity **Dynamic viscosity** No information available No information available **Explosive properties Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 3.1%, 44.75 g/l

No information available Density No information available **Bulk density**

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides

Nitrogen oxides (NOx)

Formaldehyde

May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion Ingestion may cause irritation to mucous membranes.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|-------------------|----------------------|---------------------|
| SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8 | > 5000 mg/kg(Rat) | > 2000 mg/kg(Rabbit) | > 5.2 mg/L (Rat)4 h |
| STEARIC ACID 57-11-4 | - | > 5 g/kg(Rabbit) | - |
| 2-BUTANONE OXIME 96-29-7 | = 930 mg/kg(Rat) | = 0.2 mg/kg(Rabbit) | = 20 mg/L (Rat)4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available. **Germ cell mutagenicity**No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 10362 mg/kg ATEmix (dermal) 8801 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

92.76 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|-------------------------|----------------------------------|------------------------------------|------------------------------|
| SYNTHETIC ISOPARAFFINIC | - | 45: 96 h Pimephales promelas mg/L | 4720: 96 h Den-dronereides |
| HYDROCARON | | LC50 flow-through 2.2: 96 h | heteropoda mg/L LC50 |
| 64742-47-8 | | Lepomis macrochirus mg/L LC50 | |
| | | static 2.4: 96 h Oncorhynchus | |
| | | mykiss mg/L LC50 static | |
| 2-BUTANONE OXIME | 83: 72 h Desmodesmus subspicatus | 777 - 914: 96 h Pimephales | 750: 48 h Daphnia magna mg/L |
| 96-29-7 | mg/L EC50 | promelas mg/L LC50 flow-through | EC50 |
| | | 760: 96 h Poecilia reticulata mg/L | |
| | | LC50 static 320 - 1000: 96 h | |
| | | Leuciscus idus mg/L LC50 static | |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

82080 - ULTRA BLACK GASKET MAKER 8.750Z

ΑE

No information available.

| Chemical Name | Partition coefficient | |
|------------------|-----------------------|--|
| 2-BUTANONE OXIME | 0.65 | |
| 96-29-7 | | |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status | |
|------------------|-----------------------------------|--|
| ALUMINIUM POWDER | Ignitable powder | |
| 7429-90-5 | | |

14. TRANSPORT INFORMATION

DOT

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.2 Emergency Response Guide 126

Number

<u>IATA</u>

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

<u>IMDG</u>

UN/ID no 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.2 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Not Listed. **ENCS** Not Listed. Complies **IECSC** Complies **KECL PICCS** Complies Complies **AICS**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 | |
|--------------------------|---------------------------|--|
| CARBON BLACK - 1333-86-4 | Carcinogen | |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|------------------|------------|---------------|--------------|
| LIMESTONE | X | X | X |
| 1317-65-3 | | | |
| NITROGEN | X | X | X |
| 7727-37-9 | | | |
| ALUMINIUM POWDER | X | X | X |
| 7429-90-5 | | | |
| CARBON BLACK | X | X | X |
| 1333-86-4 | | | |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

82080 - ULTRA BLACK GASKET MAKER 8.750Z AE Revision Date 21-Apr-2016

NFPA Health hazards 2 Flammability 1 Instability 0

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 21-Apr-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet