

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: PERMATEX® Large Diameter Threadlocker Red - 250 ml

bottle

Product Code: 27725 Stock No.: 27725

Manufacturer Name: Permatex, Inc.

Address: 10 Columbus Blvd.
Hartford, CT 06106

USA


General Phone Number: 1-87-Permatex, (877) 376-2839

Emergency Phone Number: 800-255-3924

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300 Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

MSDS Creation Date: September 20, 2010
MSDS Revision Date: September 28, 2010

MSDS Format: According to ANSI Z400.1-2004



NFPA



* Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Polyethylene glycol dimethacrylate	25852-47-5	40 - 70 by weight
Monomer-free Polyester Resin	No data	10 - 20 by weight
Cumene hydroperoxide	80-15-9	<3 by weight

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: CAUTION! Harmful. Irritant.

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: Can cause moderate irritation, burning sensation, tearing, redness, and

swelling. Overexposure may cause lacrimation, conjunctivitis, corneal

damage and permanent injury.

Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and

swelling.

Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache,

and anesthetic effects.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and

gastrointestinal tract and abdominal pain.

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe

reddening, swelling, and possible tissue destruction.

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

Individuals with pre-existing skin disorders, asthma, allergies or known

sensitization may be more susceptible to the effects of this product.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes.

Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes,

while removing contaminated clothing and shoes.

Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or

give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control

center immediately. Never give anything by mouth to an unconscious

person.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: >200°F (93.3°C)

Flash Point Method: COC

Auto Ignition Temperature: Not determined.

Lower Flammable/Explosive

Limit:

Not determined.

Upper Flammable/Explosive

imit:

Not determined.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire

exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this

material.

2

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA),

MSHA/NIOSH (approved or equivalent) and full protective gear.

Unusual Fire Hazards: Sealed containers at elevated temperatures may rupture explosively and

spread fire due to polymerization.

Hazardous Combustion

Byproducts:

Oxides of carbon and other unknown organic compounds. Irritating fumes and gases may be released upon thermal processing or during combustion.

NFPA Ratings:

NFPA Health:

NFPA Flammability:

NFPA Reactivity:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Evacuate area and keep unnecessary and unprotected personnel from

entering the spill area.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Spill Cleanup Measures: Absorb spill with inert material (e,g., dry sand or earth), then place in a

chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal,

flush spill area with soap and water to remove trace residue.

Avoid personal contact and breathing vapors or mists. Ventilate area. Use

proper personal protective equipment as listed in section 8.

Other Precautions: Pump or shovel to storage/salvage vessels. Add inhibitor to prevent

polymerization.

SECTION 7 - HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Storage: Store in a cool, dry, well ventilated area away from sources of heat and

incompatible materials. Keep container tightly closed when not in use.

Special Handling Procedures: Provide appropriate ventilation/respiratory protection against decomposition

products (see Section 10) during welding/flame cutting operations and to

protect against dust during sanding/grinding of cured product.

Hygiene Practices: Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local

exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the

personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29

CFR 1910.133, OSHA eye and face protection regulation, or the European

standard EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent

skin contact. Consult manufacturer's data for permeability data.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or

canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying

respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an

eyewash and a deluge shower safety station.

EXPOSURE GUIDELINES

Notes: Only established PEL and TLV values for the ingredients are listed.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid.

Color: Red

Odor: Mild chemical.

Boiling Point: >300°F (>150°C)

Melting Point: Not determined.

Specific Gravity: 1.07-1.17

Solubility: Slight.

Vapor Density: Heavier than air.

Vapor Pressure: Not determined.

Evaporation Rate: Not determined.

pH: Not determined.

Molecular Formula: Mixture

Molecular Weight: Mixture

Flash Point: >200°F (93.3°C)

Flash Point Method: COC

Auto Ignition Temperature: Not determined.

VOC Content: <3%

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and

oxidizing conditions. Oxygen-free atmospheres or inert gas blanketing.

Freezing conditions. Material can soften paint and rubber.

Incompatible Materials: Reducing agents

SECTION 11 - TOXICOLOGICAL INFORMATION

Monomer-free Polyester Resin:

RTECS Number: DE4200000

Skin: Oral - Mouse LD50: 17 gm/kg [Details of toxic effects not reported other

than lethal dose value]

Ingestion: Oral - Mouse LD50: 17 gm/kg [Details of toxic effects not reported other

than lethal dose value]

Cumene hydroperoxide:

MX2450000 RTECS Number:

Eye: Eye - Rabbit Standard Draize test.: 1 mg

Eye - Rabbit Standard Draize test.: 70%

Administration onto the skin - Rat : 500 mg/kg [Behavioral - Convulsions or Skin: effect on seizure threshold Kidney/Ureter/Bladder - Hematuria]

Administration onto the skin - Rabbit : 1200 mg/kg [Cardiac - Pulse rate

increase, without fall in BP Blood - changes in erythrocyte (RBC) count

Nutritional and Gross Metabolic - Body temperature decrease]

Administration onto the skin - Mouse : 490 mg/kg [Details of toxic effects

not reported other than lethal dose value]

Administration onto the skin - Mouse : 1200 mg/kg [Biochemical - Enzyme inhibition, induction, or change in blood or tissue levels - Catalases Biochemical - Enzyme inhibition, induction, or change in blood or tissue levels - Other oxidoreductases Biochemical - Enzyme inhibition, induction, or

change in blood or tissue levels - Other transferases]

Administration onto the skin - Rat : 250 mg/kg [Vascular - Structural changes in vessels Biochemical - Metabolism (Intermediary) - Effect on

inflammation or mediation of inflammation]

Administration onto the skin - Mouse : 300 mg/kg [Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation of inflammation] Administration onto the skin - Mouse: 2012 mg/kg/2W (Intermittent) [Skin and Appendages - Tumors Biochemical - Metabolism (Intermediary) - Other

Administration onto the skin - Mouse : 20.1 gm/kg/20W (Intermittent) [Skin

and Appendages - Tumors Tumorigenic - Facilitates action of known

carcinogen Biochemical - Metabolism (Intermediary) - Effect on inflammation

or mediation of inflammation]

Administration onto the skin - Mouse: 30442 ug/kg/4W (Intermittent) [Biochemical - Metabolism (Intermediary) - Effect on inflammation or

mediation of inflammation]

Administration onto the skin - Mouse: 100 mg/kg Administration onto the skin - Rabbit : 500 mg Administration onto the skin - Rabbit : 500 mg

Administration onto the skin - Mouse : 18000 ug/kg/18W (Intermittent) [Tumorigenic - carcinogenic by RTECS criteria Skin and Appendages -

Tumors Tumorigenic - Facilitates action of known carcinogen]

Inhalation: Inhalation - Rat LC50: 220 ppm/4H [Lungs, Thorax, or Respiration -

Dyspnea]

Inhalation - Mouse LC50: 200 ppm/4H [Lungs, Thorax, or Respiration -

Dyspnea]

Ingestion: Oral - Rat LD50: 382 mg/kg [Kidney/Ureter/Bladder - Hematuria]

Oral - Mouse LD50: 342 mg/kg [Details of toxic effects not reported other

than lethal dose value]

Oral - Rat LD50: 800 mg/kg [Details of toxic effects not reported other than

lethal dose value]

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the Waste Disposal:

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state

and local guidelines.

RCRA Number: None

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name:

Not Regulated.

DOT UN Number:

Not applicable.

DOT Hazard Class:

Not applicable.

Not applicable.

SECTION 15 - REGULATORY INFORMATION

Polyethylene glycol dimethacrylate:

TSCA Inventory Status: Listed
Canada DSL: Listed

Monomer-free Polyester Resin:

TSCA Inventory Status: Listed

SARA: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

California PROP 65: Listed: cancer

New Jersey: Listed: NJ Hazardous List; Substance Number: 1641

Massachusetts: Listed: Massachusetts Oil and Hazardous List

Pennsylvania: Listed
Canada DSL: Listed

Cumene hydroperoxide:

TSCA Inventory Status: Listed

SARA: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

New Jersey: Listed: NJ Hazardous List; Substance Number: 0543

Massachussetts: Listed: Massachusetts Oil and Hazardous List

Pennsylvania: Listed
Canada DSL: Listed

Canadian Regulations. WHMIS Hazard Class(es): D2B

All components of this product are on the Canadian Domestic Substances List.

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard: 2
HMIS Fire Hazard: 1
HMIS Reactivity: 1

•

HMIS Personal Protection:

MSDS Creation Date: September 20, 2010

MSDS Revision Date: September 28, 2010

Χ

MSDS Author: Actio Corporation

Disclaimer:

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment.

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.