



Safety Data Sheet

PERMABOND TA430

Revision Number: 1 Issue date: 05/05/15

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PERMABOND TA430 Telephone: 732-868-1372 or 800-640-7599

Product Type: Acrylic adhesive Website: www.permabond.com

Company: PERMABOND LLC

14 Robinson Street

Pottstown, PA 19464

USA

Emergency Telephone:

Medical: Poison Control Center 866-827-6282 (toll free)

or 303-389-1109

Transport: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

WARNING: CAUSES SERIOUS EYE IRRITATION

CAUSES SKIN IRRITATION

MAY CAUSE AN ALLERGIC SKIN REACTION MAY CAUSE RESPIRATORY IRRITATION

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2
SKIN IRRITATION	2
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY- SINGLE EXPOSURE- RESPIRATORY SYSTEM	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist or spray. Wash thoroughly after handling. Use in a well-

ventilated area. Wear protective gloves and eye protection. Contaminated clothing should

laundered separately.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with plenty of water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Rinse with plenty of soap and water.

If feeling unwell call a poison control center or a physician. If eye irritation occurs: Get

medical attention. If skin irritation occurs: Get medical attention.

Storage: Store in a well-ventilated cool place.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).



Disposal: Dispose of according to Federal, State/Provincial and local governmental regulations.

Existing conditions aggravated by exposure:

Skin, eye and respiratory disorders.

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	CONCENTRATION (%)*
Tetrahydrofurfuryl methacrylate	2455-24-5	60 – 100
Methacrylic acid	79-41-4	1 – 5
Epoxy resin (average MW <=700)	25068-38-6	1 – 5
Cumene hydroperoxide	80 – 15- 9	0.1 - 1
Treated fumed silica	67762-90-7	1 - 5

^{*}Exact concentration is a trade secret. Concentration ranges are provided to assist user in determining appropriate protection.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms

persist, get medical attention.

Skin contact: Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur.

Eye contact: Immediately flush with large amounts of water for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm and get medical attention. Never give anything by mouth to an

unconscious person.

Symptoms: See section 11



5. FIRE-FIGHTING MEASURES

Extinguishing media: Foam, water spray or fog, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and protective clothing. In case of fire keep

container cool with water spray.

Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperature resulting in explosions or

rupturing containers.

Hazardous combustion products: Toxic and/or irritating organic vapors may be generated. Oxides of carbon. Oxides of

sulfur and oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection equipment recommended in section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent product from entering drains or waterways.

Clean-up methods: Evacuate area. Dyke spill to prevent from entering water ways. Ventilate area. Wear

protective equipment to clean up. Soak up spill using absorbent material such as sand, silica gel, acid binder, universal binder or saw dust. Scrape up as much material as possible and store in partially filled container until disposal. Refer to section 8 (Exposure

Controls/ Personal Protection) before clean up.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container tightly closed.

Storage: Store in a cool well ventilated area away from heat, sparks, flames, or other sources of ignition. For safe storage

store between 0°C (32 °F) and 30°C (86°F)

For shelf life information contact Permabond customer service at (800)714-0170

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employees should complete an assessment of all workplaces to determine the need for and selection of proper exposure controls and protective equipment before each task is started.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tetrahydrofurfuryl methacrylate	None	None	None	None
Methacrylic acid	20 ppm TWA	None	None	None
Epoxy resin (average MW <=700)	None	None	None	None
Cumene Hydroperoxide	None	None	1 ppm (6 gm/m³) TWA (skin)	None
Treated fumed silica	10 mg/m3 TWA inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction	None	None



Engineering controls: Use local ventilation to maintain worker exposure below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection:

Use chemical resistant/ impermeable gloves (nitrile) gloves and protective clothing to prevent skin contact.

Eye/face protection: Safety goggles or safety glasses with side shields or face shield if splashing or spraying is expected.

Safety showers and eye wash stations should be available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Amber

Odor: Mild acrylic odor
Odor threshold: Not Available
pH: Not applicable

Vapor pressure: <10 mm Hg at 24°C (75°F)

Boiling point/range: >149°C (300°F)

Melting point/range: Not available

Specific gravity: 1.1 at 23.9°C (75°F)

Vapor density:
Flash point:
Flammable/Explosive limits – Lower:
Flammable/Explosive limits – upper:
Autoignition Temperature:
Evaporation rate:

Not available
Not available
Not available

Solubility in water: Slight

Partition coefficient (n-octanol/water): Not available Decomposition temperature: Not available

VOC content: <2 %, 20 grams/liter (Estimated)

10. STABILITY AND REACTIVITY

Stability: Stable when stored under the recommended storage conditions

Hazardous reactions:None under normal processing conditions. In the presence incompatible materials or

high temperature polymerization may occur.

Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic vapors.

Incompatible materials: Strong oxidizing agent. Strong reducing agents. Acids. Bases. Free radical

polymerizing catalysts. Oxygen scavengers.

Conditions to avoid: Contact with incompatible materials which may cause polymerization. Heat, sparks,

flames and other sources of ignition.



11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapor or mist may cause respiratory tract irritation.

Skin contact: Causes skin irritation. May cause skin allergic reaction.

Eye contact: Causes eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by

exposure:

Skin, eye and respiratory disorders.

Hazardous components	LD50	LC50	Immediate and delayed Health Effects
Tetrahydrofurfuryl methacrylate	None	None	Allergen, Irritant
Methacrylic acid	LD50 – Oral (RABBIT) – 1,200 mg/kg LD50 – Oral (RAT) – 1,060 mg/Kg LD50 – Dermal (RABBIT) – 500 mh/Kg	LC50 – Inhalation (RAT, 4h) – 7.1 mg/l	Corrosive, Irritant, Allergen
Epoxy resin (average MW <=700)	LD50 - Oral (RAT) 13,000 mg/Kg	None	Irritant, Allergen
Cumene Hydroperoxide	None	None	Allergen, Central nervous system, corrosive, irritant, Mutagen
Treated fumed silica	None	None	Irritant

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Tetrahydrofurfuryl methacrylate	No	No	No
Methacrylic acid	No	No	No
Epoxy resin (average MW <=700)	No	No	No
Cumene Hydroperoxide	No	No	No
Treated fumed silica	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not Available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:Dispose of according to Federal, State/Provincial and local governmental regulations.

Refer to section 8 (Exposure Controls/Personal Protection) before handling.



14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
None
Exceptions:
Not regulated
None
None
None

International Air Transportation (ICAO/IATA):

Proper shipping name: Not regulated

Hazard class or division:

Identification number:

Packing group:

Exceptions:

None

None

Water Transportation (IMO/IMDG):

Proper shipping name: Not regulated

Hazard class or division:

Identification number:

Packing group:

None

None

None

Marine pollutant:

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control

Act Inventory.

TSCA 12 (b) Export Notification:

CERCLA/SARA Section 302 EHS:

None above the reporting limits.

None above the reporting limits.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Reactive

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting

requirements of section 313 of the Emergency Planning and Community Right-To-

Know Act of 1986 (40 CFR 372). Cumene Hydroperoxide (CAS# 80-15-9).

CERCLA Reportable quantity: Cumene Hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 Kg)

California Proposition 65: No chemical listed on the California Proposition 65 are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous one: New format

ADDITIONAL INFORMATION: The information given and the recommendations made herein apply to our product(s) alone and are not combined with other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guaranty of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.

Issue date: 05/05/15