



# Dry-Treat

Chemwatch: 4878-19

Version No: 4.1.1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

# **SECTION 1 IDENTIFICATION**

### Product Identifier

Product name	Dry-Treat INTENSIFIA	
Synonyms	INTENSIFIA, Intensifier for natural stone, oil and water repellent	
Other means of identification	Not Available	
Recommended use of the	Recommended use of the chemical and restrictions on use	
Relevant identified uses	Use according to manufacturer's directions. Intensifier for porous stone, tile and concrete.	

# Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Dry-Treat	Dry-Treat Ltd	Dry-Treat	
Address	4/149-155 Pascoe Vale Rd. VIC Moonee Ponds 3039 Australia	United Kingdom	150 Dascomb Road MA Andover 01810 United States	
Telephone	1800 675 119 (AUS)	0800 0964 760 (UK)	+1 866 667 5119 (USA)	
Fax	+61 2 9954 3162	+61 2 9954 3162	+61 2 9954 3162	
Website	Not Available	Not Available	Not Available	
Email	Not Available	sds@drytreat.com	Not Available	

### Emergency phone number

Association / Organisation	Not Available	Not Available	Not Available
Emergency telephone numbers	+1 813 248 0585 (Outside USA)	+1 813 248 0585 (Outside USA)	(800) 255 3924
Other emergency telephone numbers	Not Available	Not Available	+1 813 248 0585 (Outside USA)

# SECTION 2 HAZARD(S) IDENTIFICATION

### Classification of the substance or mixture

Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Not classified as Dangerous Goods for transport purposes.

### CHEMWATCH HAZARD RATINGS

	Min	Max		NFPA 704 diamond	
Flammability	1 📕				
Toxicity	0				
Body Contact	2				
Reactivity	1		0 = Minimum	$\left(1 \times 0\right)$	
Chronic	0		1 = Low 2 = Moderate 3 = High		Note: The SDSs are
			4 = Extreme	$\sim$	Fire Yellov

he hazard category numbers found in GHS classification in section 2 of this e NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = ow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Flammable Liquid Category 4, Acute Aquatic Hazard Category 3
Label elements	
GHS label elements	Not Applicable
SIGNAL WORD	WARNING
Hazard statement(s)	
H227	Combustible liquid

### Chemwatch Hazard Alert Code: 2

Issue Date: 29/10/2013 Print Date: 19/04/2016 Initial Date: Not Available S.GHS.USA.EN H402 Harmful to aquatic life

### Hazard(s) not otherwise specified

Not Applicable

### Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

# Precautionary statement(s) Response

P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.
Precautionary statement(s) Storage	
P403+P235	Store in a well-ventilated place. Keep cool.
Precautionary statement(s) Disposal	
P501	Dispose of contents/container in accordance with local regulations.

### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
Not Available	100	Ingredients determined not to be hazardous [Manufacturer]

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

# SECTION 4 FIRST-AID MEASURES

### Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin contact occurs:</li> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

### Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# SECTION 5 FIRE-FIGHTING MEASURES

### Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
  Carbon dioxide.

# Special hazards arising from the substrate or mixture

Fire Incompatibility <ul> <li>Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result</li> </ul> Special protective equipment and precautions for fire-fighters		Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
		ent and precautions for fire-fighters
		<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> </ul>

	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> </ul>
Fire Fighting	<ul> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>

# Fire/Explosion Hazard High temperature decomposition products include silicon dioxide, small amounts of formaldehyde, formic acid, acetic acid and traces of silicon polymers. These gases may ignite and, depending on circumstances, may cause the resin/polymer to ignite. An outer skin of silica may also form. Extinguishing of fire, beneath the skin, may be difficult. Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include:carbon dioxide (CO2)nitrogen oxides (NOx)silicon dioxide (SiO2)other pyrolysis products typical of burning organic materialMay emit corrosive fumes. CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	<ul> <li>Silicone fluids, even in small quantities, may present a slip hazard.</li> <li>It may be necessary to rope off area and place warning signs around perimeter.</li> <li>Clean up area from spill, with suitable absorbant, as soon as practically possible.</li> <li>Final cleaning may require use of steam, solvents or detergents.</li> <li>Moderate hazard.</li> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

Safe handling	<ul> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information <ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>	
Conditions for safe storage	ge, including any incompatibilities
Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	<ul> <li>Avoid strong acids, bases.</li> <li>Avoid reaction with oxidising agents</li> </ul>

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Control parameters**

### OCCUPATIONAL EXPOSURE LIMITS (OEL)

### INGREDIENT DATA

Not Available

### EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Dry-Treat INTENSIFIA	Not Available	Not Available	Not Available	Not Available
	Original IDLH		Revised IDLH	
Ingredient	Original IDLH		Revised IDLH	

### Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineer effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.	
Appropriate engineering	The basic types of engineering controls are:
controls	Process controls which involve changing the way a job activity or process is done to reduce the risk.
	Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and
	"removes" air in the work environment.

Personal protection		
Eye and face protection	<ul> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>	
Skin protection	ction See Hand protection below	
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</li> <li>Suitability and durability of glove type is dependent on usage.</li> </ul>	
Body protection	See Other protection below	
Other protection <ul> <li>P.V.C. apron.</li> <li>Barrier cream.</li> </ul>		
Thermal hazards	Not Available	

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance Liquid with a characteristic odour; partially miscible with water.

Physical state	Liquid	Relative density (Water = 1)	0.99
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	77	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Partly Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7	
<ul> <li>Silicone fluids are stable under normal storage conditions.</li> <li>Hazardous polymerisation will not occur.</li> <li>At temperatures &gt; 150 C, silicones can slowly react with the oxygen in air.</li> <li>When heated &gt; 300 C, silicones can slowly depolymerise to volatile siloxanes whether or not air is present.</li> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>		
Possibility of hazardous reactions	See section 7	
Conditions to avoid		
Incompatible materials		
Hazardous decomposition products	See section 5	

# SECTION 11 TOXICOLOGICAL INFORMATION

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Vapours of silicones are generally fairly well tolerated, however very high concentrations can cause death within minutes due to respiratory failure. At high temperatures, the fumes and oxidation products can be irritating and toxic and can cause depression leading to death in very high doses.		
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Silicone fluids do not have a high acute toxicity. They may have a laxative effect and produce central nervous system depression.		
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Low molecular weight silicone fluids may exhibit solvent action and may produce skin irritation. Excessive use or prolonged contact may lead to defatting, drying and irritation of sensitive skin		
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons. Eye exposure to silicone fluids causes temporary irritation of the conjunctiva. Injection into the specific structures of the eye, however, causes corneal scarring, permanent eye damage, allergic reactions and cataract, and may lead to blindness.		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.		
	TOXICITY	IRRITATION	
Dry-Treat INTENSIFIA	Not Available	Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		
Dry-Treat INTENSIFIA	SIFIA No significant acute toxicological data identified in literature search.		
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
	0	Reproductivity	<u> </u>
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	$\odot$	STOT - Repeated Exposure	$\odot$

- Legend: X Data available but does not fill the criteria for classification
  - $\checkmark$  Data required to make classification available

S − Data Not Available to make classification

### **SECTION 12 ECOLOGICAL INFORMATION**

Mutagenicity

 $\odot$ 

### Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Aspiration Hazard

 $\odot$ 

Harmful to aquatic organisms.

For Siloxanes:

Environmental Fate: Siloxanes are used in cosmetics, wax, polishes, and to a minor extent in several other applications.

Atmospheric Fate: In the presence of nitrate ions, short chain siloxanes are broken down by sunlight to the level of silicate within days. The main source atmospheric siloxane release to the air is via evaporation.

Aquatic Fate: It is well accepted that polydimethylsiloxane fluids become permanent residents of sediment but should not have adverse environmental effects.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

### **Bioaccumulative potential**

Ingredient	Bioaccumulation	
	No Data available for all ingredients	
Mobility in soil		

Ing	gredient	Mobility
		No Data available for all ingredients

# SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:
▶ Reduction
▶ Reuse
► Recycling
<ul> <li>Disposal (if all else fails)</li> </ul>
This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
DO NOT allow wash water from cleaning or process equipment to enter drains.
It may be necessary to collect all wash water for treatment before disposal.
In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
Where in doubt contact the responsible authority.
Recycle wherever possible or consult manufacturer for recycling options.
Consult State Land Waste Authority for disposal.
Bury or incinerate residue at an approved site.
Recycle containers if possible, or dispose of in an authorised landfill.

### SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant NO

### Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### **SECTION 15 REGULATORY INFORMATION**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

### **Federal Regulations**

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	NO
Delayed (chronic) health hazard	NO
Fire hazard	YES
Pressure hazard	NO
Reactivity hazard	NO

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

### State Regulations

### US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	Υ
China - IECSC	γ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	γ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

# **SECTION 16 OTHER INFORMATION**

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### **Definitions and abbreviations**

PC -- TWA: Permissible Concentration-Time Weighted Average PC -- STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

