

Chemical<sup>™</sup> Concepts
Our customers stick with us.

SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 1

**Revision date:** 09/05/2019

Revision No: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: SURFACE BONDER ZERO 10:1 CARTRIDGE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

# 1.3. Details of the supplier of the safety data sheet

Company name: Chemical Concepts, INC.

410 Pike Road

Huntingdon Valley, PA 19006

**Tel:** 1-800-220-1966 **Fax:** 215-357-2754

Email: sales@chemical-concepts.com

#### 1.4. Emergency telephone number

Emergency tel: CHEMTREC: 800-424-9300 (USA)

703-527-3887 (INTERNATIONAL)

# Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; STOT SE 3: H335; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin

Irrit. 2: H315; Skin Sens. 1: H317; -: EUH208

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin

reaction. Causes serious eye irritation. May cause respiratory irritation. Harmful to aquatic life with long lasting effects. Contains dibenzoyl peroxide. May produce an

allergic reaction.

### 2.2. Label elements

# Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

EUH208: Contains dibenzoyl peroxide. May produce an allergic reaction.

[cont...]

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P273: Avoid release to the environment.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.2. Mixtures

# Hazardous ingredients:

METHYL METHACRYLATE - REACH registered number(s): 01-2119452498-28-000, 01-2119452498-28-0025, 01-2119452498-28-0028

EINECS	CAS	PBT / WEL	CLP Classification	Percent
201-297-1	80-62-6	-	Flam. Liq. 2: H225; STOT SE 3: H335;	50-75%
			Skin Irrit. 2: H315; Skin Sens. 1: H317	

# EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <700)

500-033-5	25068-38-6	_	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	1-5%
300-033-3	23000-30-0	_	Skin Sens. 1: H317	1-376

# 2-METHYLPROPENOIC ACID - REACH registered number(s): 01-2119463884-26-0000

201-204-4	79-41-4	-	Acute Tox. 4: H312; Acute Tox. 4: H302;	1-5%
			Skin Corr. 1A: H314	

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 3

#### DIBENZOYL PEROXIDE

202-327-6	94-36-0	-	Skin Sens. 1: H317; Org. Perox. B: H241; Eye Irrit. 2: H319	<1%			
TRIS(METHYI	TRIS(METHYLPHENYL)PHOSPHATE						
215-548-8	1330-78-5	-	Repr. 2: H361; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%			

#### Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

# 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

# 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 4

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

### 7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

# **Hazardous ingredients:**

# METHYL METHACRYLATE

# Workplace exposure limits:

Resnirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	203mg/m3	416mg/m3	-	-

# 2-METHYLPROPENOIC ACID

	<b>70</b> / 0			
UK	72 mg/m3	143 mg/m3	-	-

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 5

#### **DIBENZOYL PEROXIDE**

UK	5 mg/m3	-	-	-
----	---------	---	---	---

#### **DNEL/PNEC Values**

# **Hazardous ingredients:**

#### **METHYL METHACRYLATE**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	210mg/m3	Workers	Systemic
DNEL	Dermal	74.3 mg/m3	Workers	Systemic
PNEC	Water	0.94 mg/l	-	-

#### 2-METHYLPROPENOIC ACID

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	88mg/m3	Workers	Local
DNEL	Dermal	4.25mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	29.6mg/m3	Workers	Systemic
DNEL	-	360mg/m3 100ppm	Workers	Short term
PNEC	Fresh water	0.82mg/l	Workers	-
PNEC	Marine water	0.82mg/l	Workers	-
PNEC	Sewage treatment plant (STP)	10mg/l	Workers	-
PNEC	Soil (agricultural)	1.2mg/kg	Workers	-

#### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: ENSURE GOOD HYGENE PRACTICE Avoid breathing the vapour. Maintain good

ventilation. High standards of industrial hygiene are required for safe handling of large volumes. It is not necessary to wear special breathing aparatus in well ventilated areas

however it is good practice to maintain relative humidity between 50-60%

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing. Avoid skin contact.

Environmental: Avoid release to the environment. Prevent from entering in public sewers or the

immediate environment.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Various

**Evaporation rate:** No data available. **Oxidising:** No data available.

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 6

Solubility in water: No data available.

Viscosity: Highly viscous

**Boiling point/range°C:** 100 **Melting point/range°C:** Not applicable.

Flammability limits %: lower: 1.7 upper: 12.5

Flash point°C: <23 Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: 412 Vapour pressure: 28mmHg @ 20'C

**Relative density:** 0.93-1.05 **pH:** 4-6

VOC g/I: <50 g/I mixed

#### 9.2. Other information

Other information: Flammability based on data for methyl methacrylate

# Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Avoid extreme temperatures, open flames, sparks, and direct sunlight. Heat.

# 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

#### Section 11: Toxicological information

# 11.1. Information on toxicological effects

#### **Hazardous ingredients:**

#### **METHYL METHACRYLATE**

DERMAL	RBT	LD50	>5000	mg/kg
INHALATION	RAT	4H LC50	29.8	mg/l
ORAL	RAT	LD50	>5000	mg/kg

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 7

# 2-METHYLPROPENOIC ACID

DERMAL	RBT	LD50	500-1000	mg/kg
ORAL	RAT	LD50	1320	mg/kg
VAPOURS	RAT	1H LC50	7.1	mg/l

# **DIBENZOYL PEROXIDE**

ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	LC0	>24.3	mg/kg

# Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# **Section 12: Ecological information**

# 12.1. Toxicity

# **Hazardous ingredients:**

#### **METHYL METHACRYLATE**

DAPHNIA MAGNA	48H EC50	69	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H EC50	>110	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>79	mg/l

#### 2-METHYLPROPENOIC ACID

Daphnia magna	48H EC50	>130	mg/l
GREEN ALGA (Selenastrum capricornutum)	96H ErC50	45	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	85	mg/l

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 8

# **DIBENZOYL PEROXIDE**

BACTERIA	EC50	35	mg/l
DAPHNIA MAGNA	48H EC50	0.11	mg/l
POCHILIA RETICULATA	96H LC50	0.06	mg/l
PSEUDOKIRCHNERIELLA SUBCAPITATA	72H EC50	0.06	mg/l

### 12.2. Persistence and degradability

# 12.3. Bioaccumulative potential

# 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

# 14.1. UN number

UN number: UN1133

# 14.2. UN proper shipping name

Shipping name: ADHESIVES

# 14.3. Transport hazard class(es)

Transport class: 3

# 14.4. Packing group

Packing group: ||

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

# 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

# SURFACE BONDER ZERO 10:1 CARTRIDGE

Page: 9

#### **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Europe EINECS

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### **Section 16: Other information**

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains dibenzoyl peroxide. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H241: Heating may cause a fire or explosion.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H361: Suspected of damaging fertility or the unborn child.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: This company shall not be held liable for any damage resulting from handling or from

contact with the above product.

