

# USA SAFETY DATA SHEET



## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: LORD 606

Product Use/Class: Acrylic Adhesive, Part 1 of 2

LORD Corporation 111 LORD Drive Cary, NC 27511-7923

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

**EFFECTIVE DATE:** 04/10/2015

#### 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATION:**

Flammable liquids Category 2

Acute toxicity Inhalation - Dust and Mist Category 4 - 34.7% of the mixture consists of ingredient(s) of unknown toxicity.

Acute toxicity Inhalation - Vapours Category 4 - 34.7% of the mixture consists of ingredient(s) of unknown toxicity. Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Skin sensitization Category 1

Respiratory sensitization Category 1

Germ cell mutagenicity Category 1B

Carcinogenicity Category 2

Reproductive toxicity Category 1B

Specific target organ systemic toxicity (single exposure) Category 3

Specific target organ systemic toxicity (single exposure) Category 1 circulatory system, Nervous system,

Hematopoietic System

Specific target organ systemic toxicity (repeated exposure) Category 1 Blood, Liver, spleen, Lungs, Adrenal gland,

Kidney, Nervous system, Central nervous system, Respiratory system

Hazardous to the aquatic environment - acute hazard Category 2

Hazardous to the aquatic environment - chronic hazard Category 2

# **GHS LABEL ELEMENTS:**

Symbol(s)









# Signal Word

**DANGER** 

### **Hazard Statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause genetic defects.

Suspected of causing cancer.

May damage fertility or the unborn child.

300000009852

May cause drowsiness or dizziness.

May cause respiratory irritation.

Causes damage to organs.(circulatory system, Nervous system, Hematopoietic System)

Causes damage to organs through prolonged or repeated exposure. (Blood, Liver, spleen, Lungs, Adrenal gland,

Kidney, Nervous system, Central nervous system, Respiratory system)

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements**

#### **Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

#### Response

In case of fire: refer to section 5 of SDS for extinguishing media.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Collect spillage.

#### Storage

Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

# Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

#### Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

**Acute:** May be absorbed through the skin in harmful amounts. May cause headache and nausea. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May be severely irritating to the nose, throat and respiratory tract. Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

**Chronic:** Prolonged or repeated contact may result in dermatitis. Contains N,N-Dimethylaniline. Excessive overexposure by skin absorption or ingestion may result in anoxia due to the formation of methemoglobin. This condition impairs the blood's ability to transport oxygen. IARC has designated titanium dioxide (TiO2) as Group 2B – possibly carcinogenic to humans in dust form. However, a number of long term animal studies and human epidemiology studies evaluating TiO2 and workplace exposure show insufficient evidence for carcinogenic affects.

EPA, NTP and OSHA do not designate TiO2 as a carcinogen and ACGIH designates TiO2 as A4 - not classifiable as a human carcinogen. TiO2 is not present in this product as a dust and no airborne exposure is expected during application.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range	
Methyl methacrylate	80-62-6	40 - 45 %	
Titanium dioxide	13463-67-7	1 - 5 %	
Methacrylic acid	79-41-4	1 - 5 %	
Acrylic monomer	PROPRIETARY	1 - 5 %	
Methacrylate phosphate ester	PROPRIETARY	1 - 5 %	
Methacrylate Blend	PROPRIETARY	1 - 5 %	
N,N-Dimethylaniline	121-69-7	1 - 5 %	

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

### 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

### 5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable.

# 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:** Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Using non-sparking tools, scoop the spilled material into a container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

## 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

**STORAGE:** Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements. Store only in well-ventilated areas. Keep container closed when not in use.

**INCOMPATIBILITY:** Inorganic acids, organic acids, caustics, oxidizing agents, amines, peroxides.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### COMPONENT EXPOSURE LIMIT

<u>Chemical Name</u>	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	<u>Skin</u>
Methyl methacrylate	50 ppm	100 ppm	410 mg/m3 100 ppm	N.E.	N.A.
Titanium dioxide	10 mg/m3	N.E.	15 mg/m3	N.E.	N.A.
Methacrylic acid	20 ppm	N.E.	N.E.	N.E.	S
Acrylic monomer	N.E.	N.E.	N.E.	N.E.	N.A.
Methacrylate phosphate ester	N.E.	N.E.	N.E.	N.E.	N.A.
Methacrylate Blend	N.E.	N.E.	N.E.	N.E.	N.A.
N,N-Dimethylaniline	5 ppm	10 ppm	25 mg/m3 5 ppm	N.E.	S

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

**Engineering controls:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

### PERSONAL PROTECTION MEASURES/EQUIPMENT:

**RESPIRATORY PROTECTION:** Contains a small amount of dimethylaniline (DMA)which has poor odorwarning properties. If the exposure limit for DMA is exceeded, an air-supplied respirator is recommended. Otherwise, a NIOSH approved properly-fitted organic vapor, air purifying respirator is recommended. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact. If contact with the product is prolonged or repeated, Silver Shield or Butyl rubber gloves are recommended.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR: Characteristic VAPOR PRESSURE: N.D.

APPEARANCE: White VAPOR DENSITY: Heavier than Air

PHYSICAL STATE: Paste LOWER EXPLOSIVE LIMIT: 1 %(V)
FLASH POINT: 59 °F, 15 °C Setaflash UPPER EXPLOSIVE LIMIT: 8.8 %(V)

Closed Cup

BOILING RANGE: N.A. EVAPORATION RATE: Faster than n-butyl-

acetate.

AUTOIGNITION TEMPERATURE: N.D. DENSITY: 1.1 g/cm3 - 9.15 lb/gal

**DECOMPOSITION TEMPERATURE:** VISCOSITY, DYNAMIC: N.D. N.D. **ODOR THRESHOLD:** N.D. VISCOSITY, KINEMATIC: N.D. **SOLUBILITY IN H2O:** Insoluble **VOLATILE BY WEIGHT:** 0.00 % **VOLATILE BY VOLUME:** 0.00 % pH: N.A.

FREEZE POINT: N.D. VOC CALCULATED: 0 lb/gal, 0 g/l

COEFFICIENT OF WATER/OIL N.D.

DISTRIBUTION:

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

## 10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

**CONDITIONS TO AVOID:** Storage above 100 degrees F and below 32 degrees F. Exposure to sunlight, ultraviolet light irradiation. Avoid dropping or puncture of containers.

**INCOMPATIBILITY:** Inorganic acids, organic acids, caustics, oxidizing agents, amines, peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, oxides of nitrogen, Metal oxides

## 11. TOXICOLOGICAL INFORMATION

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

### **TOXICITY MEASURES:**

Chemical Name	<u>LD50/LC50</u>
Methyl methacrylate	Oral LD50: Rat 7,872 mg/kg
	Oral LD50: Rat 7,900 mg/kg
	Dermal LD50: Rabbit > 5 g/kg
	Inhalation LC50: Rat 4632 ppm/4 h
Titanium dioxide	Oral LD50: Rat > 10,000 mg/kg
	GHS LC50 (vapour): rat 55 mg/l /
Methacrylic acid	Oral LD50: Rat 1,060 mg/kg
	Dermal LD50: Rabbit 500 - 1,000 mg/kg
	Inhalation LC50: Rat 7.1 mg/l /4 h
Acrylic monomer	Dermal LD50: Rabbit > 3 g/kg
Methacrylate phosphate ester	Oral LD50: rat > 5,000 mg/kg
Methacrylate Blend	Oral LD50: rat > 5,000 mg/kg
N,N-Dimethylaniline	Oral LD50: Rat 700 mg/kg
	Dermal LD50: Rabbit 1770 μL/kg
	Inhalation LC50: Rat > 5.1 mg/l /4 h

Germ cell mutagenicity: Category 1B - May cause genetic defects.

Components contributing to classification: Phenol.

Carcinogenicity: Category 2 - Suspected of causing cancer.

Components contributing to classification: Titanium dioxide. N,N-Dimethylaniline.

**Reproductive toxicity:** Category 1B - May damage fertility or the unborn child. Components contributing to classification: Methyl methacrylate. Phenol.

# 12. ECOLOGICAL INFORMATION

## **ECOTOXICITY:**

Chemical Name	<b>Ecotoxicity</b>		
Methyl methacrylate	Fish: Pimephales promelas 243 - 275 mg/l96 h flow-through Pimephales promelas 125.5 - 190.7 mg/l96 h Static		
	Lepomis macrochirus 170 - 206 mg/l96 h flow-through		
	Lepomis macrochirus 153.9 - 341.8 mg/l96 h Static		
	Oncorhynchus mykiss > 79 mg/l96 h flow-through		
	Oncorhynchus mykiss > 79 mg/l96 h Static		
	Poecilia reticulata 326.4 - 426.9 mg/l96 h Static		
	Invertebrates: Daphnia magna 69 mg/l48 h		
	Plants: Pseudokirchneriella subcapitata 170 mg/l96 h		
Titanium dioxide	N.D.		
Methacrylic acid	N.D.		
Acrylic monomer	N.D.		
Methacrylate phosphate ester	N.D.		
Methacrylate Blend	N.D.		
N,N-Dimethylaniline	<u>Fish:</u> Pimephales promelas 52.6 mg/l96 h flow-through		
	Pimephales promelas 65.6 mg/l96 h		
	Poecilia reticulata 53.7 mg/l96 h semi-static		
	Brachydanio rerio 51.1 mg/l96 h semi-static		
	Brachydanio rerio 0.183 - 0.186 mg/l96 h		
	Invertebrates: Daphnia magna 5 mg/148 h		
	Plants: Desmodesmus subspicatus 340 mg/l96 h		

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

**BIOACCUMULATIVE:** Not determined for this product.

**MOBILITY IN SOIL:** Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

# 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality. Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

## 14. TRANSPORT INFORMATION

**US DOT Road** 

DOT Proper Shipping Name: Adhesives
DOT Hazard Class: 3
SECONDARY HAZARD: None
DOT UN/NA Number: 1133
Packing Group: II
Emergency Response Guide Number: 128

IATA Cargo

PROPER SHIPPING NAME: Adhesives
DOT Hazard Class: 3
HAZARD CLASS: None
UN-NUMBER: 1133

PACKING GROUP: II EMS: 3L

**IMDG** 

**PROPER SHIPPING NAME:** Adhesives

DOT Hazard Class: 3
HAZARD CLASS: None
UN-NUMBER: 1133
PACKING GROUP: II
EMS: F-E

The listed transportation classification applies to US DOT Road, IATA Cargo, and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

# 15. REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS: AS FOLLOWS:

### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

Chemical NameCAS NumberWeight % Less ThanMethyl methacrylate80-62-645.0 %N.N-Dimethylaniline121-69-75.0 %

### TOXIC SUBSTANCES CONTROL ACT:

## **INVENTORY STATUS**

The chemical substances in this product are on the TSCA Section 8 Inventory.

## **EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

### 16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2\* FLAMMABILITY: 3 PHYSICAL HAZARD: 1

\* - Indicates a chronic hazard; see Section 2

**Revision:** New GHS SDS Format

**Effective Date:** 04/10/2015

## DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.