



B920FS Bost 920FS Product Series Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

### SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1. Product Identifier

Product Name Product Code Bost 920FS Product Series B920FS

**Product(s) Covered** A19218 A25615 A25615-95L

 BOST 920FS WHITE
 24/10.1

 BOST 920FS BLACK
 24/10.1

 BS920FS/BLK/DRM/52GL/VRWTLB/3P

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended use Uses Advised Against

No information available. No information available

### 1.3. Details of the Supplier of the Safety Data Sheet

### Company Name

Bostik, Inc. 11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA Phone: +1 (800) 843-0844 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International) Fax: +1 (414) 774-8075 Email: msds@bostik-us.com

### 1.4. Emergency Telephone Number

**Emergency Telephone** 

Telephone: 1-800-227-0332 (Outside U.S.) 1-703-527-3887

### **SECTION 2: Hazards Identification**

### 2.1. Classification of the Substance or Mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Flammable Liquids	Category 4

### 2.2. Label Elements

### **EMERGENCY OVERVIEW**


### DANGER

### Hazard Statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled May cause an allergic skin reaction Suspected of causing cancer Combustible liquid

**B920FS Bost 920FS Product Series** 

Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01



### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray In case of inadequate ventilation wear respiratory protection Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Keep away from heat/sparks/open flames/hot surfaces. - No smoking

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see first aid measures on this label)

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. In case of fire: Use CO2, dry chemical, or foam to extinguish.

### **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep cool

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards Not Otherwise Classified (HNOC) Not applicable

### **Unknown Toxicity**

53.65% of the mixture consists of ingredient(s) of unknown toxicity

### 2.3. Other Information

Causes mild skin irritation.

### SECTION 3: Composition/Information on Ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical Name	CAS No	Weight-%
Polyvinyl chloride	9002-86-2	10 - 30
Limestone	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	1 - 5

### B920FS Bost 920FS Product Series

#### Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

Propylene carbonate	108-32-7	1 - 5
m-Xylene	108-38-3	1 - 5
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - 1
p-Xylene	106-42-3	0.1 - 1
Carbon black	1333-86-4	0.1 - 1
Isophorone diisocyanate	4098-71-9	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### **SECTION 4: First Aid Measures**

### 4.1. Description of First Aid Measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Immediate medical attention is not required. If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapors or decomposition products.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.
Self-protection of the First Aider	Use personal protective equipment as required.
4.2. Most Important Symptoms and I	Effects, Both Acute and Delayed
Symptoms	No information available.
4.3. Indication of Any Immediate Med	dical Attention and Special Treatment Needed
Note to Physicians	Treat symptomatically.
4.4. Reference to Other Sections	
Reference to Other Sections	SECTION 8: Exposure controls/personal protection SECTION 11: Toxicological Information

### **SECTION 5: Fire Fighting Measures**

### 5.1. Extinguishing Media

### Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

### **Unsuitable Extinguishing Media**

CAUTION: Use of water spray when fighting fire may be inefficient.

### 5.2. Special Hazards Arising from the Substance or Mixture

### **Specific Hazards Arising from the Chemical**

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Page 3/11

#### B920FS Bost 920FS Product Series

Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

### Explosion Data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. None.

### 5.3. Advice for Firefighters

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### SECTION 6: Accidental Release Measures

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.
6.2. Environmental Precautions	
Environmental Precautions	Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.
6.3. Methods and Material for Conta	inment and Cleaning up
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning up	Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.
6.4. Reference to other sections	
Reference to Other Sections	SECTION 8: Exposure controls/personal protection SECTION 7: Handling and Storage SECTION 13: Disposal Considerations

### **SECTION 7: Handling and Storage**

### 7.1. Precautions for Safe Handling

Advice on Safe Handling	Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
7.2. Conditions for Safe Storage, in	cluding any Incompatibilities
Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.
Incompatible Materials	None known based on information supplied.
7.3. Specific End Use(s)	
Other Information	No information available.

#### B920FS Bost 920FS Product Series

Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

### 7.4. References to Other Sections

Reference to Other Sections	SECTION 13: Disposal Considerations
	SECTION 10: Stability and Reactivity

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control Parameters

### **Exposure Guidelines**

. As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Polyvinyl chloride 9002-86-2	TWA: 1 mg/m <sup>3</sup> respirable fraction	-	-	-
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	IDLH: 5000 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
m-Xylene 108-38-3	STEL: 150 ppm TWA: 100 ppm	IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	-	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>
p-Xylene 106-42-3	STEL: 150 ppm TWA: 100 ppm	IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	-	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3 mg/m³ inhalable fraction	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	TWA: 3.5 mg/m³	TWA: 3.5 mg/m³ STEL: 7 mg/m³
Isophorone diisocyanate 4098-71-9	TWA: 0.005 ppm	TWA: 0.005 ppm TWA: 0.045 mg/m <sup>3</sup> STEL: 0.02 ppm STEL: 0.180 mg/m <sup>3</sup>	-	TWA: 0.01 ppm TWA: 0.09 mg/m³
Ethylbenzene 100-41-4	TWA: 20 ppm	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

Chemical Name	Argentina	Brazil	Chile	Venezuela
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	-	TWA: 8 mg/m <sup>3</sup>	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	-	-	TWA: 10 mg/m <sup>3</sup>
m-Xylene 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	-	Skin STEL: 150 ppm TWA: 100 ppm
p-Xylene 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	-	Skin STEL: 150 ppm TWA: 100 ppm
Carbon black	TWA: 3.5 mg/m <sup>3</sup>	- - -	-	TWA: 3.5 mg/m <sup>3</sup>

### B920FS Bost 920FS Product Series

#### Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

1333-86-4				
Isophorone diisocyanate	TWA: 0.005 ppm	-	-	TWA: 0.005 ppm
4098-71-9				
Ethylbenzene	TWA: 100 ppm	TWA: 78 ppm	TWA: 80 ppm	Skin
100-41-4	STEL: 125 ppm	TWA: 340 mg/m <sup>3</sup>	TWA: 348 mg/m <sup>3</sup>	STEL: 125 ppm
		_	_	TWA: 100 ppm

### 8.2. Exposure Controls

Engineering Controls	Showers Eyewash stations Ventilation systems.
	,

Personal protective equipment [PPE]

ersonar protective equipment [r	
Eye/Face Protection	Tight sealing safety goggles.
Skin and Body Protection	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Concrel Uvgiana Concideration	ana When using do not out, drink or amaka. Regular algoning of aquipment, work area and

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid	
Color	Multiple Colors	
Odor	Solvent	
Odor Threshold	No information available	
Dreverty	Values	Demontra - Mathad
Property	Values No information available	<u>Remarks • Method</u>
pH Malting Daint/Engaging Daint		
Melting Point/Freezing Point	No information available	
Boiling Point	No information available	
Flash Point	71.1 °C / 160 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper Flammability Limit	No information available	
Lower Flammability Limit	No information available	
Vapor Pressure	No information available	
Vapor Density	No information available	
Specific Gravity	No information available	
Water Solubility	No information available	
Solubility in Other Solvents		
Partition Coefficient	No information available	
Autoignition Temperature	No information available	
Decomposition Temperature	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	No information available	
Explosive Properties	No information available	
Oxidizing Properties	No information available	

9.2. Other Information

### B920FS Bost 920FS Product Series

Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

Softening Point	No information available
Molecular Weight	No information available
Solvent Content (%)	No information available
Solid Content (%)	96
Density	1.19-1.23 g/cm <sup>3</sup>
VOC	2.7 %

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

None under normal use conditions.

### 10.2. Chemical Stability

Stable under recommended storage conditions. **10.3. Possibility of Hazardous Reactions** 

None under normal processing. **10.4. Conditions to Avoid** 

Heat, flames and sparks. 10.5. Incompatible Materials

None known based on information supplied. 10.6. Hazardous Decomposition Products

None known based on information supplied.

### SECTION 11: Toxicological Information

### 11.1. Information on Toxicological Effects

Product Information	No Data Available
Inhalation	No Data Available.
Eye Contact	No Data Available.
Skin Contact	No Data Available.
Ingestion	No Data Available.

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Propylene carbonate 108-32-7	= 29000 mg/kg (Rat)	> 20 mL/kg (Rabbit)	-
m-Xylene 108-38-3	= 5 g/kg (Rat)	= 14100 µL/kg (Rabbit)	-
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	= 2234 mg/kg (Rat)	-	> 640 ppm (Rat)1 h
p-Xylene 106-42-3	= 4029 mg/kg (Rat)	-	= 4550 ppm (Rat)4 h = 4740 ppm (Rat)4 h
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Isophorone diisocyanate	= 4814 mg/kg (Rat)	1060 - 4780 mg/kg (Rabbit)	= 0.135 mg/L (Rat) 4 h

### **B920FS Bost 920FS Product Series**

#### Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

4098-71-9			
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 1432 mg/L (Rat)4 h

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Symptoms Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Irritation Corrosivity Sensitization Germ Cell Mutagenicity Reproductive Toxicity Developmental Toxicity Teratogenicity STOT - Single Exposure STOT - Repeated Exposure Chronic Toxicity	No information available. No information available.
Target Organ Effects	adverse liver effects. Blood, Central nervous system, Eyes, Gastrointestinal tract (GI), Kidney, Liver, Lungs,
	Respiratory system, Skin.
Aspiration Hazard	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen. As Titanium dioxide (13463-67-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical Name	ACGIH	IARC	NTP	OSHA
Polyvinyl chloride 9002-86-2	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
m-Xylene 108-38-3	-	Group 3	-	-
p-Xylene 106-42-3	-	Group 3	-	-
Carbon black 1333-86-4	A3	Group 2B	-	Х
Ethylbenzene 100-41-4	A3	Group 2B	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Confirmed animal carcinogen with unknown relevance to humans

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

### **SECTION 12: Ecological Information**

### 12.1. Toxicity

### B920FS Bost 920FS Product Series

#### Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmondesmus subspicatus)	CL50 (96h)>10000mg/L Fish (Oncorhynchus mykiss)		CE50 (48h) >1000 mg/L Daphnia Magna
Propylene carbonate 108-32-7	EC50 72 h > 500 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1000 mg/L (Cyprinus carpio semi-static) LC50 96 h = 5300 mg/L (Leuciscus idus static)	EC50 > 10000 mg/L 17 h	EC50 48 h > 500 mg/L (Daphnia magna )
m-Xylene 108-38-3	EC50 72 h = 4.9 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 14.3 - 18 mg/L (Pimephales promelas flow-through) LC50 96 h = 8.4 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h = 12.9 mg/L (Poecilia reticulata semi-static)		EC50 48 h 2.81 - 5.0 mg/L (Daphnia magna Static)
p-Xylene 106-42-3	EC50 72 h = 3.2 mg/L (Pseudokirchneriella subcapitata) EC50 3 h = 105.1 mg/L (Chlorella vulgaris)	LC50 96 h 7.2 - 9.9 mg/L (Pimephales promelas static) LC50 96 h = 2.6 mg/L (Oncorhynchus mykiss) LC50 96 h = 2.6 mg/L (Oncorhynchus mykiss static) LC50 96 h = 8.8 mg/L (Poecilia reticulata semi-static)	EC50 = 5.7 mg/L 30 min	EC50 48 h 3.55 - 6.31 mg/L (Daphnia magna Static)
Carbon black 1333-86-4	>10000 mg/l (Desmodesmus subspicatus) OECD 202	>1000 mg/l (Brachydanio rerio) OCDE 203		EC50 24 h > 5600 mg/L (Daphnia magna )
Isophorone diisocyanate 4098-71-9	EC50 72 h = 118.7 mg/L (Desmodesmus subspicatus)	LC50 48 h = 1.8 mg/L (Leuciscus idus static)		EC50 24 h = 83.7 mg/L (Daphnia magna )
Ethylbenzene 100-41-4	EC50 72 h = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata) EC50 96 h 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 11.0 - 18.0 mg/L (Oncorhynchus mykiss static) LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h 7.55 - 11 mg/L (Pimephales promelas flow-through) LC50 96 h = 32 mg/L (Lepomis macrochirus static) LC50 96 h 9.1 - 15.6 mg/L (Pimephales promelas static) LC50 96 h = 9.6 mg/L (Poecilia reticulata static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h 1.8 - 2.4 mg/L (Daphnia magna )

### 12.2. Persistence and Degradability

No information available.

### 12.3. Bioaccumulative Potential

No information available.

### 12.4. Mobility in Soil

No information available.

### 12.5 Other adverse effects

No information available

## SECTION 13: Disposal Considerations

B920FS Bost 920FS Product Series	Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01
13.1. Waste Treatment Methods	
Disposal of Wastes	It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations
Contaminated Packaging	Dispose of in accordance with federal, state and local regulations
SECTION 14: Transport Infor	mation
Note:	49 CFR 173.150(f)(2) "The requirements in this subchapter do not apply to a material classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant."
DOT UN/ID No Proper Shipping Name Hazard Class Packing Group Special Provisions Description Emergency Response Guide Number	NA1993 Combustible liquid, n.o.s. Combustible liquid III IB3, T1, T4, TP1 NA1993, Combustible liquid, n.o.s. (Xylenes), Combustible liquid, III, 128
ΙΑΤΑ	Not regulated
IMDG	Not regulated

## SECTION 15: Regulatory Information

## Global Inventories

TSCA	Listed
DSL	Not Listed

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory **DSL** - Canadian Domestic Substances List **Listed** - The components of this product are either listed or exempt from listing on inventory. **Not Listed** - One or more components of this product are not listed on inventory.

### <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B3 - Combustible liquid D2A - Very toxic materials



#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical

### B920FS Bost 920FS Product Series

#### Revision Date 03-Sep-2015 Supersedes Date: No information available Version 1.01

or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No
m-Xylene	108-38-3
Ethylbenzene	100-41-4

### California Proposition 65

This product contains one or more of the substances listed on Proposition 65 at or above 0.01 wt. %

Chemical Name	CAS No
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1
Titanium dioxide	13463-67-7
Carbon black	1333-86-4
Ethylbenzene	100-41-4
Quartz	14808-60-7

### <u>Europe</u>

### Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation.

## EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 16: Other Information					
HMIS_	Health Hazards 2*	Flammability 2	Physical Hazards 0	Personal Protection X	
Key or Legend to Abbreviations and Acronyms Used in the Safety Data Sheet No information available					
Key Literature References and Sources for Data No information available					
Prepared By	Product Sa	Product Safety & Regulatory Affairs			
Revision Date	03-Sep-20	03-Sep-2015			
Revision Note	Not applica	Not applicable.			
Training Advice	No informa	No information available			
Further Information	No informa	No information available			

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### **End of Safety Data Sheet**