

# USA SAFETY DATA SHEET



# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Product Use/Class: LORD 312 A Epoxy Adhesive, Part 1 of 2

LORD Corporation 111 LORD Drive Cary, NC 27511-7923 USA

Telephone: 814 868-3180 Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

## **EFFECTIVE DATE:** 08/02/2017

## 2. HAZARDS IDENTIFICATION

## **GHS CLASSIFICATION:**

Flammable liquids Category 4
Acute toxicity Inhalation - Dust and Mist Category 4 - 90.9% of the mixture consists of ingredient(s) of unknown toxicity.
Acute toxicity Inhalation - Vapours Category 4 - 90.9% of the mixture consists of ingredient(s) of unknown toxicity. Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Skin sensitization Category 1
Germ cell mutagenicity Category 2
Carcinogenicity Category 2
Specific target organ systemic toxicity (repeated exposure) Category 1 Respiratory system
Hazardous to the aquatic environment - chronic hazard Category 2

# GHS LABEL ELEMENTS:

Symbol(s)



Signal Word

DANGER

## **Hazard Statements**

Combustible liquid. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.(Respiratory system) Toxic to aquatic life with long lasting effects.

# **Precautionary Statements**

## Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

## Response

In case of fire: refer to section 5 of SDS for extinguishing media. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash before reuse. Collect spillage.

#### Storage

Store in a well-ventilated place. Keep cool. Store locked up.

#### **Disposal:**

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

## Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Harmful if absorbed through skin. Significant overexposure to n-butyl glycidyl ether by the inhalation route is unlikely under most ambient conditions due to its low volatility. However, vapors, aerosols, and mists may be formed during some applications such as heating or applications of uncured material on large surface areas. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses. Chronic: None known.

<u>hemical Name</u>	CAS Number	Range
Epoxy resin	PROPRIETARY	55 - 60 %
Glycidyl ether polymer	PROPRIETARY	20 - 25 %
Bisphenol A epoxide	PROPRIETARY	5 - 10 %
N-Butyl glycidyl ether	2426-08-6	5 - 10 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

## 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

Page: 2

# **5. FIRE-FIGHTING MEASURES**

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog, Alcohol **UNSUITABLE EXTINGUISHING MEDIA:** Not determined for this product.

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Keep containers tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:** Avoid contact. Avoid breathing vapors. Use appropriate respiratory protection for large spills or spills in confined area.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Scoop spilled material into an appropriate container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

## 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

STORAGE: Store only in well-ventilated areas. Keep container closed when not in use.

INCOMPATIBILITY: Amines, acids, water, hydroxyl, or active hydrogen compounds.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### COMPONENT EXPOSURE LIMIT

Chemical Name	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	<u>Skin</u>
Epoxy resin	N.E.	N.E.	N.E.	N.E.	N.A.
Glycidyl ether polymer	N.E.	N.E.	N.E.	N.E.	N.A.
Bisphenol A epoxide	N.E.	N.E.	N.E.	N.E.	N.A.
N-Butyl glycidyl ether	3 ppm	N.E.	270 mg/m3 50 ppm	N.E.	S

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

**Engineering controls:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

## PERSONAL PROTECTION MEASURES/EQUIPMENT:

**RESPIRATORY PROTECTION:** Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR: APPEARANCE: PHYSICAL STATE: FLASH POINT:	Mild Yellow Liquid 171 °F, 77 °C Setaflash Closed Cup	VAPOR PRESSURE: VAPOR DENSITY: LOWER EXPLOSIVE LIMIT: UPPER EXPLOSIVE LIMIT:	N.D. Heavier than Air Not Applicable Not Applicable
<b>BOILING RANGE:</b>	N.A.	EVAPORATION RATE:	Not Applicable
AUTOIGNITION TEMPERATURE:	N.D.	DENSITY:	1.13 g/cm3 - 9.39 lb/gal
DECOMPOSITION TEMPERATURE:	N.D.	VISCOSITY, DYNAMIC:	N.D.
ODOR THRESHOLD:	N.D.	VISCOSITY, KINEMATIC:	N.D.
SOLUBILITY IN H2O:	Insoluble	VOLATILE BY WEIGHT:	0.00~%
pH:	N.A.	VOLATILE BY VOLUME:	0.00 %
FREEZE POINT:	N.D.	VOC CALCULATED:	0 lb/gal, 0 g/l0 g/l
COEFFICIENT OF WATER/OIL DISTRIBUTION:	N.D.		

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

## **10. STABILITY AND REACTIVITY**

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

**CONDITIONS TO AVOID:** High temperatures.

**INCOMPATIBILITY:** Amines, acids, water, hydroxyl, or active hydrogen compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, aldehydes

#### **11. TOXICOLOGICAL INFORMATION**

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

#### **TOXICITY MEASURES:**

Chemical Name	LD50/LC50
Epoxy resin	Oral LD50: Rat 11,400 mg/kg
Glycidyl ether polymer	N.D.
Bisphenol A epoxide	N.D.
N-Butyl glycidyl ether	Oral LD50: Rat 2,050 mg/kg
	Dermal LD50: Rat > 2,150 mg/kg
	Inhalation LC50: Rat 2590 ppm/4 h

**Germ cell mutagenicity:** Category 2 - Suspected of causing genetic defects. Components contributing to classification: N-Butyl glycidyl ether.

Carcinogenicity: Category 2 - Suspected of causing cancer.

Components contributing to classification: N-Butyl glycidyl ether.

Reproductive toxicity: No classification proposed

## **12. ECOLOGICAL INFORMATION**

## **ECOTOXICITY:**

Chemical Name	Ecotoxicity	
Epoxy resin	N.D.	
Glycidyl ether polymer	N.D.	
Bisphenol A epoxide	N.D.	
N-Butyl glycidyl ether	N.D.	

**PERSISTENCE AND DEGRADABILITY:** Not determined for this product.

**BIOACCUMULATIVE:** Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

**OTHER ADVERSE EFFECTS:** Not determined for this product.

## **13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

#### 14. TRANSPORT INFORMATION

**US DOT Road** 

CS D C I HOMA		
DOT Proper Shipping Name:	Environmentally hazardous substances, liquid, n.o.s.	
DOT Hazard Class:	9	
SECONDARY HAZARD:	None	
DOT UN/NA Number:	3082	
Packing Group:	III	
<b>Emergency Response Guide Number:</b>	171	
For US DOT non-bulk road shipments this material may be classified as NOT REGULATED. For the most		
accurate shipping information, refer to your transportation/compliance department regarding changes in		

accurate shipping information, refer to your transportation/compliance department regarding changes i package size, mode of shipment or other regulatory descriptors.

IATA Cargo	
PROPER SHIPPING NAME:	Environmentally hazardous substance, liquid, n.o.s.
DOT Hazard Class:	9
HAZARD CLASS:	None
UN-NUMBER:	3082
PACKING GROUP:	III
EMS:	9L
<u>IMDG</u>	
PROPER SHIPPING NAME:	Environmentally hazardous substance, liquid, n.o.s.
DOT Hazard Class:	9
HAZARD CLASS:	None
UN-NUMBER:	3082
PACKING GROUP:	III
EMS:	F-A

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

# **15. REGULATORY INFORMATION**

# **U.S. FEDERAL REGULATIONS: AS FOLLOWS:**

#### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.: None

## TOXIC SUBSTANCES CONTROL ACT:

#### **INVENTORY STATUS**

The chemical substances in this product are on the TSCA Section 8 Inventory.

#### **EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

## **16. OTHER INFORMATION**

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

**HMIS RATINGS -** HEALTH: 2 FLAMMABILITY: 2 PHYSICAL HAZARD: 0 \* - Indicates a chronic hazard; see Section 2

**Revision:** Section 3

**Effective Date:** 08/02/2017

### DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.