



MSDS Name

DEVCON® Dev-Thane 5™ grey [1:1]

Manufacturer Name

14500

Stock No.:


1/15/2011

ITW Devcon

Kit MSDS Revision Date KIT MSDS Revision Notes

Formula Update

Components				
	DEV-THANE 5 (PART B)			
	Dev-Thane 5 Resin			
ITW Devcon Product Code: 14500				







SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: DEV-THANE 5 (PART B)

Manufacturer Name: ITW Devcon

Address: 30 Endicott Street

Danvers, MA 01923

General Phone Number: (978) 777-1100

Emergency Phone Number: (800) 424-9300

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

MSDS Revision Date: 1/15/2011

HMIS		
Health Hazard	1	
Fire Hazard	1	
Reactivity	0	
Personal Protection	x	

* Chronic Health Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	
Higher oligimers of methane diisocyanate (MDI)	N/A	60 - 100 by weight	

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Irritant.

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: Can cause moderate irritation, burning sensation, tearing, redness, and

swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage

and permanent injury...

Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling.

Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache,

and anesthetic effects.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal

tract and abdominal pain.

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening,

swelling, and possible tissue destruction.

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes.

Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes,

while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or

give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center

immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: >325°F (162.7°C)

Flash Point Method: Pensky-Martens Closed Cup

Auto Ignition Temperature: Not determined.
Lower Flammable/Explosive Limit: Not determined.
Upper Flammable/Explosive Limit: Not determined.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire

exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this

material.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH

(approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill Cleanup Measures: Absorb spill with inert material (e,g., dry sand or earth), then place in a

chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush

spill area with soap and water to remove trace residue.

Avoid personal contact and breathing vapors or mists. Ventilate area. Use

proper personal protective equipment as listed in section 8.

Personnel Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering

the spill area.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Other Precautions: Pump or shovel to storage/salvage vessels.

SECTION 7 - HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Storage: Store in a cool, dry, well ventilated area away from sources of heat and

incompatible materials. Keep container tightly closed when not in use.

Special Handling Procedures: Provide appropriate ventilation/respiratory protection against decomposition

products (see Section 10) during welding/flame cutting operations and to

protect against dust during sanding/grinding of cured product.

Hygiene Practices: Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust

ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR

1910.133, OSHA eye and face protection regulation, or the European standard

EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent

skin contact. Consult manufacturer's data for permeability data.

Respiratory Protection:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or

canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may

not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash

and a deluge shower safety station.

EXPOSURE GUIDELINES

Notes: Only established PEL and TLV values for the ingredients are listed.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid..

Color: Gray.

Odor: mild.

Boiling Point: Not determined.

Melting Point: Not determined.

Specific Gravity: 1.4

Solubility: negligible

Vapor Density: > 1 (air = 1)

Vapor Pressure: Not determined.

Percent Volatile: Not determined.

Evaporation Rate: Not determined.

pH: Not determined.

Molecular Formula: Mixture
Molecular Weight: Mixture

Flash Point: >325°F (162.7°C)

Flash Point Method: Pensky-Martens Closed Cup

Auto Ignition Temperature: Not determined.

VOC Content: Not determined.

Percent Solids by Weight Not determined.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Not reported.

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and

oxidizing conditions.

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11 - TOXICOLOGICAL INFORMATION

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

RCRA Number: None.

SECTION 14 - TRANSPORT INFORMATION

DOT UN Number: N/A

DOT Hazard Class: Not applicable.

DOT Packing Group: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Canadian Regulations. WHMIS Hazard Class(es): None.

All components of this product are on the Canadian Domestic Substances List.

SECTION 16 - ADDITIONAL INFORMATION

HMIS Fire Hazard: 1
HMIS Health Hazard: 1
HMIS Reactivity: 0
HMIS Personal Protection: x

MSDS Revision Date: 1/15/2011

MSDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our knowledge and

belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent

personnel, within a controlled environment.

Copyright© 1996-2011 Actio Software Corporation. All Rights Reserved.

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Dev-Thane 5 Resin

MSDS Manufacturer 14514

Number:

Manufacturer Name: ITW Devcon
Address: 30 Endicott Street

Danvers, MA 01923

General Phone Number: (978) 777-1100 Emergency Phone Number: (800) 424-9300

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

MSDS Revision Date: 1/15/2011



Chronic Health
Effects

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
4,4'-Diphenylmethane diisocyanate	101-68-8	60 -100 by weight
1,1'-Methylenebis (isocyanato)benzene	26447-40-5	1-10 by weight

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Irritant. Potential Sensitizer Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: Can cause moderate irritation, burning sensation, tearing, redness, and

swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage

and permanent injury.

Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling.

Allergic reactions are possible.

May cause skin sensitization, an allergic reaction, which becomes evident on

reexposure to this material.

Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache,

and anesthetic effects. May cause respiratory sensitization with asthma-like

symptoms in susceptible individuals.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal

tract and abdominal pain.

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening,

swelling, and possible tissue destruction.

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Conditions:

Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product. Isocyanate exposure levels must be monitored. Medical supervision of all employees who handle or come in contact with isocyanates is recommended (i.e. FEV, FVC). This should include pre-employment and periodic medical examinations.

Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases, recurrent skin eczema or sensitization should be excluded from working with this product. Once sensitized no further exposure can be permitted.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes.

Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes,

while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or

give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center

immediately. Never give anything by mouth to an unconscious person.

Note to Physicians: Asthmatic type symptoms may develop, which may be immediate or delayed

for several hours.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 388°F (197.7°C)
Flash Point Method: Estimated (literature)
Auto Ignition Temperature: Not determined.
Lower Flammable/Explosive Limit: Not determined.
Upper Flammable/Explosive Limit: Not determined.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire

exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this

material.

Unsuitable Media: Water may cause frothing.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH

(approved or equivalent) and full protective gear.

Unusual Fire Hazards: Do not reseal containers if contaminated with water, resin will react with water

to release carbon dioxide. As a result of the water contamination, pressure

will build up in the sealed container causing it to rupture.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spill Cleanup Measures: Absorb spill with inert material (e,g., dry sand or earth), then place in a

chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. Neutralize residue with appropriate neutralizer. Do not attempt to neutralize large quantities of material unless measures to control reactivity and heat generation have been taken. After removal, flush spill area with soap and water to remove trace

residue.

Avoid personal contact and breathing vapors or mists. Ventilate area. Use

proper personal protective equipment as listed in section 8.

A blanket of protein foam may be placed over spill for temporary control of

isocyanate vapor.

Personnel Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering

the spill area.

Environmental Precautions:

Avoid runoff into storm sewers, ditches, and waterways.

Other Precautions:

Pump large quantities into closed but not sealed metal containers. Isocyanates will react with water and generate carbon dioxide, this could result in the

rupture of any closed containers.

Neutralize using 10 parts neutralizer to 1 part isocyanate solution. Mix and allow to stand for 48 hrs in containers, letting evolved carbon dioxide to vent. Neutralizer consist of 90% water, 3-8% concentrated ammonia (or sodium

carbonate), 2% detergent.

SECTION 7 - HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Storage: Store in a cool, dry, well ventilated area away from sources of heat and

incompatible materials. Keep container tightly closed when not in use. Do not reseal container If moisture or water contamination is suspected. Water contaminated material in a sealed container may rupture due to pressure

buildup.

Special Handling Procedures: Provide appropriate ventilation/respiratory protection against decomposition

products (see Section 10) during welding/flame cutting operations and to

protect against dust during sanding/grinding of cured product.

Hygiene Practices: Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust

ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR

1910.133, OSHA eye and face protection regulation, or the European standard

EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent

skin contact. Consult manufacturer's data for permeability data.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or

canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels

respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash

and a deluge shower safety station.

EXPOSURE GUIDELINES

4,4'-Diphenylmethane diisocyanate:

Guideline ACGIH: 0.005 ppm

TLV-TWA: 0.005 ppm

Guideline OSHA: PEL-Ceiling/Peak: 0.02 ppm

Notes: Only established PEL and TLV values for the ingredients are listed.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid...

Other Precautions:

Odor:

Boiling Point:

Melting Point:

Pale to dark yellow.

Slightly musty.

Not determined.

60-68°F (15.5-20°C)

Specific Gravity: 1.19 @ 77°F
Solubility: Insoluble

Vapor Density: 8.5 MDI (air = 1)

Vapor Pressure: < 10 mmHg @77°F (MDI)

Percent Volatile: Negligible

Evaporation Rate: Not determined.

pH: Not determined.

Molecular Formula: Mixture
Molecular Weight: Mixture

Flash Point: 388°F (197.7°C)
Flash Point Method: Estimated (literature)
Auto Ignition Temperature: Not determined.

VOC Content: Not determined.

Percent Solids by Weight

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Polymerization may occur under certain conditions.

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and

oxidizing conditions. Moisture and extended exposure over 85 F.

Incompatible Materials: Alcohols, amines, strong bases (alkali, ammonia), acids, metal compounds,

moisture or water. Resin reacts with water to give off carbon dioxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

4,4'-Diphenylmethane diisocyanate:

RTECS Number: NQ9350000

Eye - Rabbit Standard Draize test.: 100 mg

Skin: Administration onto the skin - Mouse : 0.09 pph/2D (Intermittent) [Blood -

Other changes Skin and Appendages - Cutaneous sensitization, experimental

(After topical exposure)]

Administration onto the skin - Mouse : 220 mg/kg/12D (Intermittent) [Skin and Appendages - Cutaneous sensitization, experimental (After topical exposure) Biochemical - Metabolism (Intermediary) - Other proteins

Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation

of inflammation]

Administration onto the skin - Mouse : 2 pph/2W (Intermittent)

[Immunological Including Allergic - Increase in humoral immune response]

Administration onto the skin - Mouse : 2 pph/4W (Intermittent)

[Immunological Including Allergic - Increase in humoral immune response] Administration onto the skin - Mouse : 280 mg/kg/14D (Intermittent) [Immunological Including Allergic - Increase in humoral immune response]

Administration onto the skin - Rabbit : 500 mg/24H

Inhalation: Inhalation - Rat LC50: 178 mg/m3 [Details of toxic effects not reported other

than lethal dose value]

Ingestion: Oral - Rat LD50: 9200 mg/kg [Behavioral - Somnolence (general depressed

activity) Behavioral - Ataxia Nutritional and Gross Metabolic - Body

temperature decrease]

Oral - Mouse LD50: 2200 mg/kg [Details of toxic effects not reported other

than lethal dose value]

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

RCRA Number: Not determined.

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name:

DOT UN Number:

Not applicable.

DOT Hazard Class:

Not applicable.

Not applicable.

SECTION 15 - REGULATORY INFORMATION

4,4'-Diphenylmethane diisocyanate:

TSCA Inventory Status: Listed

SARA: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

New Jersey: Listed: NJ Hazardous List; Substance Number: 3757

Massachussetts: Listed
Pennsylvania: Listed
Canada DSL: Listed

1,1'-Methylenebis (isocyanato)benzene:
TSCA Inventory Status: Listed
Canada DSL: Listed

Canadian Regulations. WHMIS Hazard Class(es): D2A

All components of this product are on the Canadian Domestic Substances List.

SECTION 16 - ADDITIONAL INFORMATION

HMIS Fire Hazard: 1
HMIS Health Hazard: 3*
HMIS Reactivity: 1
HMIS Personal Protection: X

MSDS Revision Date: 1/15/2011

MSDS Author: Actio Corporation

Disclaimer: This Health and Safety Inform

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent

personnel, within a controlled environment.

 $\label{lem:copyright} \ \ \, \text{Copyright} \\ @ \ \ \, \text{1996-2011 Actio Software Corporation. All Rights Reserved.}$