

Revision Date: 09/02/2016

SS4044P

SAFETY DATA SHEET

1. Identification

Product identifier: SS4044P

Other means of identification

Synonyms: Silicone primer solution

Recommended use and restriction on use

Recommended use: Primer Restrictions on use: Not known.

Manufacturer/Importer/Distr :

ibutor Information

Momentive Performance Materials LLC

260 Hudson River Road Waterford NY 12188

Contact person : commercial.services@momentive.com

Telephone : General information

+1-800-295-2392

Emergency telephone

number

Supplier : CHEMTREC

1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 2

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Toxic to reproduction Category 1B
Specific Target Organ Toxicity - Category 1^{1.}

Single Exposure

Specific Target Organ Toxicity - Category 3²

Single Exposure

Specific Target Organ Toxicity - Category 1³

Repeated Exposure

SDS_US 1/21



Revision Date: 09/02/2016

SS4044P

Target Organs

- 1. respiratory tract irritation, narcotic effects, Central nervous system., Kidneys, Liver
- 2. narcotic effects, respiratory tract irritation, Central nervous system., Kidneys, Liver
- 3. Central nervous system., Kidneys, Liver, Skin, respiratory tract, hearing organs

Label Elements

Hazard Symbol:



Signal Word: No signal word.

Hazard Statement: Highly flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

May damage fertility or the unborn child.

Causes damage to organs.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statement

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapors. Do not eat, drink or smoke when using this product. Wash hands

thoroughly after handling.

Response: Get medical advice/attention if you feel unwell. IF exposed: Call a POISON

CENTER/doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists:

SDS_US 2/21



Revision Date: 09/02/2016

SS4044P

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

Substance(s) formed under the

Silicone resin in solvent(s)

conditions of use:

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
Acetone	67-64-1	15 - 40%	# This substance has workplace exposure limit(s).
2-Propanol	67-63-0	15 - 40%	# This substance has workplace exposure limit(s).
Xylene	1330-20-7	15 - 40%	# This substance has workplace exposure limit(s).
Ethylbenzene	100-41-4	5 - 10%	# This substance has workplace exposure limit(s).
Tetraethyl Silicate, Tetraethoxysilane	78-10-4	1 - 5%	# This substance has workplace exposure limit(s).
n-BUTANOL	71-36-3	1 - 5%	# This substance has workplace exposure limit(s).

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

SDS_US 3/21



Revision Date: 09/02/2016

SS4044P

Ingestion: Do NOT induce vomiting. Do not give victim anything to drink if he is

unconscious.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration

using a barrier device. If breathing is difficult give oxygen. Get medical

attention.

Skin Contact: Wash area with soap and water.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least

15 minutes. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: None known.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: No data available.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Carbon dioxide Alcohol foam.

Unsuitable extinguishing

media:

No data available.

Specific hazards arising from

the chemical:

No data available.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Extremely flammable. Pressure inside container is increased when heated, and may cause explosion. Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask

and full protective clothing.

SDS_US 4/21



Revision Date: 09/02/2016

SS4044P

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Avoid contact with skin and eyes. Keep out of reach of children. Avoid inhalation of vapors and spray mists.

Methods and material for containment and cleaning up:

Wear proper protective equipment as specified in the protective equipment section. Warn other workers of spill. Keep unauthorized personnel away. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is expected; material has a flash point below

200 F.

Conditions for safe storage, including any incompatibilities:

Keep away from heat, sparks and open flame. Keep container closed. Store

in original container.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Lim	it Values	Source
Acetone	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	REL	250 ppm	590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	750 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
2-Propanol	TWA	200 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	400 ppm		US. ACGIH Threshold Limit Values (03 2015)
	REL	400 ppm	980 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	500 ppm	1,225 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	400 ppm	980 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm	980 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm	1,225 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Xylene	TWA	100 ppm	•	US. ACGIH Threshold Limit Values (03 2015)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (03 2015)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

SDS_US 5/21



Revision Date: 09/02/2016

SS4044P

Г				
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	150 ppm	655 mg/m3	ÙS. ÓSHA Table Z-1-A (29 CFR 1910.1000)
				(1989)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (03 2015)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical
				Hazards (2010)
	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical
				Hazards (2010)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
				(1989)
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
				(1989)
Tetraethyl Silicate,	TWA	10 ppm		US. ACGIH Threshold Limit Values (03 2015)
Tetraethoxysilane				
	REL	10 ppm	85 mg/m3	US. NIOSH: Pocket Guide to Chemical
				Hazards (2010)
	PEL	100 ppm	850 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm	85 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
BUTANOL	Tine			(1989)
n-BUTANOL	TWA	20 ppm		US. ACGIH Threshold Limit Values (03 2015)
	Ceil_Time	50 ppm	150 mg/m3	US. NIOSH: Pocket Guide to Chemical
	55.			Hazards (2010)
	PEL	100 ppm	300 mg/m3	US. OSHA Table Z-1 Limits for Air
	0 ""			Contaminants (29 CFR 1910.1000) (02 2006)
1	Ceiling	50 ppm	150 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)
				(1989)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Acetone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEI (03 2015)
2-Propanol (acetone: Sampling time: End of shift at end of work week.)	40 mg/l (Urine)	ACGIH BEI (03 2015)
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2015)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (03 2015)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Ventilation and other forms of engineering controls are preferred for

controlling exposures. Respiratory protection may be needed for non-

routine or emergency situations.

Eye/face protection: Monogoggles

SDS_US 6/21



Revision Date: 09/02/2016

SS4044P

Skin Protection

Hand Protection: Rubber or plastics gloves Nitrile gloves are recommended.

Other: Wear suitable protective clothing and eye/face protection.

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced,

NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA

regulations (see 29CFR 1910.134).

Hygiene measures: No data available.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Pale yellow
Odor: Pungent

Odor threshold:

pH:

No data available.

not applicable

not applicable

not applicable

not applicable

rot applicable

rot applicable

rot applicable

rot applicable

rot applicable

rot applicable

Evaporation rate:No data available.
Flammability (solid, gas):
No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 12.00 %(V)
Flammability limit - lower (%): 2.10 %(V)

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

No data available.

No data available.

Vapor pressure: not applicable

Vapor density:No data available.Density:ca. 0.855 g/cm3

Relative density: 0.80

Solubility(ies)

Solubility in water: hydrolyses

SDS_US 7/21



Revision Date: 09/02/2016

SS4044P

No data available.

Solubility (other): Soluble, Aromatic Solvent

Partition coefficient (n-octanol/water) Log

Pow:

Auto-ignition temperature: > 343 °C

Decomposition temperature:No data available.SADT:No data available.Viscosity, dynamic:No data available.Viscosity, kinematic:< 20.5 mm2/s (25 °C)</th>

VOC: 624 g/l

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: No data available.

Possibility of hazardous

reactions:

Hazardous polymerisation does not occur.

Conditions to avoid: Keep away from sources of ignition - No smoking. Keep away from sources

of ignition - No smoking.

Incompatible Materials: Oxidizing agents.

Hazardous Decomposition

Products:

Carbon dioxide Silicon dioxide.

11. Toxicological information

Information on likely routes of exposure

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

SDS_US 8/21



Revision Date: 09/02/2016

SS4044P

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: No data available.

Specified substance(s):

Acetone LD 50 (Rat, No data available.): 5,800 mg/kg

LD 50 (Mouse, No data available.): 3,000 mg/kg

2-Propanol LD 50 (Rat): 5,045 mg/kg

LD 50 (Mouse): 3,600 mg/kg

Xylene LD 50 (Rat): 5,000 mg/kg

Ethylbenzene LD 50 (Rat, No data available.): 2,700 mg/kg

Tetraethyl Silicate, LD 50 (Rat, No data available.): 6,270 mg/kg

Tetraethoxysilane LD 50: > 2,000 mg/kg

n-BUTANOL LD 50 (Rat, No data available.): 790 mg/kg

LD 50 (Rabbit, No data available.): 3,484 mg/kg

Dermal

Product: No data available.

SDS_US 9/21



Revision Date: 09/02/2016

SS4044P

Specified substance(s):

Acetone LD 50 (Rabbit, No data available.): 20,000 mg/kg

2-Propanol LD 50 (Rat): 12,800 mg/kg

LD 50 (Rabbit): 12,800 mg/kg LD 50 (Rabbit): 12,800 mg/kg

Xylene LD 50 (Rabbit): 2,000 mg/kg

LD 50 (Rat): 2,000 mg/kg

Ethylbenzene LD 50 (Rabbit, No data available.): 15,354 mg/kg

LD 50 (Rabbit, No data available.): 5,000 mg/kg

Tetraethyl Silicate, Tetraethoxysilane

ilcate, ED 50 (Nabbit, No data available

LD 50 (Rabbit, No data available.): 5,875 mg/kg

n-BUTANOL LD 50 (Rabbit, No data available.): 3,400 mg/kg

LD 50 (Rat, No data available.): 4,200 mg/kg

Inhalation

Product: No data available.

Specified substance(s):

Acetone LC50 (Rat, No data available.): 38.6 mg/l

(Rat, No data available.): 7.2 mg/l

Xylene LC50 (Rat): 29.49 mg/l

Ethylbenzene (Rat, No data available.): 3.4 mg/l

(Rat, No data available.): 1.7 mg/l LC50 (Rat, No data available.): 17.6 mg/l

•

Tetraethyl Silicate,

Tetraethoxysilane

TDLo (Rat, No data available.): 1 mg/l

n-BUTANOL LC50 (Rat, No data available.): 24 mg/l

Repeated dose toxicity

Product: No data available.

SDS_US 10/21



Revision Date: 09/02/2016

SS4044P

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene Overall evaluation: 2B. Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

SDS_US 11/21



Revision Date: 09/02/2016

SS4044P

Specific Target Organ Toxicity - Single Exposure: respiratory tract irritation, narcotic effects, Central nervous system., Kidneys, Liver

Specific Target Organ Toxicity - Single Exposure: narcotic effects, respiratory tract irritation, Central nervous system., Kidneys, Liver

Specific Target Organ Toxicity - Repeated Exposure: Central nervous system., Kidneys, Liver, Skin, respiratory tract, hearing organs

Aspiration Hazard

Product: No data available.

Other effects: More severe effects if alcohol is consumed., Stimulants such as epinephrine

may induce ventricular fibrillation., This product contains a component that showed unexpected acute toxicity to pregnant rabbits in a gavage study conducted by the Chemical Manufacturers Association. There were no unexpected toxic effects in pregnant rats exposed in the same study. No developmental effects were noted in either study. Effect levels in rabbits were several times the maximum exposure which would occur at the TLV

for this component.

Contains ethylbenzene, which has shown evidence of carcinogenic activity

in animals.

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Oral

No data available.

Dermal

No data available.

Inhalation

No data available.

Repeated dose toxicity

No data available.

SDS_US 12/21



Revision Date: 09/02/2016

SS4044P

Skin Corrosion/Irritation

No data available.

Serious Eye Damage/Eye Irritation

No data available.

Respiratory or Skin Sensitization

No data available.

Carcinogenicity

No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No data available.

US. National Toxicology Program (NTP) Report on Carcinogens:

No data available.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No data available.

Germ Cell Mutagenicity

In vitro

No data available.

Germ Cell Mutagenicity

In vivo

No data available.

Reproductive toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

No data available.

Specific Target Organ Toxicity - Single Exposure

No data available.

Target Organs

SDS_US 13/21



Revision Date: 09/02/2016

SS4044P

Aspiration Hazard

No data available.

Other effects

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Acetone LC50 (Lepomis macrochirus, 96 h): 8,300 mg/l

LC0 (Leuciscus idus, 48 h): 6,320 mg/l LC50 (Leuciscus idus, 48 h): 7,505 mg/l

2-Propanol LC50 (Leuciscus idus, 48 h): 8,970 mg/l

LC50 (Pimephales promelas, 96 h): > 65,500 mg/l

Xylene LC50 (Leuciscus idus, 48 h): 86 mg/l

LC50 (Pimephales promelas, 96 h): 13.4 mg/l

LC50 (Salmo gairdneri, 96 h): 14 mg/l

Ethylbenzene LC0 (Leuciscus idus, 48 h): 26 mg/l

LC100 (Leuciscus idus, 48 h): 70 mg/l LC50 (Leuciscus idus, 48 h): 44 mg/l LC50 (Salmo gairdneri, 96 h): 4.2 mg/l

Tetraethyl Silicate, LC100 (No data available., 24 h): 9,000 mg/l LC50 (Brachydanio rerio, 96 h): > 245 mg/l

n-BUTANOL LC0 (Leuciscus idus, 48 h): > 1,000 mg/l

LC50 (Leuciscus idus, 48 h): 1,520 mg/l LC50 (Pimephales promelas, 96 h): 1,730 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

2-Propanol EC50 (Daphnia magna, 24 h): > 10,000 mg/l

EC0 (Daphnia magna): 500 mg/l

Xylene EC50 (Daphnia magna, 24 h): 165 mg/l

Ethylbenzene LC0 (Daphnia magna): 137 mg/l

SDS_US 14/21



Revision Date: 09/02/2016

SS4044P

(Daphnia magna): 184 mg/l

LC100 (Daphnia magna): 200 mg/l

Tetraethyl Silicate, Tetraethoxysilane EC50 (Blue Crab): 7,800 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Acetone 50 % (5 d, No data available.)

78 % (28 d, No data available.)

2-Propanol 82.5 % (5 d, No data available.)

Ethylbenzene 68 % (28 d, No data available.)

Tetraethyl Silicate, 98 % (28 d, OECD-Guideline 301 A (DOC Die-Away Test)) Readily

Tetraethoxysilane biodegradable

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

SDS_US 15/21



Revision Date: 09/02/2016

SS4044P

Mobility in Soil: No data available.

Known or predicted distribution to environmental compartments

Acetone No data available.

2-Propanol No data available.

Xylene No data available.

Ethylbenzene No data available.

Tetraethyl Silicate, No data available.

Tetraethoxysilane

n-BUTANOL No data available.

Known or predicted distribution to environmental compartments

Polyalkylsiloxane No data available.

Other Adverse Effects: No data available.

13. Disposal considerations

Disposal instructions: Disposal should be made in accordance with federal, state and local

regulations.

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT

UN Number: UN 1993

UN Proper Shipping Name: Flammable liquids, n.o.s.(Acetone, Isopropanol)

Transport Hazard Class(es)

Class: 3
Label(s): 3
Packing Group: II
Marine Pollutant: No

IMDG

UN Number: UN 1993

UN Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (Acetone, Isopropanol)

Transport Hazard Class(es)

Class: 3 Label(s): 3

EmS No.: F-E, S-E

Packing Group: II
Marine Pollutant: No
Limited quantity 1.00L

Excepted quantity E2

SDS_US 16/21



Revision Date: 09/02/2016

SS4044P

IATA

UN Number: UN 1993

Proper Shipping Name: Flammable liquid, n.o.s.(Acetone, Isopropanol)

Transport Hazard Class(es):

Class: 3
Label(s): 3
Packing Group: II
Cargo aircraft only Packing 364

Instructions:

Passenger and cargo aircraft

Packing Instructions:

364

Limited quantity: 1.00L Packing Instructions: Y341

Excepted quantity E2

Environmental Hazards: Not regulated.

Marine Pollutant: No

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical IdentityReportable quantityAcetone5,000 lbs.2-Propanol100 lbs.Xylene100 lbs.Ethylbenzene1,000 lbs.n-BUTANOL5,000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SDS_US 17/21



Revision Date: 09/02/2016

SS4044P

SARA 304 Emergency Release Notification

<u>Chemical Identity</u> <u>Reportable quantity</u>

Acetone 5,000 lbs.
2-Propanol 100 lbs.
Xylene 100 lbs.
Ethylbenzene 1,000 lbs.
n-BUTANOL 5,000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity

Acetone 10000 lbs 2-Propanol 10000 lbs Xylene 10000 lbs Ethylbenzene 10000 lbs Tetraethyl Silicate, 10000 lbs

Tetraethoxysilane

n-BUTANOL 10000 lbs

SARA 313 (TRI Reporting)

Reporting Reporting threshold for

threshold for manufacturing and

Chemical Identity other users processing

2-Propanol Xylene Ethylbenzene n-BUTANOL

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity Reportable quantity

Xylene Reportable quantity: 100 lbs. Ethylbenzene Reportable quantity: 1,000 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Ethylbenzene No significant risk level: 41

µg/day. Carcinogenic.

Ethanol Developmental toxin.

Toluene Maximum Allowable Dose Level

(MADL): 13000 µg/day. Developmental toxin.

Benzene Maximum Allowable Dose Level

(MADL): 49 µg/day. Developmental toxin.

SDS_US 18/21



Revision Date: 09/02/2016

SS4044P

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Acetone

2-Propanol

Xylene

Polyalkylsiloxane

Ethylbenzene

Tetraethyl Silicate, Tetraethoxysilane

n-BUTANOL

US. Massachusetts RTK - Substance List

Chemical Identity

2-Propanol

Xylene

Ethylbenzene

Tetraethyl Silicate, Tetraethoxysilane

n-BUTANOL

Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanol

Xylene

Ethylbenzene

Tetraethyl Silicate, Tetraethoxysilane

n-BUTANOL

US. Rhode Island RTK

Chemical Identity

2-Propanol

Xylene

n-BUTANOL

SDS_US 19/21



Revision Date: 09/02/2016


SS4044P

Inventory Status:

y (positive listing)	Remarks: None.
y (positive listing)	Remarks: None.
y (positive listing)	Remarks: None.
n (Negative listing)	Remarks: None.
y (positive listing)	Remarks: None.
y (positive listing)	Remarks: On TSCA Inventory
n (Negative listing)	Remarks: None.
y (positive listing)	Remarks: None.
	y (positive listing) y (positive listing) n (Negative listing) y (positive listing) y (positive listing) n (Negative listing)

16.Other information, including date of preparation or last revision

HMIS Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 09/02/2016

Revision Date: No data available.

Version #: 1.12

Further Information: No data available.

SDS_US 20/21



Revision Date: 09/02/2016

SS4044P

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

®,*, and TM indicate trademarks owned by or licensed to Momentive.

SDS_US 21/21