

SCIGRIP® 4-SC

Page: 1

Compilation date: 05/03/2012

Revision date: 25/06/2014

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SCIGRIP® 4-SC

Product code: 4SC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Scigrip Adhesives Ltd

Unit 22 Bentall Business Park

Glover Road
Washington
Tyne & Wear
NE37 3JD
England

Tel: +44(0)191 419 6444 **Fax:** +44(0)191 419 6445

Email: technical.supportuk@scigrip.com

1.4. Emergency telephone number

Emergency tel: CHEMTEL Tel: 813-248-0573 (International)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36; Xn: R40; -: R66; -: R67

Classification under CLP: Carc. 2: H351; Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Most important adverse effects: Highly flammable. Irritating to eyes. Limited evidence of a carcinogenic effect. Repeated

exposure may cause skin dryness or cracking. Vapours may cause drowsiness and

dizziness.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

EUH066: Repeated exposure may cause skin dryness or cracking.

SCIGRIP® 4-SC

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard







Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260: Do not breathe vapours.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice/attention.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.





Risk phrases: R11: Highly flammable.

R36: Irritating to eyes.

R40: Limited evidence of a carcinogenic effect.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S36/37: Wear suitable protective clothing and gloves.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

SCIGRIP® 4-SC

Page: 3

Hazardous ingredients:

DICHLOROMETHANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-838-9	75-09-2	Xn: R40	Carc. 2: H351	50-70%

METHYL ACETATE

201-185-2	79-20-9	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	30-50%
			STOT SE 3: H336; -: EUH066	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

SCIGRIP® 4-SC

Page: 4

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

SCIGRIP® 4-SC

Page: 5

Hazardous ingredients:

DICHLOROMETHANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	350 mg/m3	1060 mg/m3	-	-

METHYL ACETATE

	IK 616 mg/m3	770 mg/m2		l
1 (IK 616 mg/m3	3 770 mg/m3	_	· -

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Viscosity: Non-viscous

Boiling point/range°C: 57 Flash point°C: -9

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

SCIGRIP® 4-SC

Page: 6

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DICHLOROMETHANE

DERMAL	RAT	LC50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg
VAPOURS	RAT	LD50	52000	mg/kg

METHYL ACETATE

ORL	RAT	LD50	>5	gm/kg
SCU	RAT	LDLO	8	gm/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SCIGRIP® 4-SC

Page: 7

DICHLOROMETHANE

DAPHNIA MAGNA	48H EC50	1682	mg/l
GREEN ALGA (Selenastrum capricornutum)	48H EC50	45.41	mg/l
PIMEPHALES PROMELAS	96H LC50	193	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1992

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S.

(mixture containing: METHYL ACETATE; DICHLOROMETHANE)

14.3. Transport hazard class(es)

Transport class: 3 (6.1)

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

SCIGRIP® 4-SC

Page: 8

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

R11: Highly flammable.

R36: Irritating to eyes.

R40: Limited evidence of a carcinogenic effect.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: This company shall not be held liable for any damage resulting from handling or from

contact with the above product.

