

Tensorgrip

SAFETY DATA SHEET Tensorgrip P302 Non-Flam High Temp Contact Adhesive

1. Identification		
Product identifier		
Product name	Tensorgrip P302 Non-Flam High Temp Contact Adhesive	
Product number	USA	
Recommended use of the chemical and restrictions on use		
Application	Canister Spray Adhesive	
Details of the supplier of the safety data sheet		
Supplier	Tensorgrip 5710 F St Omaha NE 68117 (402) 731 3636 (402) 731 1473 marketing.us@quin-global.com	
Emergency telephone number	θΓ	
Emergency telephone	Chemtrec: 1 800 424 9300	
2. Hazard(s) identification		
2. Hazard(s) identification Classification of the substance	ce or mixture	
	ze or mixture Aerosol 3 Press. Gas, Compressed - H280	
Classification of the substand		
Classification of the substand Physical hazards	Aerosol 3 Press. Gas, Compressed - H280 Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 -	
Classification of the substand Physical hazards Health hazards	Aerosol 3 Press. Gas, Compressed - H280 Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373	
Classification of the substand Physical hazards Health hazards Environmental hazards	Aerosol 3 Press. Gas, Compressed - H280 Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373 Not Classified The liquid may be irritating to eyes, respiratory system and skin. Symptoms following	
Classification of the substand Physical hazards Health hazards Environmental hazards Human health	Aerosol 3 Press. Gas, Compressed - H280 Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373 Not Classified The liquid may be irritating to eyes, respiratory system and skin. Symptoms following	

Hazard statements	 H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	 P251 Pressurized container: Do not pierce or burn, even after use P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P308+P313 If exposed or concerned: Get medical advice/ attention. P405 Store locked up. P410+P403 Protect from sunlight. Store in a well-ventilated place. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Contains	Methylene Chloride

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Methylene Chloride	60-75%
CAS number: 75-09-2	
Classification	
Acute Tox. 3 - H301	
Acute Tox. 4 - H312	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Carc. 2 - H351	
STOT SE 3 - H335, H336	
STOT RE 2 - H373	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures Description of first aid measures		
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.	
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.	
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.	

Eye contact	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.	
Most important symptoms and	effects, both acute and delayed	
General information	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.	
Inhalation	Irritating to respiratory system. Irritation of nose, throat and airway. Headache.	
Ingestion	Gastrointestinal symptoms, including upset stomach. Stomach pain. Nausea, vomiting. Diarrhea.	
Skin contact	Prolonged contact may cause redness, irritation and dry skin.	
Eye contact	May cause eye irritation. Prolonged contact may cause redness and/or tearing.	
5. Fire-fighting measures		
Special hazards arising from t	ne substance or mixture	
Specific hazards	Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up.	
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO2). Carbon monoxide (CO). Hydrocarbons Aldehydes.	
Advice for firefighters		
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.	
6. Accidental release measure	s	
Personal precautions, protecti	ve equipment and emergency procedures	
Personal precautions	For personal protection, see Section 8.	
Personal precautions Environmental precautions	For personal protection, see Section 8.	
	For personal protection, see Section 8. Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material.	
Environmental precautions	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material.	
Environmental precautions Environmental precautions	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material.	
Environmental precautions Environmental precautions Methods and material for cont	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material. ainment and cleaning up Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place	
Environmental precautions Environmental precautions Methods and material for cont Methods for cleaning up	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material. ainment and cleaning up Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place	
Environmental precautions Environmental precautions Methods and material for cont Methods for cleaning up 7. Handling and storage	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material. ainment and cleaning up Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place	
Environmental precautions Environmental precautions Methods and material for cont Methods for cleaning up 7. Handling and storage Precautions for safe handling	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material. ainment and cleaning up Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level.	
Environmental precautions Environmental precautions Methods and material for cont Methods for cleaning up 7. Handling and storage Precautions for safe handling Usage precautions Advice on general	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material. ainment and cleaning up Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Do not eat, drink or smoke when using this product.	
Environmental precautions Environmental precautions Methods and material for cont Methods for cleaning up 7. Handling and storage Precautions for safe handling Usage precautions Advice on general occupational hygiene	Avoid discharge into drains. Contain spillage with sand, earth or other suitable non- combustible material. ainment and cleaning up Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Do not eat, drink or smoke when using this product.	

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Methylene Chloride

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm A3

Short-term exposure limit (15-minute): OSHA 125 ppm

Long-term exposure limit (8-hour TWA): OSHA 25 ppm

ACGIH = American Conference of Governmental Industrial Hygienists. A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans. OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment



Appropriate engineering controls	This product must not be handled in a confined space without adequate ventilation. Provide adequate general and local exhaust ventilation.
Eye/face protection	Wear chemical splash goggles.
Hand protection	Use protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.
Hygiene measures	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

9. Physical and Chemical Properties

Information on basic physical and chemical properties		
Appearance	Aerosol. Liquid	
Color	Clear. Blue.	
Odor	Organic solvents.	
Relative density	1.22	
Solubility(ies)	Negligibly soluble in water	
Volatile organic compound	This product contains a maximum VOC content of 0 g/l.	
10. Stability and reactivity		
Stability	Stable at normal ambient temperatures and when used as recommended.	
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.	

Materials to avoid	May cau	se oxidation with: Aluminum.
Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Aldehydes. Hydrocarbons.	
11. Toxicological information		
Information on toxicological ef	fects	
Acute toxicity - oral		
ATE oral (mg/kg)	145.82	
Acute toxicity - dermal	4 000 07	
ATE dermal (mg/kg)	1,603.97	
Toxicological information on in	gredients.	
		Methylene Chloride
Acute toxicity - or	ral	
Acute toxicity ora mg/kg)	II (LD₅o	2,000.0
Species		Rat
ATE oral (mg/kg))	100.0
Acute toxicity - de	ermal	
Acute toxicity der mg/kg)	rmal (LD₅₀	2,000.0
Species		Rat
ATE dermal (mg/	/kg)	1,100.0
Acute toxicity - in	halation	
Acute toxicity inh (LC₅₀ vapours mo		52.0
Species		Rat
ATE inhalation (v mg/l)	apours	11.0
Carcinogenicity		
Carcinogenicity		Cancinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal studies
Target organ for carcinogenicity		Tumerigenic: Carcinogenic by RTECS criteria. Endochrine: Tumors
IARC carcinogen	icity	IARC Group 2B Possibly carcinogenic to humans.
NTP carcinogeni	city	Reasonably anticipated to be a human carcinogen.
Specific target or	gan toxicit	y - single exposure
STOT - single ex	posure	May cause respiratory irritation. May cause drowsiness or dizziness
Specific target or	gan toxicit	y - repeated exposure

STOT - repeated exposure Inhalation - May cause damage to organs through prolonged or repeated exposure -Central nervous system Oral - May cause damage to organs through prolonged or repeated exposure -Liver, blood.

General informati	on RTECS: PA8050000
12. Ecological Information	
13. Disposal considerations	
Waste treatment methods	
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
14. Transport information	
Air transport notes	1. <75kg, 2. <150kg
UN Number	
UN No. (TDG)	3500
UN No. (ICAO)	3500
UN No. (DOT)	3500
UN proper shipping name	
Proper shipping name (TDG)	Chemical Under Pressure, N.O.S. (Air, Compressed)
Proper shipping name (DOT)	Chemical Under Pressure, N.O.S. (Air, Compressed)
Transport hazard class(es)	
TDG class	2
TDG label(s)	2.2
Transport labels	
Packing group	

Packing group

Not applicable.

15. Regulatory information

US Federal Regulations

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Methylene Chloride Final CERCLA RQ: 1000(454) pounds (Kilograms)

SARA 313 Emission Reporting

Methylene Chloride 0.1 %

SARA (311/312) Hazard Categories

Present.

Methylene Chloride

Acute Health hazard Chronic Health hazard

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

Methylene Chloride Known to the State of California to cause cancer.

Massachusetts "Right To Know" List

Methylene Chloride All the ingredients are listed or exempt.

New Jersey "Right To Know" List

Methylene Chloride All the ingredients are listed or exempt.

Pennsylvania "Right To Know" List

Methylene Chloride All the ingredients are listed or exempt.

Inventories

US - TSCA

Present.

Methylene Chloride Present.

16. Other information

Revision date	6/15/2016
Revision	4
Supersedes date	10/7/2015
SDS No.	20353
Hazard statements in full	 H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood, Central nervous system, Liver) through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure.
ACA HMIS Health rating.	Moderate hazard. (2)



ACA HMIS FlammabilityWill not burn. (0)rating.Normally stable. (0)ACA HMIS Physical hazardNormally stable. (0)ACA HMIS PersonalBprotection rating.

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application.