

Date Issued : 11/04/2014 MSDS No : 11740134_FG08000 Date-Revised : 06/12/2018 Revision No : 5

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: PIPE SEALANT W/ PTFE 50ML (10)

MANUFACTURER

Pacer Technology 3281 E. Guasti Rd., Suite 260 Ontario, CA 91761 Emergency Contact: CHEMTREC Emergency Phone: 800-424-9300 Alternate Emergency Phone: 703-527-3887 Product Stewardship: 909-987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Inhalation), Category 4 Skin Irritation, Category 2 Eye Irritation, Category 2 Target Organ Toxicity (Single exposure), Category 3

GHS LABEL ELEMENTS

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



SIGNAL WORD: WARNING

HAZARD STATEMENTS

H315: Causes skin irritation. H319: Causes serious eye irritation. H332: Harmful if inhaled. H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash skin and hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P362: Take off contaminated clothing.

Response:

P302+352: IF ON SKIN: Wash with plenty of soap and water.





Date Issued : 11/04/2014 MSDS No : 11740134_FG08000 Date-Revised : 06/12/2018 Revision No : 5

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P332+P313: If skin irritation occurs: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyethylene Glycol Dimethacrylate	40 - 49	25852-47-5
Cellulose Acetate Butyrate	5 - 9	9004-36-8
Polytetrafluoroethylene	5 - 9	9002-84-0
Silica, amorphous	5 - 9	67762-90-7
Saccharin, Sodium	1 - 4	128-44-9
Cumene Hydroperoxide	1 - 4	80-15-9
N,N-DIMETHYL-O-TOLUIDINE	≤ 1	609-72-3

4. FIRST AID MEASURES

EYES: Immediately flush eyes with large quantities of water for several minutes, while holding eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation or bonding occurs.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms reoccur. Wash clothing before reuse.

INGESTION: Do Not induce vomiting. Contact physician at once.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes serious eye irritation.

SKIN: Causes skin irritation. May cause sensitization by skin contact.

SKIN ABSORPTION: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

INGESTION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Slightly irritating to eyes and respiratory tracts.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).



Date Issued : 11/04/2014 MSDS No : 11740134_FG08000 Date-Revised : 06/12/2018 Revision No : 5

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Flammable

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

EXPLOSION HAZARDS: Containers may rupture violently under fire temperatures. Cool containers with water if exposed to fire conditions.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE EXPLOSION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

SENSITIVE TO STATIC DISCHARGE: None known.

SENSITIVITY TO IMPACT: None Known.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, hydrogen fluoride, and carbonyl fluoride.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid and place in sealed container for disposal.

LARGE SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LAND SPILL: Prevent from entering into soil, ditches, sewers, waterways and/or ground water. See Section 12, Ecological Information.

AIR SPILL: None known

GENERAL PROCEDURES: Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface.

SPECIAL PROTECTIVE EQUIPMENT: Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section).

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid contact with skin and eyes. Wash thoroughly after handling.

STORAGE: Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

STORAGE TEMPERATURE: Suggested storage conditions: Less than 77F/25C. Protect from freezing.

LOADING TEMPERATURE: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

LOADING/UNLOADING VISCOSITY: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

STORAGE PRESSURE: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.



Date Issued : 11/04/2014 MSDS No : 11740134_FG08000 Date-Revised : 06/12/2018 Revision No : 5

SPECIAL SENSITIVITY: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

ELECTROSTATIC ACCUMULATION HAZARD: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
	EXPOSURE LIMITS			
Chemical Name	Туре		ppm	mg/m³
Cumene Hydroperoxide	OSHA PEL	TWA	50	245

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Vinyl or rubber gloves.

RESPIRATORY: If ventilation is not adequate, wear NIOSH approved respiratory protection.

PROTECTIVE CLOTHING: Wear protective clothing. Launder contaminated clothing before reuse.

WORK HYGIENIC PRACTICES: Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid ODOR: Low odor. **ODOR THRESHOLD:** No data available APPEARANCE: White paste. COLOR: White. pH: No data available PERCENT VOLATILE: No data available FLASHPOINT AND METHOD: No data available AUTOIGNITION TEMPERATURE: No data available VAPOR PRESSURE: No data available VAPOR DENSITY: No data available BOILING POINT: No data available FREEZING POINT: No data available MELTING POINT: No data available POUR POINT: No data available THERMAL DECOMPOSITION: No data available SOLUBILITY IN WATER: No data available



Date Issued : 11/04/2014 MSDS No : 11740134_FG08000 Date-Revised : 06/12/2018 Revision No : 5

EVAPORATION RATE: No data available DENSITY: No data available SPECIFIC GRAVITY: No data available VISCOSITY: No data available MOLECULAR WEIGHT: No data available (VOC): No data available

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: May occur upon depletion of inhibitor.

STABILITY: Stable

CONDITIONS TO AVOID: Avoid temperatures exceeding 100F/38C and avoid contact with metal powders, metal salts and amines.

POSSIBILITY OF HAZARDOUS REACTIONS: Under normal conditions of storage and use, hazardous reactions will not occur. **HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

INCOMPATIBLE MATERIALS: Oxidizers, metal salts, heat, inert gases and amines.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)	
Polyethylene Glycol Dimethacrylate	> 2000 mg/kg			
Cumene Hydroperoxide	382 mg/kg (rat)	133 mg/kg (rabbit)	220 ppm per 4 hr (rat)	

SERIOUS EYE DAMAGE/IRRITATION: May cause slight irritation.

RESPIRATORY OR SKIN SENSITISATION: May cause sensitization by skin contact.

CARCINOGENICITY

- **IARC:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.
- **NTP:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.
- **OSHA:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Prevent product from entering drains or sewers in case of spill.

ECOTOXICOLOGICAL INFORMATION: Prevent contamination of soil, drains and surface waters. Dike and contain material. Soak up residue with absorbent (clay, sand) materials and dispose of properly.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of following all Local Authority requirements for disposal.



Date Issued : 11/04/2014 MSDS No : 11740134_FG08000 Date-Revised : 06/12/2018 Revision No : 5

PRODUCT DISPOSAL: Dispose of following all Local Authority requirements for disposal.

EMPTY CONTAINER: Dispose of following all Local Authority requirements for disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not restricted

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Not restricted

AIR (ICAO/IATA)

SHIPPING NAME: Not restricted

VESSEL (IMO/IMDG)

SHIPPING NAME: Not restricted

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: Section 313: Cumene hydroperoxide (CAS 80-15-9), less than 3%.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Cumene Hydroperoxide	1 - 4	80-15-9

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Cumene Hydroperoxide	1 - 4	10

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Polyethylene Glycol Dimethacrylate	25852-47-5
Cellulose Acetate Butyrate	9004-36-8
Polytetrafluoroethylene	9002-84-0
Silica, amorphous	67762-90-7
Saccharin, Sodium	128-44-9
Cumene Hydroperoxide	80-15-9
N,N-DIMETHYL-O-TOLUIDINE	609-72-3

TSCA STATUS: All ingredients in this mixture are in compliance with TSCA.

CALIFORNIA PROPOSITION 65: A WARNING: This product can expose you to Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



Date Issued : 11/04/2014 MSDS No : 11740134_FG08000 Date-Revised : 06/12/2018 Revision No : 5

WHMIS CLASS: D2B - Toxic (Irritant)


16. OTHER INFORMATION


APPROVED BY: Pacer Technology Regulatory Department

PREPARED BY: Pacer Technology Regulatory Department Date-Revised: 06/12/2018

REVISION SUMMARY: This MSDS replaces the 09/21/2017 MSDS. Revised: Section 12:

BIOACCUMULATION/ACCUMULATION, AQUATIC TOXICITY (ACUTE) - Notes. Section 14: SHIPPING NAME.





HMIS RATINGS NOTES: Safety glasses and gloves are recommended for usage.

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

