

ARALDITE® adhesive solutions

Our adhesive solutions can shorten product development times by up to six months, and streamline maintenance tasks by curing up to 20% faster than alternatives.



## MADE POSSIBLE

Chemical Concepts Our expertise is your solution. Chemical-concepts.com 800.220.1966 410 Pike Road • Huntingdon Valley, PA 19006





## TRUSTED ADHESIVE SOLUTIONS FOR WIND TURBINE DEVELOPMENT AND REPAIR

At Huntsman Advanced Materials, we are committed to solving complex engineering challenges for the global wind industry.

Whether you are an OEM looking to develop next generation turbines in shorter timeframes or an MRO service provider focused on optimizing resources and costs, our adhesives are the perfect bonding solution in harsh environments, including high humidity, and cold temperatures.

We offer a full range of adhesive products for all development, assembly, and maintenance requirements. No other structural adhesives on the market cure as quickly in such extreme conditions.

#### **EFFICIENCY AND PRODUCTIVITY**

Huntsman Advanced Materials is trusted worldwide for delivering solutions that minimize costs and maximize performance, with strong technical and customer support. We share your goals in creating better ways to streamline processes, simplify resources, and deliver dependable results every time.

Our broad expertise and deep understanding of the challenges you face has inspired us to develop both standardized products and custom-made solutions. With excellent aging and weather resistance, fast curing times, and outstanding adhesion properties, we ensure product development teams have greater design freedom to innovate and bring products to market faster, while maintenance teams can save time and costs for off-site structural maintenance tasks.

#### Ideas made possible

- Open new possibilities in your design process
- Reduce development time by up to six months
- Rest assured with our OEM-gualified, TSCA- and **REACH-registered product portfolio**

#### Performance made possible

- Reduce risks through a more secure supply chain
- Extend the lifetime of your blades in all conditions
- Minimize downtime, repair time, and costs

#### **Tomorrow made possible**

- Lead the market with next generation turbine designs
- Create larger, lighter, and tougher blades that last longer
- Be ready for the future, whatever the conditions

**150%** Reduce downtime by up to 50%

✓90%
Reduce total repair time by up to 90%
Greate reliable bonds even down to -4°F



## VERSATILE APPLICATIONS FOR NEXT GENERATION TURBINES

Void filling and trailing edge openings: ARALDITE<sup>®</sup> 2010 / ARALDITE<sup>®</sup> 2023 / ARALDITE<sup>®</sup> 2031-1

Reduce void filling time by 50% with high gap filling properties and exceptional UV resistance. ARALDITE<sup>®</sup> 2031-1 adhesive also offers excellent shear thinning properties and low shrinkage.

#### Sensor bonding and lightning conductor: ARALDITE<sup>®</sup> 2051 & ARALDITE<sup>®</sup> 2015-1

strength within minutes.

Achieve high bond strength and weathering resistance with ARALDITE® 2015-1 adhesive. ARALDITE® 2051 adhesive is approved by OEMS for its long-term bonding capability, reducing maintenance costs by up to 70%.

Bolt, stud and insert fixing:
 ARALDITE® 2021-1 / ARALDITE® 2051 & ARALDITE® 2050
 ARALDITE® 2021 and ARALDITE® 2051 adhesives enable
 you to position bolts, studs, and inserts with reliable handling



### Vortexes and add-ons bonding: ARALDITE<sup>®</sup> 2051 & ARALDITE<sup>®</sup> 2050 / ARALDITE<sup>®</sup> 2021-1 & ARALDITE<sup>®</sup> 2022-1

Install add-ons and vortexes in harsh conditions with fast-curing ARALDITE® 2050 and ARALDITE® 2051 adhesives. Streamline assembly of other small parts with OEM-approved ARALDITE® 2021-1 adhesive.

#### 5 Nacelle bonding: ARALDITE<sup>®</sup> 2022-1

Improve assembly time with faster curing and bond multiple substrates with medium open time.

#### **C** Tooling bonding high temperature: ARALDITE<sup>®</sup> 2019

Increase the lifespan of tooling with ARALDITE<sup>®</sup> 2019 adhesive, delivering high temperature and chemical resistance and exceptional mechanical strength.

## Shell bonding repair: ARALDITE<sup>®</sup> 2023 / ARALDITE<sup>®</sup> 2031-1

Complete shell bonding and repairs for multiple part sizes, such as blade tips and mastics, in a single step.

#### Wind blade repair: ARALDITE<sup>®</sup> 2023 / ARALDITE<sup>®</sup> 2050 & ARALDITE<sup>®</sup> 2051

Extend the season of repair with reliable bonds in extreme temperatures and humidity using ARALDITE® 2050 and ARALDITE® 2051 adhesives.

#### Proof joint adhesives: ARALDITE<sup>®</sup> 2031-1

Achieve high fracture toughness, dynamic loading, and weathering resistance in root joints.

## **Control shaft and components:** ARALDITE<sup>®</sup> 2014-2

Achieve precise and reliable positioning of components and control shaft parts with long-lasting bonds, proven for 30+ years.



#### CASE 1:

## **GAP-FILLING OF WIND BLADES WITH ARALDITE® 2031-1 ADHESIVE**



One of our OEM customers needed a reliable solution for injecting an adhesive into the gaps of wind blades after their infusion and assembly.

By using ARALDITE® 2031-1 adhesive with its shear thinning and low shrinkage properties, the OEM was able to successfully fill-in gaps left after infusion and shell bonding of the blades.

The adhesive delivered outstanding resistance to weathering and high lap shear strength, which proved perfect for the application's demanding outdoor conditions. The adhesive also cures at room temperature, ensuring effective blade continuity.

# 60-minute pot life at room temperature

ARALDITE® 2031-1

		Typical properties						
ARALDITE <sup>®</sup> adhesives	Chemistry	Mix ratio	Pot life	Gap fill	Recommended cure temperature	Glass transition (Tg) midpoint		
Units		V/V	Mins at 77°F / 100g	Mm	°F	°F		
ARALDITE® 2010-1	Ероху	1:1	10	1	73	104		
ARALDITE <sup>®</sup> 2014	Ероху	2:1	110	5	73	156.2		
ARALDITE® 2015-1	Ероху	1:1	45	10	73	172.4		
ARALDITE <sup>®</sup> 2019	Ероху	2:1	100	5	>140	251.6		
ARALDITE® 2031-1	Ероху	1:1	60	10	73	167		
ARALDITE <sup>®</sup> 2021-1	Acrylic	1:1	3	4	73	242.6		
ARALDITE® 2022-1	Acrylic	1:1	10	4	73	237.2		
ARALDITE <sup>®</sup> 2023	Acrylic	10:1	10* / 35* / 75*	30	73	170.6		
ARALDITE <sup>®</sup> 2050	Acrylic	1:1	1*	4	-4* / 73	260.6		
ARALDITE <sup>®</sup> 2051	Acrylic	1:1	4*	4	104	260.6		
ARALDITE® 2053-15	Acrylic	10:1	15*	5	32* / 104	235.4		
ARALDITE® 2053-5	Acrylic	10:1	5*	5	73	239		

\* on 20 grams \*\* Substrate failure

#### CASE 2:

## **BONDING INSIDE BLADE ADD-ONS WITH ARALDITE® 2051 ADHESIVE**

A maintenance and repair customer needed a reliable, weather-resistant solution for bonding add-ons, such as sensors, onto the internal composite structure of wind blades.

ARALDITE® 2051 adhesive proved to be the ideal solution. The adhesive is non-sagging and can be used in freezing temperatures with no need of heating, thereby extending repairs into wintertime and reducing downtime by up to three days. The adhesive has since been used by the customer for a broad variety of other tasks, simplifying its inventory and reducing maintenance costs by up to 70%.



**170%** Reduce maintenance costs by up to 70% with ARALDITE® 2051 adhesive

Handling time (time to 145 Psi)	LSS at 74°F VA4 steel	CFRP	EP - GRP	Key features
Mins at 74°F	Psi	Psi	Psi	
30	3336	1885	725	Fast curing epoxy, with low shrinkage
300	3336	2466	1305**	High temperature resistance and resistant to chemicals and water
240	3481	3191	2176	Gap filling and bonding for dis-similar substrates
270	3916	5076	5221**	Toughened and temperature resistant to 284°F
180	3626	2901**	2901	High weather resistant metal and composite bonder
9	3481	2901	1740**	Toughened and rapid curing adhesive with performance to 212°F
12	3626	3336	2611**	Multipurpose acrylic with good balance of work to cure time
40 / 70 / 100	3046	3046	2466	For dynamic enviroments where large gap filling is required to produce tough flexible bonds
9	4351	3626	2321	Ultra fast curing from -4°F to 77°F under water and in high humidity conditions
15	4206	2611	1740	Fast curing from 32°F to 104°F in high humdity conditions
40	3481	3191	3046	Excellent ageing and weathering with high elongation
20	3336	3916	3191	Fast cure with excellent temperature and ageing resistance

## MADE POSSIBLE

#### **Huntsman Advanced Materials**

At Huntsman Advanced Materials, we make things possible. Serving many of the world's leading businesses across virtually every industry, we enable greater innovation, performance and sustainability to address global engineering challenges and contribute towards a better quality of life.

Our capabilities in high-performance adhesives and composites, delivered by more than 1600 associates, support over 2000 global customers with innovative, tailor-made solutions and more than 1500 pioneering epoxy, acrylic, phenolic and polyurethane-based polymer products.

We operate synthesis, formulating and production facilities around the world



Distributed by



## HUNTSMAN

#### For more information

www.huntsman.com/advanced\_materials advanced\_materials@huntsman.com

#### Europe, Middle East & Africa

Huntsman Advanced Materials (Switzerland) GmbH Klybeckstrasse 200 P.O. Box 4002 Basel Switzerland Tel: +41 61 299 1111 Fax: +41 61 299 1112

#### Asia Pacific & India

Huntsman Advanced Materials (Guangdong) Co., Ltd, Shanghai Branch Office 455 Wenjing Road, Minhang District Shanghai 200245, P.R. China Tel: +86 21 3357 6588 Fax: +86 21 3357 6547

#### Americas

Huntsman Advanced Materials Americas Inc. 10003 Woodloch Forest Drive The Woodlands Texas 77380 USA Tel: +1 888 564 9318 Fax: +1 281 719 4047

#### Legal information

All trademarks mentioned are either property of or licensed to Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.

Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. or Huntsman Advanced Materials (Guangdong) Ltd. ("Huntsman" The following supercedes Buyer's documents. While the information and recommendations included in this publication are, to the best of Huntsman's knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A REPRESENTATION OR WARBANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLEC-TUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL BISK AND LIABILITY WHATSOFVER BESULTING. FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Data and results are based on controlled conditions and/ or lab work. Buver is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights.

The Product may be or become hazardous. Buyer should (i) obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, (ii) take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and in direct customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product and (iii) comply with and ensure that its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product comply with all safety information contained in the applicable Material Safety Data Sheets, Technical Data Sheets or other instructions provided by Huntsman and all applicable laws, regulations and standards relating to the handling, use, storage, distribution and disposal of and exposure to the Product. Please note that products may differ from country to country. If you have any queries, kindly contact your local Huntsman representative.

© 2021 Huntsman Corporation. All rights reserved. Ref. No. AdMat wind segment brochure 03.21\_EN\_US



