

MINIMIZE INVENTORY. SIMPLIFY PRODUCTION.

**ARALDITE® 2012
adhesive helps maximize
your production
flexibility with
minimized inventory.**

ARALDITE® 2012 adhesive offers well-proven, reliable performance, helping you reduce the risk and complexity of production. Aerospace-qualified and radiation-resistant, ARALDITE® 2012 adhesive enables fast bonding and rapid attainment of strength with minimum contact pressure time.

With the ability to bond metals and plastics, working with this multi-purpose adhesive can also help you simplify your inventory management. The short curing time speeds up your production processes, resulting in time saved and long-lasting bonds.

PRODUCT BENEFITS

- Fast curing
- Self-levelling
- Bonds multiple metals and plastics



MADE POSSIBLE

COMPLETE COMPLEX BONDING APPLICATIONS WITHIN SHORT PROCESSING TIMES.



ARALDITE® 2012 adhesive has a long history of creating fast-curing, high-performance bonds between multiple materials.

SUPERIOR PERFORMANCE

6 mins
6-min pot life at room temperature

2C Epoxy technology	362,595 psi Tensile modulus
6,381 psi Tensile strength	ca. 4% Elongation at break

158°F
158°F maximum continuous operating temperature*

20 mins
20-min fixture time at room temperature

30,000 cP
30,000 cP mixed viscosity at room temperature

* For the maximum continuous operating temperature, we consider the maximum temperature for which the residual lap shear strength is 1/3 of the lap shear strength at room temperature or the temperature for which the residual lap shear strength is 725 psi.

With our Material Models, you get fast and accurate simulations when qualifying adhesives for your project.

Click to find your Material Model



Legal information

All trademarks mentioned are either property of or licensed to Huntsman Corporation or an affiliate thereof in one or more, but not all, countries. Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. or Huntsman Advanced Materials (Guangdong) Ltd. ("Huntsman"). The following supersedes Buyer's documents. While the information and recommendations included in this publication are, to the best of Huntsman's knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Data and results are based on controlled conditions and/or lab work. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights. The Product may be or become hazardous. Buyer should (i) obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, (ii) take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product and (iii) comply with and ensure that its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product comply with all safety information contained in the applicable Material Safety Data Sheets, Technical Data Sheets or other instructions provided by Huntsman and all applicable laws, regulations and standards relating to the handling, use, storage, distribution and disposal of and exposure to the Product. Please note that products may differ from country to country. If you have any queries, kindly contact your local Huntsman representative.

ARALDITE® is a trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.
© 2023 Huntsman Corporation. All rights reserved.
Ref. No. AdMat_Araldite 2012_core range_EN_US_May 2023

Americas

Huntsman Advanced Materials Americas Inc.
10003 Woodloch Forest Drive
The Woodlands, TX 77380, USA
Tel.: +1 888 564 9318
Fax: +1 281 719 4047

Asia Pacific

Huntsman Advanced Materials (Guangdong) Co., Ltd.
Shanghai Branch Office
455 Wenjing Road, Minhang District
Shanghai 200245, P.R. China
Tel: +86 21 3357 6588
Fax: +86 21 3357 6547



Responsible Care®
OUR COMMITMENT TO EXCELLENCE

BPA free

Europe, Middle East & Africa

Huntsman Advanced Materials (Switzerland) GmbH
Klybeckstrasse 200
P.O. Box
4002 Basel, Switzerland
Tel.: +41 61 299 1111
Fax: +41 61 299 1112

For more information: www.huntsman.com