

# MAKE PRECISE BONDS WITH LESS SHRINKAGE

**ARALDITE® 2014  
adhesive enables  
durable bonds that  
resist the harshest  
conditions.**

ARALDITE® 2014 adhesive offers straightforward processability combined with high chemical and temperature resistance. Curing at room temperature, this adhesive enables a reliable and long-lasting bond with resistance to hydraulic oils and temperatures up to 284°F.

The cartridge format makes it easy to use in confined spaces and the low shrinkage rate allows for tight tolerances. This versatile adhesive is suited for a variety of applications including bonding filter media, electronic fuse assembly, and bonding composite pipes for marine settings.

## PRODUCT BENEFITS

- Resistant to chemicals
- Temperature resistant
- Low shrinkage rate



**MADE POSSIBLE**

CREATE RELIABLE BONDS, EVEN UNDER HARSH CONDITIONS AND HIGH TEMPERATURES.



ARALDITE® 2014 adhesive is a highly chemical- and temperature-resistant adhesive with proven performance spanning more than 30 years.

SUPERIOR PERFORMANCE

**40** mins

40-min pot life at room temperature

**2C**

Epoxy technology

**631,475** psi

Tensile modulus

**3,773** psi

Tensile strength

ca. **1%**

Elongation at break

**284**°F

284°F maximum continuous operating temperature\*



**↑5** mm

Up to 5 mm gap-filling

**180** mins

180-min fixture time at room temperature

\* For the maximum continuous operating temperature, we consider the maximum temperature for which the residual lap shear strength is 1/3 of the lap shear strength at room temperature or the temperature for which the residual lap shear strength is 725 psi.

With our Material Models, you get fast and accurate simulations when qualifying adhesives for your project.

Click to find your Material Model



Legal information

All trademarks mentioned are either property of or licensed to Huntsman Corporation or an affiliate thereof in one or more, but not all, countries. Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. or Huntsman Advanced Materials (Guangdong) Ltd. ("Huntsman"). The following supersedes Buyer's documents. While the information and recommendations included in this publication are, to the best of Huntsman's knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Data and results are based on controlled conditions and/or lab work. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights. The Product may be or become hazardous. Buyer should (i) obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, (ii) take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and in direct customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product and (iii) comply with and ensure that its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product comply with all safety information contained in the applicable Material Safety Data Sheets, Technical Data Sheets or other instructions provided by Huntsman and all applicable laws, regulations and standards relating to the handling, use, storage, distribution and disposal of and exposure to the Product. Please note that products may differ from country to country. If you have any queries, kindly contact your local Huntsman representative.

ARALDITE® is a trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.  
© 2023 Huntsman Corporation. All rights reserved.  
Ref. No. AdMat\_Araldite 2014\_core range\_EN\_US\_May 2023

Americas

Huntsman Advanced Materials Americas Inc.  
10003 Woodloch Forest Drive  
The Woodlands, TX 77380, USA  
Tel.: +1 888 564 9318  
Fax: +1 281 719 4047

Asia Pacific

Huntsman Advanced Materials (Guangdong) Co., Ltd.  
Shanghai Branch Office  
455 Wenjing Road, Minhang District  
Shanghai 200245, P.R. China  
Tel: +86 21 3357 6588  
Fax: +86 21 3357 6547



Responsible Care®

BPA free

Europe, Middle East & Africa

Huntsman Advanced Materials (Switzerland) GmbH  
Klybeckstrasse 200  
P.O. Box  
4002 Basel, Switzerland  
Tel.: +41 61 299 1111  
Fax: +41 61 299 1112

For more information: [www.huntsman.com](http://www.huntsman.com)