



Technical Data Sheet

Product name	: H2O Glue® Sticky Stuff			
Manufacturer or supplier's details				
Company name of supplier Address	<ul><li>Chemical Concepts, Inc.</li><li>410 Pike Road</li><li>Huntingdon Valley, PA 19006</li></ul>			
Telephone	: Non-Emergency: (800) 220.196	6		
Emergency telephone number	: INFOTRAC: (800) 535.5053			

## Recommended use of the chemical and restrictions on use

Recommended use

: Adhesives

H2O Sticky Stuff is a quick-setting, HAP's free, low pressure, sprayable adhesive that has been designed to produce a strong permanent bond when used with a variety of insulation materials.

## **TYPICAL PROPERTIES**

Color:	Amber
Viscosity:	450 cPs
Base:	Synthetic Rubber
Solvent:	Heptane/Acetone
Solids:	40%
Wt/Gal, lbs:	6.8

The primary use for this adhesive is in bonding fiberglass insulation to sheet metal used in heating and air conditioning duct work.

H2O Sticky Stuff should only be applied to clean, dry surfaces. Best bonds are obtained if substrates are maintained at temperatures above 40°F. Drying time and coverage per gallon will vary according to the rate of adhesive application and local atmospheric conditions. Suitable equipment for spray application is listed below, however, other equivalent spray equipment is available.

Manufacturer	Model	Air Cap	Fluid Tap
Binks	2001SS	665D	63A
Binks	18	66PJ	66
De Vilbiss	MBC	770	FX
De Vilbiss	JGA	770	FX

H2O Sticky Stuff was specifically designed for application via spray, but may be applied by brush or roller applications.

Additional information regarding other specific applications is available upon request. Consult SDS for health and safety information. For further information or questions, please contact our technical representatives.