SAFETY DATA SHEET



1. Identification

Product identifier KE-3475-TUV

Other means of identification

Sales Code GCCZS0

Recommended use RTV rubbers

RTV rubber for electrical, electronic and general industry (coating)

Recommended restrictions Industrial use only.

Manufacturer/Importer/Supplier/Distributor information

Name Shin-Etsu Silicones of America, Inc.
Address 1150 Damar Drive, Akron, OH 44305 USA

Contact Regulation compliance group

Telephone Number +1-330-630-9860 **Fax Number** +1-330-630-9855

Emergency Phone Number Chemtrec: +1-800-424-9300 (Within US)

Chemtrec: +1-703-527-3887 (Outside US)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2ASensitization, skinCategory 1BReproductive toxicity (fertility, the unbornCategory 2

child)

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Chemical Concepts
Our expertise is your solution.
Chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May

cause an allergic skin reaction. Suspected of damaging the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after

handling. Contaminated work clothing must not be allowed out of the workplace.

Response In case of fire: Use water fog, foam, dry chemical powder or carbon dioxide(CO2) to extinguish. IF

ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash it before

reuse.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: KE-3475-TUV SDS US

Hazard(s) not otherwise

classified (HNOC)

HMIS® ratings

None known.

Supplemental information

Substance(s) formed under the condition of use

This product reacts with water, moisture or humid air to evolve following compounds:

Acetone

None.

Health: 2* Flammability: 3 Physical hazard: 0

3. Composition/information on ingredients

Chemical name	Common name and synonyms	CAS number	%
Alkenoxysilane*		Proprietary*	3 - < 5
Alkoxysilane*		Proprietary*	1 - < 3
Organosilane*		Proprietary*	1 - < 3
Toluene		108-88-3	< 1

67-64-1 Acetone

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. For minor skin

contact, avoid spreading material on unaffected skin. If skin irritation or rash occurs: Get medical

CAS number

%

advice/attention. Take off contaminated clothing and wash before reuse.

Rinse immediately with plenty of water for at least 15 minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention immediately.

Most important

Eye contact

Chemical name

symptoms/effects, acute and

delayed

Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin

reaction.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2).

None known.

Specific hazards arising from

the chemical

By heating and fire, harmful vapors/gases may be formed.

Nitrogen oxides. (corrosive)

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet,

gloves, rubber boots, and self-contained breathing apparatus.

Fire-fighting equipment/instructions Move containers from fire area if you can do so without risk.

General fire hazards

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch or walk through spilled material. Ventilate closed spaces before entering them. Wear appropriate personal protective equipment.

Material name: KE-3475-TUV SDS US

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Vapors may form explosive mixtures with air. Provide adequate ventilation.

Use care in handling/storage. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges. Use personal protective equipment as required. Wash hands thoroughly after handling.

Do not breathe mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in cool place. Store in a well-ventilated place. Keep container tightly closed. Keep out of the reach of children. Store in a cool, dry place out of direct sunlight. Keep in original container.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Decomposition	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
,		1000 ppm	
US. OSHA Table Z-2 (29 CFR 191	0.1000)		
Components	Type	Value	
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Decomposition	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Toluene (CAS 108-88-3)	STEL	560 mg/m3	
,		150 ppm	
	TWA	375 mg/m3	
		100 ppm	
Decomposition	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	

Biological limit values

ACGIH Biological Expose Components	ure Indices Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

Material name: KE-3475-TUV

ACGIH Biological Exposure Indices

 Decomposition
 Value
 Determinant
 Specimen
 Sampling Time

 Acetone (CAS 67-64-1)
 50 mg/l
 Acetone
 Urine
 *

Exposure guidelines

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

TOLUENE; TOLUOL (CAS 108-88-3)

Can be absorbed through the skin.

US. Minnesota Hazardous Substances List (Minn. Rules 5206.0400).

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Provide eyewash station.

Pay attention to ventilation such as local exhaust, mechanical and/or door open for at least 24 hours after application.

Individual protection measures, such as personal protective equipment

Eye/face protection Tightly sealed safety glasses according to EN 166.

Skin protection

Hand protection Wear protective gloves.

Other Wear suitable protective clothing.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with skin. Avoid contact with eyes. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Handle in accordance with good industrial hygiene and

safety practice.

9. Physical and chemical properties

Appearance

Form Paste.

Color Milk-white, translucent

Odor Acetone odor
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not applicable
Initial boiling point and boiling Not applicable

range

Flash point 71.6 °F (22 °C) Closed Cup

Evaporation rate < 1 (Butyl Acetate=1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

2.1 % v/v [Acetone]

(%)

Flammability limit - upper

13.0 % v/v [Acetone]

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Negligible (25 °C)

Vapor density > 1 (air=1)

Relative density 1.01 (25 °C)

Solubility(ies)

Solubility (water) Not soluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature No data

^{* -} For sampling details, please see the source document.

Decomposition temperature

Not available. 3.2 Pa·s (25 °C) **Viscosity**

Other information

Molecular weight Not applicable

10. Stability and reactivity

Reactivity No hazardous reaction known under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid None known.

Incompatible materials Strong oxidizing agents. Water, moisture.

Hazardous decomposition

products

This product reacts with water, moisture or humid air to evolve following compounds:

Acetone.

Thermal breakdown of this product during fire or very high heat condition may evolve the following

hazardous decomposition product:

Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Nitrogen

oxides. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eve contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic

skin reaction.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Alkenoxysilane (CAS Proprie	etary)	
Acute		
Oral		
LD50	Rat	> 20 ml/kg
Alkoxysilane (CAS Proprieta	агу)	
Acute		
Dermal		
LD50	Rabbit	4290 mg/kg
Oral		
LD50	Rat	1570 - 3650 mg/kg
		1780 mg/kg
Organosilane (CAS Propriet	ary)	
Acute		
Oral		
LD50	Rat	3.67 ml/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	12124 mg/kg
		14.1 ml/kg
Inhalation		-
LC50	Mouse	400 ppm, 24 hours
		11 /

Material name: KE-3475-TUV

15699 Version #: 01 Issue date: 04-27-2015

SDS US

Species Test Results Components Oral LD50 Rat 5000 mg/kg 2.6 g/kg Decomposition **Species Test Results** Acetone (CAS 67-64-1) Acute Inhalation LC50 Rat 50.1 mg/l, 8 Hours Oral LD50 Mouse 3000 mg/kg Rabbit 5340 mg/kg Rat 5800 mg/kg Skin corrosion/irritation SKIN-RABBIT: 5mg/24Hr SEVERE [Alkoxysilane] Causes severe skin burns and eye damage. [Organosilane] Causes skin irritation. [Toluene] EYE-RABBIT: 0.75mg/24Hr SEVERE [Alkoxysilane] Serious eye damage/eye Causes serious eye damage. [Organosilane] irritation Causes eye irritation. [Toluene] Causes serious eye irritation. [Acetone] Respiratory or skin sensitization Respiratory sensitization Not available. Skin sensitization Positive (Guinea pig) [Alkoxysilane] Negative(Ames Test) [Alkoxysilane] Germ cell mutagenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging the unborn child. [Toluene]

Specific target organ toxicity -

single exposure

Carcinogenicity

May cause damage to the following organs.

Narcotic effects. [Toluene] Narcotic effects. [Acetone]

Specific target organ toxicity -

repeated exposure

Central nervous system. [Toluene]

Aspiration hazard Not available.

Further informationThis product reacts with water , moisture or humid air to evolve following compounds:

Acetone

12. Ecological information **Ecotoxicity** Toxic to aquatic life. Harmful to aquatic life with long lasting effects. [Toluene] Components **Species Test Results** Alkoxysilane (CAS Proprietary) Aquatic Fish LC50 Oryzias latipes > 1000 mg/l, 48 hr Toluene (CAS 108-88-3) **Aquatic** Crustacea EC50 Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours Fish LC50 Coho salmon, silver salmon 5.5 mg/l, 96 hours (Oncorhynchus kisutch)

Material name: KE-3475-TUV SDS US

Decomposition Species Test Results

Acetone (CAS 67-64-1)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours LC50 Fish Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

Persistence and degradability Causes easily hydrolysis in water or atmosphere. [Alkoxysilane]

Bioaccumulative potential Not available. Mobility in soil Not available. Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Follow applicable Federal, State and Local regulations.

14. Transport information

DOT

UN1993 **UN** number

UN proper shipping name Flammable liquids, n.o.s. (Alkenoxysilane)

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IB2, T7, TP1, TP8, TP28 Special provisions

150 Packaging exceptions 202 Packaging non bulk Packaging bulk 242

IATA

UN1993 **UN number**

Flammable liquid, n.o.s. (Alkenoxysilane) **UN proper shipping name**

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (Alkenoxysilane)

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. F-E, S-E* **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Material name: KE-3475-TUV SDS US

This product is not intended to be transported in bulk.



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 313 (TRI reporting)

US state regulations

US. Massachusetts RTK - Substance List

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Toluene (CAS 108-88-3)

US. Rhode Island RTK

Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Material name: KE-3475-TUV

Country(s) or region Inventory name On inventory (yes/no)*

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL) Yes

New Zealand New Zealand Inventory No **Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information, including date of preparation or last revision

04-27-2015 Issue date

Version # 01

Health: 2 NFPA ratings Flammability: 3

Instability: 0

NFPA ratings



Disclaimer

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are

This product has been designed, manufactured and developed solely for general industrial use only. This product is not designed for, intended for use as, or suitable for, medical, surgical or other particular purposes. Users have the sole responsibility and obligation to determine the suitability of this product for any application, to make preliminary tests, and to confirm the safety of this product for their use. Users must never use this product for the purpose of implantation into the human body and/or injection into humans.

Revision Information

Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Additional Components

Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data

Ecological Information: Ecotoxicity

Transport Information: Proper Shipping Name/Packing Group



Material name: KE-3475-TUV SDS US