

Touchstone[™] Liquid Tints



Product Description

Use with clear resins where you need to make slight color adjustments.

Product Features

- Can be used with urethanes, epoxies and polyesters
- Create translucent or opaque looks
- Squeeze bottles make it easy to measure
- Easier mixing than paste tints
- Even consistency throughout adhesive



Applications

- Custom color matching
- Repairs
- Stone restoration
- Countertop fabrication



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

Specifications

Product Type:	Coloring Agent
Viscosity:	Liquid
Mix Ratio:	Add color as needed for color match
Set Time:	NA
Cure Time:	NA
Pot Life:	NA
Application Conditions:	Interior, Exterior; Vertical, Horizontal
Coverage:	NA
Recommended Application Temp:	75°F (24°C)
Available Colors:	Black, Blue, Brown, Buff, Gray, Green, Red, Red/Brown, White, Yellow
Sizes:	2oz (60ml), 8oz (237ml), Sets of 10
Other:	NA



Surface Preparation & Use

Does not apply

Mixing Instructions

Minimum product and substrate temperature should be at or above 55°F (13°C). Add colorant to the adhesive or patching material and mix thoroughly. Do not exceed an addition of more than 4% by weight or by volume.

Temperature Dependency

Does not apply



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

Shelf Life & Storage

Shelf life is approximately one year if kept in unopened cans in a dry area at 75°F (24°C).

Limitations

Does not apply

Safety

Before storing, mixing, or applying this product, read and understand all the product's Safety Data Sheets. For a copy of the SDS, contact Bonstone Materials at (800) 425-2214.

Warranty

This product's warranty is limited to replacement of defective material and freight charges to destination only. Bonstone Materials. is not responsible for consequential damages.