

Touchstone ' **Scrim**

Product Description

Reinforcing mesh scrim is ideal for reinforcing fragile stones and slabs.

Product Features

- 3' x 150' Roll (914mm x 45,720)
- Reinforces fragile stones and slabs
- Can be used with epoxy, vinyl ester, polyester and urethane systems



Chamical

Applications

- · Countertop fabrication
- Tile setting

Specifications		Chemical	
Product Type:	Scrim	Concepts	
Viscosity:	Fiberglass mesh	Our expertise is your solution.	
Mix Ratio:	NA	chemical-concepts.com	
Set Time:	NA	800.220.1966	
Cure Time:	NA	410 Pike Road • Huntingdon Valley, PA 19006	
Pot Life:	NA		
Application Conditions:	NA		
Recommended Application Temp:	NA		
Coverage:	475 sq ft roll (144,780mm)		
Available Colors:	White		
Sizes:	38" wide x 150' linear ft/roll (965mm x 45,720mm)		
Other:	NA		







Technical Data Sheet

Surface Preparation & Use

Does not apply

Mixing Instructions

Does not apply



chemical-concepts.com 800.220.1966 410 Pike Road • Huntingdon Valley, PA 19006

Temperature Dependency

Does not apply

Shelf Life & Storage

Store on end in original manufacturers box. Do not permit prolonged exposure to sun and other elements of weather. Do not permit contact with petroleum products.

Limitations

Does not apply

Safety

Before storing, mixing, or applying this product, read and understand all the product's Safety Data Sheets. For a copy of the SDS, contact Bonstone Materials at (800) 425-2214.

Warranty

This product's warranty is limited to replacement of defective material and freight charges to destination only. Bonstone Materials. is not responsible for consequential damages.



Technical Data Sheet

Testina	Data

<u>Strengths</u>	Results	Test Method
Tensile	Warp: 100 tex Welf: 204 tex	Not available
Compressive	Not available	Not available
Flexural	Not available	Not available
<u>Modulus</u>		
Tensile	Not available	Not available
Compressive	Not available	Not available
Flexural	Not available	Not available
Elongation: Tensile: Elongation at break	Not available	Not available
Shore D	Not available	Not available
Heat Distortion Temp	Not available	Not available
Shear Strength	Not available	Not available
24 Hour Water Absorption	Not available	Not available
Other	NA	

