

Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 1 / 10

Safety Data Sheet

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

1. Identification

1.1. Product identifier

Product name Permabond 130 UV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Identified Uses Industrial **Professional** Consumer Use

1.3. Details of the supplier of the safety data sheet

Permabond Engineering Adhesives Full address Niederkasseler Lohweg 18 40547 Düsseldorf **District and Country** Germany +44 (0)1962 711 661 Tel.

e-mail address of the competent person responsible for the Safety Data Sheet

Permahond I CC Supplier:

14 Robinson Street Pottstown, PA 19464, USA tel 732-868-1372 OR 800-640-7599

www. permabond.com

info.europe@permabond.com

Chemical™ Concepts Our expertise is your solution. chemical-concepts.com 800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

1.4. Emergency telephone number

For urgent inquiries refer to Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport: CHEMTREC 800-424-9300 (toll free) or 1-703-741-5970

2. Hazards identification

2.1. Classification of the substance or mixture

Classification and Hazard Statement Flammable liquid, category 4 Eye irritation, category 2 Skin irritation, category 2

Specific target organ toxicity - single exposure,

category 3

Skin sensitization, category 1

Hazard pictograms:

Combustible liquid. Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation.

May cause an allergic skin reaction.



Signal words: Warning

Hazard statements:

H227 Combustible liquid.

Causes serious eye irritation. H319 H315 Causes skin irritation.

H335 May cause respiratory irritation. H317 May cause an allergic skin reaction.

Precautionary statements:

Prevention:



Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 2 / 10

2. Hazards identification .../>>

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapors or aerosols.

P280 Wear protective gloves / eye protection / face protection.

P271 Use only outdoors or in a well-ventilated area.
P264 Carefully wash the contaminated skin after use.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P312 Call a POISON CENTER / doctor / . . . / if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: use dry powder, dry sand or dry earth to extinct.

P363 Wash contaminated clothing before reuse.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of the product according to current regulations.

2.2. Other hazards

No other hazards known.

3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification:

ethyl 2-cyanoacrylate

NDEX 607-236-00-9 60 ≤ x < 100 Flammable liquid, category 4 H227, Eye irritation, category 2 H319, Skin

irritation, category 2 H315, Specific target organ toxicity - single exposure,

category 3 H335

EC 230-391-5 CAS 7085-85-0

REACH Reg. 01-2119527766-29-XXXX

PHENYL BIS(2,4,6-TRIMETHYLBENZOYL)-PHOSPHINEOXIDE

 $0.1 \le x < 1$ Skin sensitization, category 1 H317

EC 423-340-5 CAS 162881-26-7

REACH Reg. 01-2119900459-37-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

^{*} There is a batch to batch variation.





Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 3 / 10

4. First-aid measures .../>>

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available



Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 4 / 10

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

USA CAL/OSHA-PEL California Division of Oc

California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits

(PELs).

ethyl 2-cyanoacrylate													
Threshold Limit Value													
Type	Country	TWA/8h		STEL/15	min	Remarks / Observations							
		mg/m3	ppm	mg/m3	ppm								
CAL/OSHA	USA	1.02	0.2										

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing. EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance Colour Odour		liquid yellow punge	ent			Information			
Odour threshold	not available not available					Reason for missing data:substance/mixture is			
рН		HOL AV	allable			non-soluble	ing data.sub:	water)	
Melting point / freezing point		not ap	plicable				`	,	
Initial boiling point	>	100	°C	(212 °F)					
Boiling range		not av	ailable						
Flash point		83	°C		(181,4 °F)				
Evaporation rate		not av	ailable						
Flammability		not av	ailable						
Lower inflammability limit		not av	ailable						
Upper inflammability limit		not av	ailable						
Lower explosive limit		not av	ailable						
Upper explosive limit		not av	ailable						
								@EPY 11 5 2 - SDS 1004 1	



Permabond 130 UV

mBar

not available

Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 5 / 10

Temperature: 25 °C

9. Physical and chemical properties

Vapour pressure ~0.6 Vapour density not available

Relative density

Solubility not available Partition coefficient: n-octanol/water not available Auto-ignition temperature not available Decomposition temperature not available Viscosity not available Explosive properties not available

Oxidising properties 9.2. Other information

Information not available

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Strong reducing and oxidizing agents.

10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Ε



Permabond Engineering Adhesives

Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 6 / 10

11. Toxicological information .../>>

PHENYL BIS(2,4,6-TRIMETHYLBENZOYL)-PHOSPHINEOXIDE LD50 (Oral): > 2000 mg/kg LD50 (Dermal): > 2000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

PHENYL BIS(2,4,6-TRIMETHYLBENZOYL)-PHOSPHINEOXIDE

LC50 - for Fish > 9 mg/l/96h OECD 203

EC50 - for Crustacea > 1175 mg/l/48h OECD 201

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available



Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 7 / 10

12. Ecological information .../>>

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR EXEMPT ADR / RID-

IMDG: IMDG CODE EXEMPT

IATA: 3334

14.2. UN proper shipping name

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: AVIATION REGULATED LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR EXEMPT ADR / RID:

IMDG CODE EXEMPT IMDG:

IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: Ш

14.5. Environmental hazards

ADR EXEMPT ADR / RID:

IMDG: IMDG CODE EXEMPT

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: -Limited Quantities: -Tunnel restriction code: -

Special provision: -

IMDG: EMS: -Limited Quantities: -

IATA: Maximum quantity: 450 L Packaging instructions: 964 Cargo: Packaging instructions: 964

Passengers: Maximum quantity: 450 L

Special provision:

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant



Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 8 / 10

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

No component(s) listed.

Minnesota:

No component(s) listed.

New Jersey:

7085-85-0 ethyl 2-cyanoacrylate

New York:



Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 9 / 10

15. Regulatory information .../>>

No component(s) listed.

Pennsylvania:

No component(s) listed.

California:

No component(s) listed.

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H227 Combustible liquid.

H319 Causes serious eye irritation. **H315** Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

E١



Permabond Engineering Adhesives

Permabond 130 UV

Revision nr.1 Dated 11/2/2023 First compilation Printed on 11/2/2023 Page n. 10 / 10

16. Other information .../>>

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

