



SG400 Mixed 10:1

SafetyDataSheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 9/14/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : SG400 Mixed 10:1
Product code : JD-sg400

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives, binding agents
Recommended use : Adhesives, sealants

1.3. Supplier

Manufacturer

IPS ADHESIVES
600 ELLIS ROAD
DURHAM
NC 27703-6015, USA

1.4. Emergency telephone number

Emergency number : 800-255-3924 (Domestic) +1-813-248-0585 (International)
VelocityEHS: 24 hrs/7 days

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H335 - May cause respiratory irritation

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
METHYL METHACRYLATE	CAS-No.: 80-62-6	≥ 50 – < 75	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-METHYLPROPENOIC ACID	CAS-No.: 79-41-4	≥ 1 – < 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314
PARAFFIN WAX	CAS-No.: 8002-74-2	< 1	Not classified
2-HYDROXYETHYL METHACRYLATE	CAS-No.: 868-77-9	< 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
2,6-DI-TERT-BUTYL-P-CRESOL	CAS-No.: 128-37-0	< 1	STOT RE 2, H373

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If eye irritation persists: Get medical advice/attention.

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting because of corrosive effects.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SG400 Mixed 10:1	
No additional information available	
METHYL METHACRYLATE (80-62-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	
ACGIH OEL TWA [ppm]	Methyl methacrylate
ACGIH OEL STEL [ppm]	50 ppm
Remark (ACGIH)	100 ppm
	TLV® Basis: URT & eye irr; body weight eff; pulm edema. Notations: DSEN; A4 (Not classifiable as a Human Carcinogen)
Regulatory reference USA - OSHA - Occupational Exposure Limits	ACGIH 2023
Local name OSHA PEL (TWA) [1] OSHA PEL (TWA) [2] Regulatory reference (US-OSHA)	
	Methyl methacrylate
	410 mg/m ³
	100 ppm
	OSHA Annotated Table Z-1
2-HYDROXYETHYL METHACRYLATE (868-77-9)	
No additional information available	
PARAFFIN WAX (8002-74-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	
ACGIH OEL TWA	Paraffin wax fume
Remark (ACGIH)	2 mg/m ³
Regulatory reference	TLV® Basis: URT irr; nausea
	ACGIH 2023

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-METHYLPROPENOIC ACID (79-41-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Methacrylic acid
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: Skin & eye irr
Regulatory reference	ACGIH 2022

2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	
ACGIH OEL TWA	Butylated hydroxytoluene
Remark (ACGIH)	2 mg/m³ (IFV - Inhalable fraction and vapor)
Regulatory reference	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
	ACGIH 2022

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection: Protective gloves
Eye protection: Safety glasses
Skin and body protection: Wear suitable protective clothing
Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Mixture contains one or more component(s) which have the following colour(s):
Colorless. white Clear, colourless Colourless to slightly yellowish
Odor : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour:
Acrid Barely perceptible odour Ester-like

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold	: No data available :
pH	No data available :
Melting point	Not applicable : No
Freezing point	data available : No
Boiling point	data available : No
Flash point	data available : No
Relative evaporation rate (butyl acetate=1)	data available : Not
Flammability (solid, gas)	applicable. : No data
Vapor pressure	available : No data
Relative vapor density at 20°C	available : No data
Relative density	available : No data
Solubility	available : No data
Partition coefficient n-octanol/water (Log Pow)	available : No data
Auto-ignition temperature	available : No data
Decomposition temperature	available : No data
Viscosity, kinematic	available : No data
Viscosity, dynamic	available : No data
Explosion limits	available : No data
Explosive properties	available : No data
Oxidizing properties	available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified :
Acute toxicity (dermal)	Not classified :
Acute toxicity (inhalation)	Not classified

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHYL METHACRYLATE (80-62-6)	
LD50 oral rat	> 5000 mg/kg
LD50 oral	29.8 mg/l 4hrs
LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE US (oral)	31.568 mg/kg body weight
2-HYDROXYETHYL METHACRYLATE (868-77-9)	
LD50 oral rat	5564 mg/kg body weight Animal: rat, Guideline: other:
LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Animal sex: male
LD50 dermal	> 3000 mg/kg
ATE US (oral)	5564 mg/kg body weight
2-METHYLPROPENOIC ACID (79-41-4)	
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
LD50 oral rat	> 2930 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
METHYL METHACRYLATE (80-62-6)	
IARC group	3 - Not Classifiable
2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
NOAEL (chronic,oral,animal/male,2 years)	25 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: toxicity (migrated information)
IARC group	3 - Not Classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
METHYL METHACRYLATE (80-62-6)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
2-HYDROXYETHYL METHACRYLATE (868-77-9)	
LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
LOAEL (oral, rat, 90 days)	100 mg/kg body weight Animal: rat, Animal sex: male

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
NOAEL (oral,rat,90 days)	25 mg/kg body weight Animal: rat, Animal sex: male
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

METHYL METHACRYLATE (80-62-6)	
Viscosity, kinematic	0.561 mm ² /s

Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

METHYL METHACRYLATE (80-62-6)	
LC50 - Fish [1] EC50 - Crustacea [1] EC50	> 79 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
72h - Algae [1]	69 mg/l Test organisms (species): Daphnia magna > 110 mg/l Test organisms (species):
	Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

2-HYDROXYETHYL METHACRYLATE (868-77-9)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes 380 mg/l Test organisms
EC50 - Crustacea [1]	(species): Daphnia magna 380 mg/l 836 mg/l Test organisms (species):
EC50 - Other aquatic organisms [1]	Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [1]	345 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	49.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d' 24.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	
NOEC (chronic)	

2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
LC50 - Fish [1]	> 0.57 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	0.48 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	0.48 mg/l Aquatic invertebrates
EC50 72h - Algae [1]	> 0.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
ErC50 algae	0.758 mg/l
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.023 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.053 mg/l Test organisms (species): Oryzias latipes Duration: '42 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)	
Bioconcentration factor (BCF REACH)	598
Partition coefficient n-octanol/water (Log Pow)	5.2

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA no. : UN1133 :
UN-No. (TDG) UN1133 :
UN-No. (IMDG) 1133 :
UN-No. (IATA) 1133

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Adhesives :
Proper Shipping Name (TDG) ADHESIVES :
Proper Shipping Name (IMDG) ADHESIVES :
Proper Shipping Name (IATA) Adhesives

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



TDG

Transport hazard class(es) (TDG) : 3

Hazard labels (TDG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3

Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : II

Packing group (IMDG) : II

Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1133

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (t_r - t_f)$ Where: t_r is the maximum mean bulk temperature during transport, and t_f is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 :
DOT Packaging Non Bulk (49 CFR 173.xxx) 173 :
DOT Packaging Bulk (49 CFR 173.xxx) 242 :
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

UN-No. (TDG) : UN1133
Explosive Limit and Limited Quantity Index : 5 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L
Emergency Response Guide (ERG) Number : 128

IMDG

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B
Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provision (IATA) : A3
ERG code (IATA) : 3L

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

METHYL METHACRYLATE	CAS-No. 80-62-6	≥ 50 – < 75%
---------------------	-----------------	--------------

METHYL METHACRYLATE (80-62-6)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

METHYL METHACRYLATE (80-62-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2-HYDROXYETHYL METHACRYLATE (868-77-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

PARAFFIN WAX (8002-74-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2-METHYLPROPENOIC ACID (79-41-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

National regulations

METHYL METHACRYLATE (80-62-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2-HYDROXYETHYL METHACRYLATE (868-77-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SG400 Mixed 10:1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PARAFFIN WAX (8002-74-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2-METHYLPROPENOIC ACID (79-41-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2,6-DI-TERT-BUTYL-P-CRESOL (128-37-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H225	Highly flammable liquid and vapor Harmful if swallowed Harmful in
H302	contact with skin Causes severe skin burns and eye damage Causes
H312	skin irritation May cause an allergic skin reaction Causes serious eye
H314	damage Causes serious eye irritation May cause respiratory irritation
H315	May cause damage to organs through prolonged or repeated exposure
H317	
H318	
H319	
H335	
H373	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006