

PRODUCT DATA SHEET GL13B SERIES

COEX GLUELESS PROTECTIVE FILM

General Product Description:

The GL13B series provides a light tack of 4-6 Oz/inch and is designed for application on glass, PMMA (Plexiglass®), polished metals or other glossy surfaces. Multi-layer coextruded protective film contains inhibitors to provide extended UV protection for up to 3 months. Polyolefin blend contains high strength resins for improved strength and puncture resistance. Glueless adhesive technology is absolutely safe to use and eliminates any worry about adhesive transfer or ghosting. Different from conventional adhesive systems, this film is 100% recyclable (♻️ 4) The film is tinted blue. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. The user should determine whether the product is fit for purpose and is suitable for the user's method of application before use.

Product Properties:

Film:

Material	Polyolefin Blend
Color	Blue (Tinted)
UV Resistance	90-days

Film Gauge:

ASTM D-1000	1.3 mil
-------------	---------

Puncture Resistance:

Dart D1709	120 g
------------	-------

Tensile Strength:

D882 (MD)	> 2000 PSI
-----------	------------

Elongation (at break):

D882 (MD)	150 %
-----------	-------

Adhesive Type:

Type	Glue-less
------	-----------

Adhesion Properties:

PSTC-1 metal	4 - 6 oz/in
--------------	-------------

Notice to Buyers:

Except as otherwise provided herein, the quality shall be in accordance with the seller's specifications. Final determination of the suitability of the use contemplated by the buyer is the SOLE RESPONSIBILITY OF THE BUYER, and the seller shall have no responsibility in connection with such suitability.