

## PRODUCT DATA SHEET GL18C SERIES

### COEX GLUELESS PROTECTIVE FILM

#### General Product Description:

The GL18C series protective film features a medium to high tack and is designed for application on smooth surfaces like smooth metals, plastics and painted surfaces. Multi-layer Co-Extruded film contains high strength resins for improved strength and puncture resistance. A UV inhibitor offers 60-day UV protection. Glueless adhesive technology is absolutely safe to use and eliminates any worry about adhesive transfer or ghosting. Different from conventional adhesive based products, this film is 100% recyclable (♻️ 4) Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. The user should determine whether the product is fit for purpose and is suitable for the user's method of application before use.

#### Product Properties:

##### Film:

Material	Polyolefin Blend
Color	Clear
UV Resistance	60-days

##### Film Gauge:

ASTM D-1000	1.8 mil
-------------	---------

##### Puncture Resistance:

Dart D1709	180 g
------------	-------

##### Tensile Strength:

D882 (MD)	> 2600 PSI
-----------	------------

##### Elongation (at break):

D882 (MD)	250 %
-----------	-------

##### Adhesive Type:

Type	Glue-less
------	-----------

##### Adhesion Properties:

PSTC-1 metal	8 - 10 oz/in
--------------	--------------

#### Notice to Buyers:

Except as otherwise provided herein, the quality shall be in accordance with the seller's specifications. Final determination of the suitability of the use contemplated by the buyer is the SOLE RESPONSIBILITY OF THE BUYER, and the seller shall have no responsibility in connection with such suitability.