

**SECTION 1. IDENTIFICATION**

Product name	:	Sika® Primer-215
Company name	:	Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids	:	Category 2
Eye irritation	:	Category 2A
Skin sensitization	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 2

GHS label elements

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H225 Highly flammable liquid and vapor. H317 May cause an allergic skin reaction.



H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements :

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

**Other hazards**

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS
Mixtures**Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
ethyl acetate	141-78-6	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	>= 30 - < 50
butanone	78-93-3	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	>= 10 - < 20
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	Not Assigned	Skin Sens. 1A; H317	>= 5 - < 10
n-butyl acetate	123-86-4	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5 - < 10
Aromatic Polyisocyanate-Prepolymer	68958-67-8	Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 1 - < 5
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 5
xylene	1330-20-7	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 5
ethylbenzene	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Eye Irrit. 2A; H319	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.



- Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Respiratory disorder
Allergic reactions
Excessive lachrymation
Loss of balance
Vertigo
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES



- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
Store in cool place.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : Explosives
Oxidizing agents



Poisonous gases
Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyl acetate	141-78-6	TWA	400 ppm 1,400 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,400 mg/m ³	OSHA P0
butanone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m ³	OSHA Z-1
		TWA	200 ppm 590 mg/m ³	OSHA P0
		STEL	300 ppm 885 mg/m ³	OSHA P0
		TWA	150 ppm 710 mg/m ³	OSHA Z-1
n-butyl acetate	123-86-4	TWA	150 ppm 710 mg/m ³	OSHA P0
		STEL	200 ppm 950 mg/m ³	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm	ACGIH
xylene	1330-20-7	STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
ethylbenzene	100-41-4	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm 435 mg/m ³	OSHA P0
		STEL	125 ppm 545 mg/m ³	OSHA P0
		TWA	20 ppm	ACGIH

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this



product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

- Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures** : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : liquid
- Color** : colorless
- Odor** : ester-like
- Odor Threshold** : No data available
- pH** : Not applicable substance/mixture is non-soluble (in water)
- Melting point/range / Freezing point** : No data available



Boiling point/boiling range	: 171 °F / 77 °C
Flash point	: 18 °F / -8 °C (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: Upper flammability limit 12 %(V)
Lower explosion limit / Lower flammability limit	: Lower flammability limit 2 %(V)
Vapor pressure	: ca. 60 hpa
Relative vapor density	: No data available
Density	: ca. 1 g/cm ³ (68 °F / 20 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: 333 °C
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 7 mm ² /s (104 °F / 40 °C)
Explosive properties	: No data available
Oxidizing properties	: No data available
Volatile organic compounds (VOC) content	: 661.1 g/l

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.



Incompatible materials : No data available

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

butanone:

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

**ethylbenzene:**

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
-------------	---	----------

OSHA Not applicable**NTP** Not applicable**Reproductive toxicity**

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Exposure time: 96 h
------------------	---	---



Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

n-butyl acetate:

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l

Aromatic Polyisocyanate-Prepolymer:

Toxicity to microorganisms : EC50 (Natural microorganism): > 10,000 mg/l
Method: OECD Test Guideline 209
Remarks: Information taken from reference works and the literature.

xylene:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2.2 mg/l
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia): 1.17 mg/l
Exposure time: 7 d

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 1866
 Proper shipping name : Resin solution
 Class : 3
 Packing group : II
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 364
 Packing instruction (passenger aircraft) : 353

IMDG-Code

- UN number : UN 1866
 Proper shipping name : RESIN SOLUTION
 Class : 3
 Packing group : II
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Domestic regulation

49 CFR

- UN/ID/NA number : UN 1866
 Proper shipping name : Resin solution
 Class : 3
 Packing group : II
 Labels : FLAMMABLE LIQUID
 ERG Code : 127
 Marine pollutant : no

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.



Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)
xylene	1330-20-7	100

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Specific target organ toxicity (single or repeated exposure)
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylene	1330-20-7	>= 1 - < 5 %
ethylbenzene	100-41-4	>= 0.1 - < 1 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

xylene	1330-20-7	>= 1 - < 5 %
--------	-----------	--------------

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including ethylbenzene, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
OSHA P0 / TWA : 8-hour time weighted average



OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 04/05/2022

000000019845
US / Z8



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006