



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

SECTION 1. IDENTIFICATION

Product name : SikaBiresin® AP017 (Formerly P-17) Part A

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.



SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)


Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity (Inhalation) : Category 1A

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer by inhalation.



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Precautionary Statements

:

Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash skin thoroughly after handling.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/ attention.
- P332 + P313 If skin irritation occurs: Get medical advice/ attention.
- P337 + P313 If eye irritation persists: Get medical advice/ attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

Disposal:

- P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration \geq 1%.

Other hazards

None known.



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Talc	14807-96-6		>= 50 - < 70
vinyltoluene	25013-15-4	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Asp. Tox. 1; H304	>= 10 - < 20
barium sulfate	7727-43-7		>= 1 - < 5
Quartz (SiO ₂) >5µm	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
May cause cancer by inhalation.
irritant effects
Excessive lachrymation



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Erythema
Dermatitis

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
- Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapors or spray mist.



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Avoid exceeding the given occupational exposure limits (see section 8).
 Do not get in eyes, on skin, or on clothing.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharge.
 Open drum carefully as content may be under pressure.
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
 Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.
 Keep in a well-ventilated place.
 Observe label precautions.
 Store in accordance with local regulations.

Materials to avoid : Explosives
 Oxidizing agents
 Poisonous gases
 Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
vinyltoluene	25013-15-4	TWA	100 ppm 480 mg/m ³	OSHA Z-1
		TWA	100 ppm 480 mg/m ³	OSHA P0
barium sulfate	7727-43-7	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (total)	15 mg/m ³	OSHA Z-1



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

		dust)		
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
Quartz (SiO ₂) >5µm	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
 The engineering controls also need to keep gas, vapor or



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

dust concentrations below any lower explosive limits.

Personal protective equipment

- Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures** : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : paste
- Color** : various
- Odor** : pungent
- Odor Threshold** : No data available
- pH** : Not applicable
- Melting point/ range / Freezing point** : No data available
- Boiling point/boiling range** : 338 °F / 170 °C



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Flash point	:	ca. 127 °F / 53 °C (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	2 hpa
Relative vapor density	:	No data available
Density	:	1.59 - 2.13 g/cm ³ (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	8 g/l Part A + Valspar Cream Hardener BPO Part B Combined. 8 g/l Part A + AP017 Reducer Part A + Valspar Cream Hardener BPO Part B Combined.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans	
	Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
OSHA	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide (> 10 µm)	13463-67-7
OSHA	OSHA specifically regulated carcinogen	
	Talc (Mg ₃ H ₂ (SiO ₃) ₄) (crystalline silica)	14807-96-6
OSHA	OSHA specifically regulated carcinogen	
	Quartz (SiO ₂) (crystalline silica)	14808-60-7

NTP Known to be human carcinogen



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Quartz (SiO₂)
(Silica, Crystalline (Respirable Size))

14808-60-7

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks

: Titanium dioxide (13463-67-7)
In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Domestic regulation

49 CFR

UN/ID/NA number : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID
ERG Code : 127
Marine pollutant : no

DOT: As per 49CFR 173.150 (f) Combustible Liquid Exception, Material is Not Regulated.
IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Carcinogenicity
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Talc, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 01/03/2025



SikaBiresin® AP017 (Formerly P-17) Part A

Revision Date 01/03/2025

Print Date 01/07/2025

100000056511
US / Z8



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006